

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	2909	2.27	0.00	0.0%	54.37	54.37
0.50	2792	8.56	146.20	71.2%	59.21	205.41
1.00	2724	14.85	285.28	80.0%	71.17	356.45
1.50	2656	21.15	417.24	82.2%	90.25	507.49
2.00	2588	27.44	542.09	82.3%	116.44	658.53
2.50	2520	33.73	659.82	81.5%	149.75	809.56
3.00	2452	40.03	770.43	80.2%	190.18	960.60
3.50	2384	46.32	873.92	78.6%	237.72	1111.64
4.00	2316	52.61	970.30	76.8%	292.38	1262.68
4.50	2248	58.90	1059.55	74.9%	354.16	1413.72
5.00	2180	65.20	1141.69	73.0%	423.06	1564.75
5.50	2113	71.49	1216.72	70.9%	499.08	1715.79
6.00	2045	77.78	1284.62	68.8%	582.21	1866.83
6.50	1977	84.08	1345.41	66.7%	672.46	2017.87
7.00	1909	90.37	1399.08	64.5%	769.83	2168.91
7.50	1841	96.66	1445.64	62.3%	874.31	2319.95
8.00	1773	102.96	1485.07	60.1%	985.91	2470.98
8.50	1705	109.25	1517.39	57.9%	1104.63	2622.02
9.00	1637	115.54	1542.59	55.6%	1230.47	2773.06
9.50	1569	121.84	1560.67	53.4%	1363.42	2924.10
10.00	1501	128.13	1571.64	51.1%	1503.50	3075.14
10.50	1433	134.42	1575.49	48.8%	1650.69	3226.17
11.00	1365	140.72	1572.22	46.6%	1804.99	3377.21
11.50	1297	147.01	1561.83	44.3%	1966.42	3528.25
12.00	1229	153.30	1544.33	42.0%	2134.96	3679.29
12.50	1161	159.60	1519.70	39.7%	2310.62	3830.33
13.00	1093	165.89	1487.96	37.4%	2493.40	3981.36
13.50	1025	172.18	1449.11	35.1%	2683.29	4132.40
14.00	957	178.48	1403.13	32.8%	2880.31	4283.44
14.50	889	184.77	1350.04	30.4%	3084.44	4434.48
15.00	821	191.06	1289.83	28.1%	3295.68	4585.52