


Wiring Diagram

	P1		P2		P3		P4
20mm Twisted	1	Red	1	} 20mm Twisted	1	Red	1
	2	Black	2		2	Black	2
	3	White	3				
	4	Green	4				
20mm Twisted	4	Blue	5				
	5	Yellow	6				
	6	Purple	7				
20mm Twisted	7	Brown	8				

Electrical Test

- HIPOT TEST: DC 300V.
- INSULATION RESISTANCE: 10M OHM/MIN.
- CONDUCTIVE RESISTANCE: 3 OHM/MAX .
- 100% OPEN SHORT & MISWIRE TEST.

5	DC connector	5.5*2.1 female, Black	1 PC
4	DC connector	5.5*2.1 male, Black	1 PC
3	Over moulding	Moulding 45P PVC, Black	1 PC
2	RJ45 connector	8P/8C, Gold plated 3U', Black	2 PC
1	Cable	NOUL cable 28AWG*8C+22AWG*2C, OD: 6.5mm, Black TPU	1 PC
NO.	PART NAME	DESCRIPTION	Q'TY

<i>X.±</i>	<i>°X.±</i>	UNITS: MM	NAME:(INTEND USE)		SCALE	SHEET	REV.
<i>.X±</i>	<i>°X±</i>	MAT'L	PART NO:		TITLE:		
<i>.XX±</i>	<i>°XX±</i>		APPD:	RJ45 CABLE			
<i>.XXX±</i>	<i>°XXX±</i>	FINISH	CHKD:	DWG NO:			
		Q'TY	DR:	CUSTOMER NO:			
			Kevin 27.03.2014	COMARK ELECTRONICS CO., LTD.			

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF COMARK ELECTRONICS FACTORY AND SHALL NOT BE REPRODUCED. COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF COMARK ELECTRONICS CO., LTD.