

# LED Tube Light Specification



	Model No	T8E12W288V2002	T8E12N288V2005	T8E12D288V2008
<b>Optical Parameter</b>	LED Source	SMD3528,288PCS	SMD3528,288PCS	SMD3528,288PCS
	Luminous Flux (lm)	1500-1600Lm	1600-1700Lm	1600-1700Lm
	Illuminance (lx)	410lx	420lx	420lx
	Color Temperature (K)	2700-3500K	3500-5000K	5000-7000K
	Color Rendering Index	≥ 75	≥ 75	≥ 75
	Beam Angle	180°	180°	180°
	Life Span (hrs)	≥ 50000 H	≥ 50000 H	≥ 50000 H
<b>Electrical Parameter</b>	Input Voltage (V)	AC85-265V	AC85-265V	AC85-265V
	Frequency (Hz)	50/60HZ	50/60HZ	50/60HZ
	LED Power Consumption (W)	18±1W	18±1W	18±1W
	Power Factor (PF)	>0.96	>0.96	>0.96
<b>Structure Parameter</b>	Materials and processes	PC frosted cover	PC frosted cover	PC frosted cover
	Dimensions (MM)	Φ26×1212mm	Φ26×1212mm	Φ26×1212mm
	Base	G13	G13	G13
	Net Weight	508g	508g	508g
	Proof Rate	IP54	IP54	IP54