

Shenglu SLT5041XYCE2&SLT5042XYCE2 enhanced cash-in-transit (Dual rear wheels)



SLT5041XYCE2



SLT5042XYCE2

Specification

Chassis :JX1049DL2 (second-class)		Fuel Consumption (L/100km)	≤9
Wheel-Drive	4*2	Displacement (L)	2.8
Dimension (L*W*H) (mm)	5810*2096*2300	Engine JX493ZLQ3	
		supercharged diesel engine	
Cash Cabin Volume (m ³)	5.0	Emission	State III
Wheel Base (mm)	3570	Max. Power (kW/r/min)	85/3600
Tread F/R (mm)	1700/1645	Seats	5
Curb Weight (kg)	2800	Min. ground clearance (mm)	160
Max. total mass (kg)	4000	Min. Turning Diameter (m)	13.8
Load Capacity (kg)	1200	Max. Speed (km/h)	≥110

Configuration

- Front ballistic windshield
- Power steering
- Central controlled door locking system
- Front and rear ram bumpers
- Aluminum cash cabin
- Fire extinguisher
- Ballistic glass for side windows (Light SPC material)
- Remote alarm, anti-theft and anti-hijacking system
- A 3-way, 4-tapered end lock and two cross locks on cash cabin door
- Driver and Co-driver's ballistic window glass (Light SPC material)
- One big size gun port wase mounted in the bottom of each side of the escort cabin windows.
- One lift shot port (delivery hole) was mounted in each side of the driver cabin.
- Observation window on the side sliding door
- LCD dual monitoring system(inner cash cabin is black&white monitor,the other one on the back of the vehicle is chromatic color)
- Color : White
- Radio/CD player
- Air-conditioning system
- Power sunroof
- Fuse assembly