

## FSC-C037 Closure

### Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C

[www.youfibercable.com](http://www.youfibercable.com)

### Description

1. One kinds of elastic ring provided: Ø15mm. Ø15 can be shrunk till Ø7.
2. The fittings provided with FSC-C037: 2pcs of special wrench, earthing wire, nylon tie, labeling paper, desiccant, 4 pieces of elastic ring, 4 pieces of plastic gaskets.
3. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for bunchy fiber, 1 piece metal hoop.

### Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-C036I (bunchy)	288x178	24	4	16mm	OFST with 8 cores(1~3pcs of OFST 036)
FSC-C037II (bunchy)	mm	48			OFST with 12 cores(1~4pcs of OFST 037)

### Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC