

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. The installation accessories provided: seal tape, insulation tape, 3 pieces of special wrenches, hanging hook, abrasive cloth, earthing wire, nylon tie, labeling paper, measuring paper, desiccant.
2. Accessories for customers' selection: earthing deriving device, buffer tube for ribbon or bunchy fiber.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-A016I (bunchy)	400x185x 90mm	64	6	4X13mm 2X16mm	OFST with 16 cores(1~4pcs of OFST 016)
FSC-A024II (bunchy)		96			OFST with 24cores(1~4pcs of OFST 024)
FSC-A017III (ribbon)		144			OFST with 36cores(1~4pcs of OFST 017)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC