

## FSC-A018 Closure

### Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



[www.youfibercable.com](http://www.youfibercable.com)

### Description

1. The installation accessories provided: seal tape, insulation tape, 3 pieces of special wrenches, hanging hook, abrasive cloth, earthing wire, nylon tie, labeling paper, measuring paper, desiccant.
2. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for ribbon or bunchy fiber.

### Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-A018I (bunchy)	455x220x 132mm	96	6	2X23mm 2x20mm 2X16mm	OFST with 12 cores(1~8pcs of OFST 018)
FSC-A002II (bunchy)		144			OFST with 24cores(1~6pcs of OFST 002)
FSC-A004III (ribbon)		288			OFST with 72cores(1~4pcs of OFST 004)

### Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC