

FSC-E032 PLC Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. FSC-E031 accommodates one set of elastic seal fitting for 6 inlet/outlet ports.
2. Installation accessories provided: seal tape, insulation tape, 2pcs of special wrenches, abrasive cloth, earthing wire, nylon ties, labeling paper, measuring paper and desiccant.
3. Accessories by customers' selection: earthing device, buffer pipe, pressure testing valve, adapter panel, adapter, pigtail, patchcord, wall-mounting bracket and pole mounting bracket.

Parameter

Model	Size	Unit	Optical Fiber Splice Tray(OFST)	Total Cores
FSC-E032 I PLC	510x 250 mm	Set	OFST with 1pcs 1x16 PLC or 2pcs 1x8 PLC Splitter	1~2
FSC-E032 II Bunchy		Set	OFST with 12 cores(1~14pcs of OFST 031 tray	168

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC