



Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor,Guaner yongtai building no.810 chongyun road,yongping street,
 baiyun district,guangzhou city,guangdong china.
 Tel: 86 20 66656962 Web: www.liwin.en.alibaba.com www.liwin-china.com
 whatsapp/wechat:8615920871181 Sky: davi.ke
 Email: liwinchina@liwin-china.com Company Email: liwinchina@liwin-china.com
 Kirby Ke (General Manager) Mobile: +86 15920871181

LED Bar Lights (Mini Order: 1 cart)

Specifications	Part no.	LED Qty Dimentions	Photos
L15X curved Series/4D (3W/PC)			
* 10W/pcs USA CREE Operating Voltage: 10-30V DC * Waterproof rate: IP67 Color Temperature: 6000K * Beam: Spot/ Flood/ Combo Body Color: Black/white(No stock) Shell material:Aluminum alloy spraying Fitting screw: 304 stainless steel Lens material:PC * 30000 hours above life time * Yellow/white light out of the three lines, pure white light out of the second line	L15X-120W	12pcs*10w 21.9 inch	
	L15X-150W	15pcs*10w 27.2 inch	
	L15X-180W	18pcs*10w 32.6 inch	
	L15X-210W	21pcs*10w 37.9 inch	
	L15X-240W	24pcs*10w 43.2 inch	
	L15X-270W	27pcs*10w 48.5 inch	
L15X-300W	30pcs*10w 53.8 inch		
L14X curved Series-3D/4D/5D (5W/PC ETI)			
* Operating Voltage: 10-30V DC * Current draw change with your working * Voltage and power * Waterproof rate: IP 67 * Color Temperature: 6000K * Beam: Spot/ Flood/ Combo * Body Color: Black, * Material: Diecast aluminum housing * Lens material:PC * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L14X-90W	18pcs*5w 18 inch	
	L14X-120W	24pcs*5w 24 inch	
	L14X-150W	30pcs*5w 30 inch	
	L14X-180W	36pcs*5w 35.5 inch	
	L14X-210W	42pcs*5w 41.5 inch	
	L14X-240W	48pcs*5w 47.5 inch	
L11X curved Series/5D (5W/PC)			
* 5W/PC Osram LED * Operating Volt:9-32V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L11X-200WO-4D	40pcs*5w 21.5 inch	
	L11X-300WO-4D	60pcs*5w 31.5 inch	
	L11X-400WO-4D	80pcs*5w 41.5 inch	
	L11X-500WO-4D	100pcs*5w 51.5 inch	
L11X curved Series-4D/5D (3W/PC cree)			
* 3W/PC LED * Operating Volt:9-32V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L11X-72W-4D	24pcs*3w 13.5 inch	
	L11X-120W-4D	40pcs*3w 21.5 inch	
	L11X-180W-4D	60pcs*3w 31.5 inch	
	L11X-240W-4D	80pcs*3w 41.5 inch	
	L11X-288W-4D	96pcs*3w 50 inch	
	L11X-300W-4D	100pcs*3w 51.5 inch	
L11X-312W-4D	104pcs*3w 53 inch		
L5X curved Series (10W/PC)			
* 10W/PC Cree LED * Operating Volt:9-32V DC * 950±50LM each LED * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L5X-60W	6pcs*10w 13.5 inch	
	L5X-100W	10pcs*10w 21.5 inch	
	L5X-140W	14pcs*10w 31.5 inch	
	L5X-200W	20pcs*10w 41.5 inch	
	L5X-240W	24pcs*10w 50 inch	
L4X curved Series (3W/PC)			
* 3W/PC LED * Operating Volt:9-32V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L4X-72W	24pcs*3w 13.5 inch	
	L4X-120W	40pcs*3w 21.5 inch	
	L4X-180W	60pcs*3w 31.5 inch	
	L4X-240W	80pcs*3w 41.5 inch	
	L4X-288W	96pcs*3w 50 inch	
	L4X-300W	100pcs*3w 51.5 inch	