



# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)

Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: [davi.ke](mailto:davi.ke)

Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)

Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
1.5W/PCS				
L25B Series (1.5W/PC four row)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-32V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L25B-132W	132pcs*1.5W 21 inch	4 pcs/ctn	
	L25B-212W	212pcs*1.5W 31 inch	4 pcs/ctn	
	L25B-292W	292pcs*1.5W 41 inch	4 pcs/ctn	
	L25B-356W	356pcs*1.5W 50 inch	4 pcs/ctn	
	L25B-372W	372pcs*1.5W 51.5 inch	4 pcs/ctn	
3W/PCS				
L30 Series (3W/PC three row CREE)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-30V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L30-36W	12pcs*3W 4 inch	40 pcs/ctn	
	L30-72W	24pcs*3W 5.2 inch	20 pcs/ctn	
	L30-288W	96pcs*3W 20 inch	6 pcs/ctn	
	L30-360W	120pcs*3W 25 inch	6 pcs/ctn	
	L30-432W	144pcs*3W 30 inch	6 pcs/ctn	
L29 Series (3W/PC three row CREE)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-30V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L29-216W	72pcs*3W 15 inch	6 pcs/ctn	
	L29-324W	108pcs*3W 20 inch	6 pcs/ctn	
	L29-459W	153pcs*3W 30 inch	4 pcs/ctn	
	L29-594W	198pcs*3W 40 inch	4 pcs/ctn	
L26 Series (3W/PC three row CREE)				
<ul style="list-style-type: none"><li>* Operating Voltage: 10-30V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L26-180W	60pcs*3W 16.5 inch	6 pcs/ctn	
	L26-288W	96pcs*3W 24.5 inch	4 pcs/ctn	
	L26-423W	141pcs*3W 34.5 inch	4 pcs/ctn	
	L26-558W	186pcs*3W 44.5 inch	4 pcs/ctn	
	L26-666W	222pcs*3W 52.5 inch	4 pcs/ctn	
L25 Series (3W/PC four row)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-32V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L25-54W	18pcs*3W 4 inch	40 pcs/ctn	
	L25-108W	36pcs*3W 6.5 inch	6 pcs/ctn	
	L25-180W	60pcs*3W 9.2 inch	6 pcs/ctn	
	L25-252W	84pcs*3W 12 inch	6 pcs/ctn	
	L25-324W	108pcs*3W 17.2 inch	6 pcs/ctn	
	L25-378W	126pcs*3W 20 inch	6 pcs/ctn	
	L25-432W	144pcs*3W 22.6 inch	4 pcs/ctn	



Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
 Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: [davi.ke](mailto:davi.ke)  
 Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
 Kirby Ke ( General Manager ) Mobile: +86 15920871181



# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: [davi.ke](mailto:davi.ke)  
Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
L8 Series-7D (3W/PC CREE) with daytime light				
<ul style="list-style-type: none"><li>* 3W/PC LED Cree</li><li>* Operating Volt:10-30V DC</li><li>* Color Temperature:6000K</li><li>* Operation temperature:-40°C~85°C</li><li>* Waterproof rate:IP67</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Mounting Bracket:Stainless steel bracket</li><li>* 30000 hours above life time</li></ul>	L8-36W-7D	12pcs*3w 7 inch	6 pcs/ctn	
	L8-72W-7D	24pcs*3 12 inch	6 pcs/ctn	
	L8-108W-7D	36pcs*3w 17 inch	6 pcs/ctn	
	L8-144W-7D	48pcs*3w 20 inch	4 pcs/ctn	
	L8-180W-7D	60pcs*3w 31 inch	4 pcs/ctn	
	L8-216W-7D	72pcs*3w 35 inch	4 pcs/ctn	
	L8-252W-7D	84pcs*3w 40 inch	4 pcs/ctn	
	L8-288W-7D	96pcs*3w 49 inch	4 pcs/ctn	
L8 Series-4D/5D (3W/PC CREE)				
<ul style="list-style-type: none"><li>* 3W/PC LED Cree</li><li>* Operating Volt:10-30V DC</li><li>* Color Temperature:6000K</li><li>* Operation temperature:-40°C~85°C</li><li>* Waterproof rate:IP67</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Mounting Bracket:Stainless steel bracket</li><li>* 30000 hours above life time</li></ul>	L8-18W-4D/5D	6pcs*3W 4 inch	40 pcs/ctn	
	L8-36W-4D/5D	12pcs*3w 7 inch	20 pcs/ctn	
	L8-54W-4D/5D	18pcs*3w 9 inch	10 pcs/ctn	
	L8-72W-4D/5D	24pcs*3 12 inch	10 pcs/ctn	
	L8-90W-4D/5D	30pcs*3 15 inch	4 pcs/ctn	
	L8-108W-4D/5D	36pcs*3w 17 inch	4 pcs/ctn	
	L8-126W-4D/5D	42pcs*3w 20 inch	4 pcs/ctn	
	L8-144W-4D/5D	48pcs*3w 23 inch	4 pcs/ctn	
	L8-180W-5D/5D	60pcs*3w 31 inch	4 pcs/ctn	
	L8-198W-5D/5D	60pcs*3w 33 inch	4 pcs/ctn	
	L8-234W-4D/5D	78pcs*3w 36 inch	4 pcs/ctn	
	L8-252W-4D/5D	84pcs*3w 40 inch	4 pcs/ctn	
	L8-288W-4D/5D	96pcs*3w 49 inch	4 pcs/ctn	
	L8-324W-4D/5D	108pcs*3w 51 inch	4 pcs/ctn	
L8 Series (3W/PC)				
<ul style="list-style-type: none"><li>* 3W/PC LED</li><li>* Operating Volt:10-30V DC</li><li>* Color Temperature:6000K</li><li>* Operation temperature:-40°C~85°C</li><li>* Waterproof rate:IP67</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Mounting Bracket:Stainless steel bracket</li><li>* 30000 hours above life time</li></ul>	L8-18W	6pcs*3W 4 inch	20 pcs/ctn	
	L8-36W	12pcs*3w 7 inch	4 pcs/ctn	
	L8-54W	18pcs*3w 9 inch	4 pcs/ctn	
	L8-72W	24pcs*3 12 inch	4 pcs/ctn	
	L8-90W	30pcs*3 15 inch	4 pcs/ctn	
	L8-108W	36pcs*3w 17 inch	4 pcs/ctn	
	L8-126W	42pcs*3w 20 inch	4 pcs/ctn	
	L8-144W	48pcs*3w 23 inch	4 pcs/ctn	
	L8-180W	60pcs*3w 29 inch	4 pcs/ctn	
	L8-198W	66pcs*3w 32 inch	4 pcs/ctn	
	L8-234W	78pcs*3w 36 inch	4 pcs/ctn	
	L8-252W	84pcs*3w 39 inch	4 pcs/ctn	
	L8-288W	96pcs*3w 42 inch	4 pcs/ctn	
	L8-324W	108pcs*3w 51 inch	4 pcs/ctn	
L4B Series (3W/PC)				
<ul style="list-style-type: none"><li>* 3W/PC Epistar LED</li><li>* Operating Volt:9-32V DC</li><li>* Color Temperature:6000K</li><li>* Operation temperature:-40°C~85°C</li><li>* Waterproof rate:IP67</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Mounting Bracket:Stainless steel bracket</li><li>* 30000 hours above life time</li></ul>	L4B-36WC	12pcs*3w 8 inch	6 pcs/ctn	
	L4B-72WC	24pcs*3w 15 inch	6 pcs/ctn	
	L4B-120WC	40pcs*3w 22 inch	4 pcs/ctn	
	L4B-180WC	60pcs*3w 32 inch	4 pcs/ctn	
	L4B-240WC	80pcs*3w 42 inch	4 pcs/ctn	
	L4B-288WC	96pcs*3w 50 inch	4 pcs/ctn	
	L4B-300WC	100pcs*3w 52 inch	4 pcs/ctn	





# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: davi.ke  
Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
L4 Series (3W/PC)				
* 3W/PC LED * Operating Volt:10-30V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L4-36W	12pcs*3w 7.5 inch	8 pcs/ctn	
	L4-72W	24pcs*3w 13.5 inch	4 pcs/ctn	
	L4-120W	40pcs*3w 21.5 inch	4 pcs/ctn	
	L4-180W	60pcs*3w 31.5 inch	4 pcs/ctn	
	L4-240W	80pcs*3w 41.5 inch	4 pcs/ctn	
	L4-288W	96pcs*3w 50 inch	4 pcs/ctn	
	L4-300W	100pcs*3w 51.5 inch	4 pcs/ctn	
L2 Series (3W/PC)				
* 3W/PC Epsitar LED * Operating Volt:10-30V DC * 220±20LM each Epsitar LED * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L2-36W	12pcs*3w 7.5 inch	8pcs/ctn	
	L2-60W	20pcs*3w 7.5 inch	4pcs/ctn	
	L2-72W	24pcs*3w 13.5 inch	4pcs/ctn	
	L2-120W	40pcs*3w 21.5 inch	4pcs/ctn	
	L2-180W	60pcs*3w 31.5 inch	4pcs/ctn	
	L2-240W	80pcs*3w 41.5 inch	4pcs/ctn	
	L2-288W	96pcs*3w 50 inch	4pcs/ctn	
	L2-300W	100pcs*3w 51.5 inch	4pcs/ctn	
5W/PCS				
L31 Series (5W/PC)				
* 5W/PC Cree LED Operating Voltage: 9-30V DC * Waterproof rate: IP 67 * Color Temperature: 6000K * Beam: Flood * Body Color: Black * Material: Diecast aluminum housing * Lens material:PC * Mounting Bracket:Stainless steel bracket mounting brackets on the bottom * 30000 hours above life time	L30-30W	6pcs*5w 5 inch	24pcs/ctn	
	L30-60W	12pcs*5w 9 inch	12pcs/ctn	
	L30-120W	24pcs*5w 13.5 inch	8pcs/ctn	
L28 Series (5W+3W/PC)				
* 5W+3W/PC Cree LED * Operating Voltage: 9-32V DC * Waterproof rate: IP 67 * Color Temperature: 6000K * Beam: Spot * Body Color: Black * Material: Diecast aluminum housing * Lens material:PC * Mounting Bracket:Stainless steel bracket mounting brackets on the bottom * 30000 hours above life time	L28-48W	6*5W+6*3W 10.6 inch	6pcs/ctn	
	L28-96W	12*5W+12*3W 16.7 inch	6pcs/ctn	
	L28-160W	20*5W+20*3W inch	4pcs/ctn	
	L28-240W	30*5W+30*3W 32.2 inch	4pcs/ctn	
	L28-320W	40*5W+40*3W 42.2 inch	4pcs/ctn	
	L28-384W	48*5W+48*3W 50.3 inch	4pcs/ctn	
	L28-400W	50*5W+50*3W 52.2 inch	4pcs/ctn	
L16 Series (5W/PC)				
* 5W/pcs USA CREE Operating Voltage: 10-30V DC * Waterproof rate: IP67 Color Temperature: 6000K * Beam: Spot/ Flood/ Combo Body Color: Black/white(No stock) Shell material:Aluminum alloy spraying Fitting screw: 304 stainless steel	L16-30W	6pcs*5w 6.8 inch	24pcs/ctn	
	L16-60W	12pcs*5w 13 inch	12pcs/ctn	
	L16-90W	18pcs*5w 19.1 inch	12pcs/ctn	
	L16-120W	24pcs*5w 25.2 inch	8pcs/ctn	
	L16-150W	30pcs*5w 31.4 inch	6pcs/ctn	



# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: [davi.ke](mailto:davi.ke)  
Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
Lens material:PC * 30000 hours above life time Yellow/white light out of the three lines, pure white light out of the second line	L16-180W	36pcs*5w 37.5 inch	6pcs/ctn	
	L16-210W	42pcs*5w 43.7 inch	6pcs/ctn	
	L16-240W	48pcs*5w 49.8 inch	4pcs/ctn	
L14 Series-4D/5D (5W/PC ETI)				
* Operating Voltage: 10-30V DC * Current draw change with your working * Voltage and power * Waterproof rate: IP 67 * Color Temperature: 6000K * Beam: Spot/ Flood/ Combo * Body Color: Black, * Material: Diecast aluminum housing * Lens material:PC * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L14-30W	6pcs*5W 6 inch	8pcs/ctn	   
	L14-50W	10pcs*5W 10 inch	8pcs/ctn	
	L14-60W	12pcs*5W 12 inch	6pcs/ctn	
	L14-90W	16pcs*5W 18 inch	4pcs/ctn	
	L14-100W	20pcs*5W 20 inch	4pcs/ctn	
	L14-120W	24pcs*5W 24 inch	4pcs/ctn	
	L14-150W	30pcs*5W 30 inch	4pcs/ctn	
	L14-180W	36pcs*5W 35.5 inch	4pcs/ctn	
	L14-200W	40pcs*5W 39.5 inch	4pcs/ctn	
	L14-210W	42pcs*5W 41.5 inch	4pcs/ctn	
	L14-240W	48pcs*5W 47.5 inch	4pcs/ctn	
	L14-250W	50pcs*5W 49.5 inch	4pcs/ctn	
L14 Series (5W/PC)				
* Operating Voltage: 10-30V DC * Current draw change with your working * Voltage and power * Waterproof rate: IP 67 * Color Temperature: 6000K * Beam: Spot/ Flood/ Combo * Body Color: Black, * Material: Diecast aluminum housing * Lens material:PC * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L14-30W	6pcs*5W 6 inch	8pcs/ctn	   
	L14-50W	10pcs*5W 10 inch	8pcs/ctn	
	L14-60W	12pcs*5W 12 inch	6pcs/ctn	
	L14-90W	16pcs*5W 18 inch	4pcs/ctn	
	L14-100W	20pcs*5W 20 inch	4pcs/ctn	
	L14-120W	24pcs*5W 24 inch	4pcs/ctn	
	L14-150W	30pcs*5W 30 inch	4pcs/ctn	
	L14-180W	36pcs*5W 35.5 inch	4pcs/ctn	
	L14-200W	40pcs*5W 39.5 inch	4pcs/ctn	
	L14-210W	42pcs*5W 41.5 inch	4pcs/ctn	
	L14-240W	48pcs*5W 47.5 inch	4pcs/ctn	
	L14-250W	50pcs*5W 49.5 inch	4pcs/ctn	
L110 Series-4D/5D (5W/PC Osram)				
* 5W/PC LED * Operating Volt:10-30V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L11-60WO-4D/5D	12pcs*5w 7.5 inch	8pcs/ctn	 
	L11-120WO-4D/5D	24pcs*5w 13.5 inch	4pcs/ctn	
	L11-200WO-4D/5D	40pcs*5w 21.5 inch	4pcs/ctn	
	L11-300WO-4D/5D	60pcs*5w 31.5 inch	4pcs/ctn	
	L11-400WO-4D/5D	80pcs*5w 41.5 inch	4pcs/ctn	
	L11-500WO-4D/5D	100pcs*5w 51.5 inch	4pcs/ctn	
L8 Series-4D/5D (5W/PC Osram)				
* 5W/PC LED Osram * Operating Volt:10-30V DC * Color Temperature:6000K * Operation temperature:-40°C~85°C * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L8-30WO-4D/5D	6pcs*5w 4 inch	20 pcs/ctn	  
	L8-60WO-4D/5D	12pcs*5w 7 inch	6 pcs/ctn	
	L8-90WO-4D/5D	18pcs*5w 10 inch	6 pcs/ctn	
	L8-120WO-4D/5D	24pcs*5w 12 inch	4 pcs/ctn	
	L8-150WO-4D/5D	30pcs*5w 15 inch	4 pcs/ctn	
	L8-180WO-4D/5D	36pcs*5w 17 inch	4 pcs/ctn	
	L8-210WO-4D/5D	42pcs*5w 20 inch	4 pcs/ctn	
	L8-240WO-4D/5D	48pcs*5w 23 inch	4 pcs/ctn	
	L8-300WO-4D/5D	60pcs*5w 29 inch	4 pcs/ctn	
	L8-390WO-4D/5D	78pcs*5w 36 inch	4 pcs/ctn	
	L8-480WO-4D/5D	96pcs*5w 42 inch	4 pcs/ctn	



# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: [davi.ke](mailto:davi.ke)  
Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
L1 Series (5W/PC)				
<ul style="list-style-type: none"><li>* 5W/PC Cree LED</li><li>* Operating Volt:10-30V DC</li><li>* 420±30LM each LED</li><li>* Color Temperature:6000K</li><li>* Operation temperature:-40°C~85°C</li><li>* Waterproof rate:IP67</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Mounting Bracket:Stainless steel bracket</li><li>* 30000 hours above life time</li></ul>	L1-30W	6pcs*5w 10.5 inch	4 pcs/ctn	
	L1-60W	12pcs*5w 20 inch	4 pcs/ctn	
	L1-90W	18pcs*5w 29.5 inch	4 pcs/ctn	
	L1-120W	24pcs*5w 39 inch	4 pcs/ctn	
	L1-150W	30pcs*5w 48.5 inch	4 pcs/ctn	
	L1-180W	36pcs*5w 58 inch	4 pcs/ctn	
L1-210W	42pcs*5w 67.5 inch	4 pcs/ctn		
10W/PCS				
L34 Series (10W/PC)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-30V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L34-30W	3pcs*10w 6.4 inch	12 pcs/ctn	
	L34-60W	6pcs*10w 11.8 inch	12 pcs/ctn	
	L34-90W	9pcs*10w 17.2 inch	6 pcs/ctn	
	L34-120W	12pcs*10w 22.7 inch	6 pcs/ctn	
	L34-150W	15pcs*10w 28.1 inch	6 pcs/ctn	
	L34-180W	18pcs*10w 33.5 inch	4 pcs/ctn	
	L34-210W	21pcs*10w 39 inch	4 pcs/ctn	
	L34-240W	24pcs*10w 44.4 inch	4 pcs/ctn	
L34-270W	27pcs*10w 49.8 inch	4 pcs/ctn		
L33 Series (10W/PC) with daytime light				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-30V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L33-60W	6pcs*10w 12.2 inch	8 pcs/ctn	
	L33-120W	12pcs*10w 22.8 inch	6 pcs/ctn	
	L33-180W	18pcs*10w 33.5 inch	4 pcs/ctn	
	L33-240W	24pcs*10w 44 inch	4 pcs/ctn	
L32 Series (10W/PC)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-32V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L32-60W	6pcs*10w 11 inch	6 pcs/ctn	
	L32-120W	12pcs*10w 21 inch	6 pcs/ctn	
	L32-180W	18pcs*10w 31 inch	4 pcs/ctn	
	L32-240W	24pcs*10w 41 inch	4 pcs/ctn	
	L32-300W	30pcs*10w 51 inch	4 pcs/ctn	
L27 Series (10W/PC)				
<ul style="list-style-type: none"><li>* Operating Voltage: 9-32V DC</li><li>* Waterproof rate: IP 67</li><li>* Color Temperature: 6000K</li><li>* Beam: Spot/ Flood/ Combo</li><li>* Body Color: Black</li><li>* Material: Diecast aluminum housing</li><li>* Lens material:PC</li><li>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</li><li>* 30000 hours above life time</li></ul>	L27-30W	3pcs*10w 5.6 inch	6pcs/ctn	
	L27-60W	6pcs*10w 5.6 inch	6pcs/ctn	
	L27-90W	9pcs*10w 5.6 inch	4 pcs/ctn	
	L27-120W	12pcs*10w 5.6 inch	4 pcs/ctn	
	L27-150W	15pcs*10w 5.6 inch	4 pcs/ctn	
	L27-180W	18pcs*10w 5.6 inch	4 pcs/ctn	
	L27-210W	21pcs*10w 5.6 inch	4 pcs/ctn	
	L27-240W	24pcs*10w 5.6 inch	4 pcs/ctn	





# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor, Guaner yongtai building no.810 chongyun road, yongping street,  
baiyun district, guangzhou city, guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)  
Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: davi.ke  
Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)  
Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
L15 Series (10W/PC)				
<p>* 10W/pcs USA CREE</p> <p>Operating Voltage: 10-30V DC</p> <p>* Waterproof rate: IP67</p> <p>Color Temperature: 6000K</p> <p>* Beam: Spot/ Flood/ Combo</p> <p>Body Color: Black/white(No stock)</p> <p>Shell material:Aluminum alloy spraying</p> <p>Fitting screw: 304 stainless steel</p> <p>Lens material:PC</p> <p>* 30000 hours above life time</p> <p>Yellow/white light out of the three lines, pure white light out of the second line</p>	L15-30W	3pcs*10w 6 inch	12pcs/ctn	
	L15-60W	6pcs*10w 11.3 inch	12pcs/ctn	
	L15-90W	9pcs*10w 16.6 inch	6pcs/ctn	
	L15-120W	12pcs*10w 21.9 inch	6pcs/ctn	
	L15-150W	15pcs*10w 27.2 inch	6pcs/ctn	
	L15-180W	18pcs*10w 32.6 inch	4pcs/ctn	
	L15-210W	21pcs*10w 37.9 inch	4pcs/ctn	
	L15-240W	24pcs*10w 43.2 inch	4pcs/ctn	
	L15-270W	27pcs*10w 48.5 inch	4pcs/ctn	
	L15-300W	30pcs*10w 53.8 inch	4pcs/ctn	
L13 Series (10W/PC)				
<p>* 10W/PC <b>Cree</b> LED</p> <p>Operating Voltage: 10-30 DC</p> <p>* Current draw change with your working Voltage and power</p> <p>* Waterproof rate: IP 67</p> <p>* Color Temperature: 6000K</p> <p>* Beam: Spot/ Flood/ Combo</p> <p>* Body Color: Black</p> <p>* Material: Diecast aluminum housing</p> <p>* Lens material:PC</p> <p>* Mounting Bracket:Stainless steel bracket mounting brackets on the bottom</p> <p>* 30000 hours above life time</p>	L13-20W	2pcs*10w 4.4 inch	12pcs/ctn	
	L13-40W	4pcs*10w 8.0 inch	6pcs/ctn	
	L13-60W	6cs*10w 12 inch	6pcs/ctn	
	L13-80W	8pcs*10w 15 inch	6pcs/ctn	
	L13-120W	12pcs*10w 22.5 inch	4pcs/ctn	
	L13-160W	16pcs*10w 28 inch	4pcs/ctn	
	L13-200W	20pcs*10w 37 inch	4pcs/ctn	
	L13-240W	24pcs*10w 43.5 inch	4pcs/ctn	
	L13-260W	26pcs*10w 47 inch	4pcs/ctn	
L7 Series (10W/PC)				
<p>* 10W/PC LED</p> <p>* Operating Volt:10-30V DC</p> <p>* Color Temperature:6000K</p> <p>* Operation temperature:-40°C~85°C</p> <p>* Waterproof rate:IP67</p> <p>* Beam: Spot/ Flood/ Combo</p> <p>* Mounting Bracket:Stainless steel bracket</p> <p>* 30000 hours above life time</p>	L7-40W	4pcs*10W 4.6 inch	10 pcs/ctn	
	L7-80W	8pcs*10w 7.8 inch	6 pcs/ctn	
	L7-120W	12pcs*10 11 inch	6 pcs/ctn	
	L7-160W	16pcs*10w 14.3 inch	6 pcs/ctn	
	L7-200W	20pcs*10w 17.5 inch	6 pcs/ctn	
	L7-240W	24pcs*10w 20.6 inch	6 pcs/ctn	
	L7-280W	28pcs*10w 23.6 inch	6 pcs/ctn	
	L7-320W	32pcs*10w 26.6 inch	4 pcs/ctn	
	L7-360W	36pcs*10w 29.6 inch	4 pcs/ctn	
L6-4D Series (10W/PC)				
<p>* 10W/PC <b>Cree LED</b></p> <p>* Operating Volt:10-30V DC</p> <p>* 950±50LM each LED</p> <p>* Color Temperature:6000K</p>	L6-20W-4D	2pcs*10w 5 inch	8 pcs/ctn	
	L6-40W-4D	4pcs*10w 8 inch	8 pcs/ctn	
	L6-60W-4D	6pcs*10w 11 inch	4 pcs/ctn	
	L6-80W-4D	8pcs*10w 14 inch	4 pcs/ctn	
	L6-100W-4D	10pcs*10w 17.5 inch	4 pcs/ctn	
	L6-120W-4D	12pcs*10w 20 inch	4 pcs/ctn	



# Liwin Electronic Technology Co.,Ltd.

ADD: 6th floor,Guaner yongtai building no.810 chongyun road,yongping street,  
baiyun district,guangzhou city,guangdong china.

Tel: 86 20 66656962 Web: [www.liwin.en.alibaba.com](http://www.liwin.en.alibaba.com) [www.liwin-china.com](http://www.liwin-china.com)

Yahoo: [kirbyke168@yahoo.com](mailto:kirbyke168@yahoo.com) Msn: [kirby.ke@hotmail.com](mailto:kirby.ke@hotmail.com) Sky: davi.ke

Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com) Company Email: [liwinchina@liwin-china.com](mailto:liwinchina@liwin-china.com)

Kirby Ke (General Manager) Mobile: +86 15920871181

## LED Bar Lights (Mini Order: 1 carton)

Specifications	Part no.	LED Qty Dimentions	Pcs/Ctn	Photos
Operation temperature:-40℃~85℃ * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L6-160W-4D	16pcs*10w 26 inch	4 pcs/ctn	
	L6-180W-4D	18pcs*10 29.5 inch	4 pcs/ctn	
	L6-200W-4D	20pcs*10 32 inch	4 pcs/ctn	
	L6-240W-4D	24pcs*10w 38 inch	4 pcs/ctn	
	L6-260W-4D	26pcs*10w 41 inch	4 pcs/ctn	
	L6-300W-4D	30pcs*10w 47 inch	4 pcs/ctn	
L6 Series (10W/PC)				
* 10W/PC <b>Cree LED</b> * Operating Volt:10-30V DC * 950±50LM each LED * Color Temperature:6000K * Operation temperature:-40℃~85℃ * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L6-20W	2pcs*10w 5 inch	8 pcs/ctn	  
	L6-40W	4pcs*10w 8 inch	8 pcs/ctn	
	L6-60W	6pcs*10w 11 inch	4 pcs/ctn	
	L6-80W	8pcs*10w 14 inch	4 pcs/ctn	
	L6-100W	10pcs*10w 17.5 inch	4 pcs/ctn	
	L6-120W	12pcs*10w 20 inch	4 pcs/ctn	
	L6-160W	16pcs*10w 26.5 inch	4 pcs/ctn	
	L6-180W	18pcs*10 29.5 inch	4 pcs/ctn	
	L6-200W	20pcs*10 32 inch	4 pcs/ctn	
	L6-240W	24pcs*10w 38 inch	4 pcs/ctn	
	L6-260W	26pcs*10w 41 inch	4 pcs/ctn	
	L6-300W	30pcs*10w 47 inch	4 pcs/ctn	
L5 Series (10W/PC)				
* 10W/PC <b>Cree LED</b> * Operating Volt:10-30V DC * 950±50LM each LED * Color Temperature:6000K * Operation temperature:-40℃~85℃ * Waterproof rate:IP67 * Beam: Spot/ Flood/ Combo * Mounting Bracket:Stainless steel bracket * 30000 hours above life time	L5-20W	2pcs*10w 5.9 inch	12 pcs/ctn	  
	L5-40W	4pcs*10w 9.5 inch	6 pcs/ctn	
	L5-80W	8pcs*10w 17.9 inch	6 pcs/ctn	
	L5-120W	12pcs*10w 25.9 inch	4 pcs/ctn	
	L5-160W	16pcs*10w 33.9 inch	4 pcs/ctn	
	L5-180W	18pcs*10w 37.5 inch	4 pcs/ctn	
	L5-240W	24pcs*10w 50 inch	4 pcs/ctn	
Relay for led bars lights: DT joint	LW-001			
Relay for led bars lights: DT joint	LW-002			