

File No.: JS-FT009B01-001 Version:A0

9W 0.6M Luxury Rotable Diffusion T8 LED Tube Specifications

Features

- ◆ Compared with the traditional fluorescent lamp, LED fluorescent lamp can save 80% energy.
- ♦ In the same lighting conditions, the LED lamp brightness attenuation lower than that of traditional fluorescent lamps.
- ◆LED lamps excluding ultraviolet and infrared radiation, does not contain mercury, lead, harmful environmental substances.
- ◆ Products with long life and super bright SMD LED, the product life of up to 30,000 hours, is 10 times the traditional fluorescent tube.
- ◆ The product installation is a single-ended input, and the products have been certified by CE, ROHS certification.

Application

◆ Its products are widely used in homes, offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.

Technical Specifications

Model No.	JFT009W8B01	JFT009N7B01	JFT009S7B01	Figure:
Color Temperature	2700-3500K	4000-4500K	5700-7000K	
Luminous Flux	700lm±10%	750lm±10%	800lm±10%	
Color Rendering Index(R)	>80	>70	>70	
LED Quantity	84 PCS			Dimensional Drawings.
Input	AC 85-264V, 47-63HZ			_ <u>L</u>
Input Power	9W±15%			Φ26mm 1
LED Power	8.4W			IES Diagram:
Power Factor	>0.9			210 150
Type of Power	Internal Installation and Isolation			(240)
Operation Ambient Temperature	-20℃~40℃			240 120
Storage Ambient Temperature	-20℃~50℃			270 90
Operation Ambient Humidity	10%~90%			300 212.9 60
Shell Material	1/2 Aluminum Shell and 1/2 Diffusion PC Cover and Rotation of the Tube Plug			330 425.8 30 532.3
Product Dimensions	Ф26×L588mm			
Packaging Dimensions	Paper Box: Ф42×L630mm			1.0 531.72 3.256
	Carton: L650×W250×H200mm			
Packaging Quantity	20 PCS/Carton			2.0 132.93 6.512
Packaging	5×4			
GW	8KG			3.0 59.08 9.768
Product Life Time	≥30000 Hours			Height(m) Center E(lx) Diameter(m) Beam Angle: 115.9

Confirmed by: Check by: Approval by: