

File No.: JS-FT012B01-001 Version:A0

12W 0.9M Luxury Rotable Diffusion T8 LED Tube Specifications

Features

- ◆ Compared with the traditional fluorescent lamp, LED fluorescent lamp can save 80% energy.
- ♦ In the same lighting conditions, the LED lamp brightness attenuation lower than that of traditional fluorescent lamps.
- ◆LED lamps excluding ultraviolet and infrared radiation, does not contain mercury, lead, harmful environmental substances.
- ◆ Products with long life and super bright SMD LED, the product life of up to 30,000 hours, is 10 times the traditional fluorescent tube.
- ◆ The product installation is a single-ended input, and the products have been certified by CE, ROHS certification.

Application

◆ Its products are widely used in homes, offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.

Technical Specifications

Model No.	JFT012W8B01	JFT012N7B01	JFT012S7B01	Figure:
Color Temperature	2700-3500K	4000-4500K	5700-7000K	
Luminous Flux	950lm±10%	1000lm±10%	1050lm±10%	
Color Rendering Index(R)	>80	>70	>70	
LED Quantity	108 PCS			
Input	AC 85-264V, 47-63HZ			Dimensional Drawings.
Input Power	12W±15%			Φ26mm 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
LED Power	10.8W			IES Diagram: Polar Graph
Power Factor	>0.9			210 150
Type of Power	Internal Installation and Isolation			240
Operation Ambient Temperature	-20℃~40℃			120
Storage Ambient Temperature	-20℃~50℃			90
Operation Ambient Humidity	10%~90%			300 212.9 60
Shell Material	1/2 Aluminum Shell and 1/2 Diffusion PC Cover and Rotation of the Tube Plug			330 425.8 30
Product Dimensions	Ф26×L894mm			
Packaging Dimensions	Paper Box: Ф42XL930mm			1. 0 531. 72 3. 256
	Carton: L950×W250×H200mm			
Packaging Quantity	20 PCS/Carton			2.0 132.93 6.512
Packaging	5×4			
GW	12KG			3.0 59.08 9.768
Product Life Time	≥30000 Hours			Height(n) Center E(k) Diameter(m) Beam Angle: 116.9

Confirmed by: Check by: Approval by: