

File No.: JS-FT022B01-001 Version:A0

## 22W 1.5M Luxury Rotable Diffusion T8 LED Tube Specifications

## **Features**

- ◆ Compared with the traditional fluorescent lamp, LED fluorescent lamp can save 80% energy.
- ♦ In the same lighting conditions, the LED lamp brightness attenuation lower than that of traditional fluorescent lamps.
- ◆LED lamps excluding ultraviolet and infrared radiation, does not contain mercury, lead, harmful environmental substances.
- ◆ Products with long life and super bright SMD LED, the product life of up to 30,000 hours, is 10 times the traditional fluorescent tube.
- ◆ The product installation is a single-ended input, and the products have been certified by CE, ROHS certification.

## **Application**

◆ Its products are widely used in homes, offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.

## **Technical Specifications**

Model No.	JFT022W8B01	JFT022N7B01	JFT022S7B01	Figure:
Color Temperature	2700-3500K	4000-4500K	5700-7000K	
Luminous Flux	1900lm±10%	2000lm±10%	2100lm±10%	
Color Rendering Index(R)	>80	>70	>70	
LED Quantity	216 PCS			Dimensional Drawings.
Input	AC 85-264V, 47-63HZ			L L
Input Power	22W±15%			Φ26mm 1
LED Power	21.6W			IES Diagram:
Power Factor	>0.9			210 150
Type of Power	Internal Installation and Isolation			120
Operation Ambient Temperature	-20℃~40℃			
Storage Ambient Temperature	-20℃~50℃			270 90
Operation Ambient Humidity	10%~90%			300 212.9 60
Shell Material	1/2 Aluminum Shell and 1/2 Diffusion PC Cover and Rotation of the Tube Plug			230 425.8 30
Product Dimensions	Ф26×L1498mm			
Packaging Dimensions	Paper Box: Ф42×L1530mm			1.0 531.72 3.256
	Carton: L1550×W250×H200mm			
Packaging Quantity	20 PCS/Carton			2.0 132.93 6.512
Packaging	5×4			
GW	25KG			3.0 59.08 9.768
Product Life Time	≥30000 Hours			Height(m) Center E(h) Diameter(m) Beam Angle: 115.9

Confirmed by: Check by: Approval by: