

# 40W 600x600 Luxury Ceiling LED Panel Light Specifications

## 1. Features

- ◆ A high stability constant current driver to ensure the service life of LED.
- ◆ Wide input voltage range AC 100-240V 50/60Hz applies to most countries.
- ◆ Energy-saving, low power consumption.
- ◆ Environmental friendly, no flicker, no UV or infrared radiation, low-heat, no mercury element. No harmful substances produced in the process of using.
- ◆ The product life of up to 30.000 hours, is 10 times the traditional fluorescent tube.
- ◆ Convenient to install and use, replaceable with the traditional grille lamp.
- ◆ The products have been certified by CE, ROHS certification.

**CE RoHS**

## 2. Application

- ◆ Its products are widely used in offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.


## 3. Technical Specifications

Model No.	JPL040W8A02	JPL040N7A02	JPL040S7A02
Color Temperature	27000-3500K	4000-4500K	5700-6300K
Luminous Flux	2600lm±10%	2800lm±10%	3000lm±10%
Color Rendering Index(R)	>80	>70	>70
LED Quantity	576 PCS		
Input	AC 100-240V, 47-63HZ		
Input Power	40W±15%		
LED Power	34.5W		
Power Factor	>0.9		
Type of Power	External Installation and Isolation		
Operation Ambient Temperature	-20℃~40℃		
Storage Ambient Temperature	-20℃~50℃		
Operation Ambient Humidity	10%~90%		
Shell Material	Unique Aluminum Shell and Diffusion PC Cover		
Beam Angle	120°		
Product Dimensions	L595×W595×D40mm		
Mounting Dimensions	L600×W600		
Packaging Dimensions	Carton: L652×W82×H659mm		
Packaging Quantity	1PCS/Carton		
Packaging	1×1		
GW	4.3 KG		
Product Life Time	≥30.000 Hours		

Figure:



Dimensional Drawings:



IES Diagram:

