

File No.: JS-BL003C38-001 Version:A0

3W Common Bright C38 LED Bulb Specifications

1. Features

- ◆ High luminous efficiency.
- ◆ Unique cooling technology used, excellent cooling effect, long life span.
- ◆ Environment friendly, the product does not contain mercury, lead and other harmful substances, achieves healthy lighting without UV and stroboscopic effect.
- lacktriangle High color rendering index, reproduce the original color with clearer vision.
- ◆ Products with long life and super bright SMD LED, the product life is up to 30.000 hours, is 10 times the traditional fluorescent tube.
- ◆ The products have been certified by CE, ROHS certification.

C € RoHS

2. Application

◆ Its products are widely used in homes, offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.

3. Technical Specifications

	W-184				
Model No.	JCA003W8C38	JCA003N7C38	JCA003S7C38	Figure:	
Color Temperature	2700-3500K	4000-4500K	5700-6300K		T
Luminous Flux	150lm±10%	180lm±10%	200lm±10%		
Color Rendering Index(R)	>80	>70	>70		L
LED Quantity	4PCS			No. of the last of	
Input	AC 85-264V, 47-63Hz			Dimensional Drawings:	1
Input Power	3W±15%			IES Diagram:	1
LED Power	2W			Polar Graph	
Type of Power	Internal Installation and Isolation			200 150	
Operation Ambient Temperature	-20℃~40℃			740	120
Storage Ambient Temperature	-20°C∼50°C			210	90
Operation Ambient Humidity	10%~90%			23/1	60
Shell Material	Unique Ceramics Shell and Diffusion Cover			99.3	
Lamp Base	E27/E26/GU10/E17/E14			115.3	
Product Dimensions	D37XL122			1.0	11.029
Packaging Dimensions	Paper Box: L50×W50×H132mm				
	Carton: 400×400×600mm			28.25	22.050
Packaging Quantity	196 PCS/Carton			2.0	22.059
Packaging	49×4				
GW	21.4KG			3.0	33.088
Product Life Time	≥30.000 Hours			Height(m) Center E(lx) Beam Angle:159.4	Diameter(m)