

20W 1.2M Flare Series Dimmable Diffusion T8 LED Tube Specifications

1. Features

- Compared with the traditional fluorescent lamp, LED fluorescent lamp can save 80% energy.
- In the same lighting conditions, the LED lamp brightness attenuation lower than that of traditional fluorescent lamps.
- ◆ LED lamps excluding ultraviolet and infrared radiation, does not contain mercury, lead, harmful environmental substances.
- ◆ Products with long life and super bright SMD LED, the product life of up to 30.000 hours, is 10 times the traditional fluorescent tube.
- The product installation is a single-ended input, and the products have been certified by CE, ROHS certification.

C€ RoHS

Application

2.

Its products are widely used in homes, offices, hotels, shopping malls, hospitals, schools, government departments, industrial lighting, automotive lighting and other lighting applications.

3. Technical Specifications

Model No.	JFT020W8C01	JFT020N7C01	JFT020S7C01	Figure:
Color Temperature	2700-3500K	4000-4500K	5700-6300K	
Luminous Flux	1650lm±10%	1700lm±10%	1750lm±10%	
Color Rendering Index(R)	>80	>70	>70	
LED Quantity	288 PCS			
Input	AC 185-264V, 47-63HZ			Dimensional Drawings: L
Input Power	20W±15%			Ф26mm] [
LED Power	17.3W			IES Diagram:
Power Factor	>0.9			210 150
Type of Power	External Installation and Isolation and Dimmable			240 120
Operation Ambient Temperature	-20°C~40°C			
Storage Ambient Temperature	-20°C~50°C			212.9
Operation Ambient Humidity	10%~90%			300 60 60
Shell Material	1/3 Aluminum Shell and 2/3 Diffusion PC Cover			532.3
Product Dimensions	Φ26×L1198mm			
Packaging Dimensions	Paper Box: 042×L1230mm			1.0 531.72 3.256
	Carton: L1250×W250×H200mm			
Packaging Quantity	35 PCS/Carton			2.0 132.93 6.512
Packaging	5×7			
GW	19.2KG			3.0 59.08 9.768
Product Life Time	≥30.000 Hours			Height(m) Center E(k) Diameter(m) Diameter(m)

Declaration

We can't guarantee the silicon control dimmable LED lamp we manufacture is 100% compatible with all the silicon control dimmers on the market, if any flickering happens or the

dimming function is not ideal is normal situation, customer may change the dimmer compatible with our lamp to realize the dimming function.

West Area, A building, National University Science and Technology Park of Zhejiang University (No. 525 Xixi Road, Hangzhou City, Zhejiang Province, China)