




Air-Separater Machine

Brief Introduction

The main use purpose of the fanning machine independently developed and manufactured by our company is to convey the riddlings after screening to the fanning machine by the conveyer belt, we take advantage of the wind power to separate out the light density garbage such as the plastic bags and paper bags in the garbage so as



to achieve the purpose of sorting, recovering and recycling the garbage. The air classification equipment independently developed and manufactured by our company have the features that the power is low, noise is small and the air classification effect is well. There are two kinds of this production. One is positive pressure fanning machine; the other is negative pressure fanning machine.



Technical Parameters :

Type Function	Flow Rate (m ³ /h)	Main Engine Power (kW)	Full Pressure (Pa)	Structural Form
TBH-ZYFX-40	3200 - 4600	2.2	840 - 800	Fix Type
TBH-FYFX-200	17700 - 25900	40.2	3550 - 4550	Fix Type

External Form, Joint Dimensions:

Type Function	Feed Inlet Height	Gurry Port Height	Overall Dimensions
TBH-ZYFX-40	4080	1670	3000×3480×4080
TBH-FYFX-200	indetermination	indetermination	1600×2900×1750

Notes: Our company could redesign according to the requirements of the users. Our company can produce the positive pressure and negative pressure fanning machines.

