



## Tianjin Innovator Environmental Engineering Co.,Ltd

6-2-605 RongHe Plaza, Central Road, Airport Economic Development Zone, Tianjin, China  
Tel:+86 22 84841648 Fax:+86 22 84841659 Email:Matthews@innorecycling.com  
www.innorecycling.com

### **156\*78 Solar mono wafer INEE55W/ 18VSolar Module**

ITEM NO	INEE55/18V
MONO or POLY	Poly
Maximum power (Wp)	55wp
Maximum power voltage (V)	17.1
Maximum power current (A)	3.22
Open circuit voltage (V)	21.4
Short circuit current (A)	3.53
Number of cells (Pcs)	36
Size of module (mm)	771*665*30
Maximum system voltage (V)	715
Temperature coefficients of Isc (%)	0.065+/-0.015%/°C
Temperature coefficients of Voc (%)	- (2.23+/-0.1) mv/ °C
Temperature coefficients of Pm (%)	- (0.5+/-0.05) / °C
Temperature coefficients of Im (%)	+0.1/ °C
Temperature coefficients of Vm (%)	-0.38/ °C
Temperature Range	-40°C ~+85°C
Tolerance Wattage (e.g. +/-5%)	+/-5%
Surface Maximum Load Capacity	60m/s(200kg/sq.m)
Allowable Hail Load	steel ball fall down from 1m height
Weight per piece (kg)	6.2
Length of Cables (mm)	900mm
Cell Efficiency (%)	>13%
Module Efficiency (%)	>11.5%
Output tolerance (%)	+/-5%
Frame (Material, Corners, etc.)	Aluminum
Standard Test Conditions	AM1.5 100mw/cm <sup>2</sup> 25°C
Warranty	2 years product warranty and 25years 80% of power
FF (%)	69%
Packing	2PCS/CTN , 2072CTN/40 FCL

**Fly With GEP Innovation, Make Our Lives Better**

