# 天津天应泰钢管Tianjin Tianyingtai Steel Pipe Co.,Ltd ( For domestic)

## 天津汇来国际Tianjin Huilai International Trade Co Ltd ( For Over Sea)

## Standard: GB/T3091-2008 GB/T9711.1-97 ASTM API

High Quality High Performance High Standard to let u win the future

No：20150910

### ERW CARBON STEEL PIPE

| Specification | Thickness | GB/T3091 ASTM A-class | | Specification | Thickness | GB/T3091 ASTM A-class | | Specification | Thickness | GB/T3091 ASTM A-class | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Q235 | Q345 | | | Q235 | Q345 | | | Q235 | Q345 |
| Φ26.9 (6分) | 1.5-1.6 | 2640 | | Φ88.9 (3") | 2.5-2.75 | 2350 | 2750 | Φ165 (6") | 2.5-2.75 | 2470 | 2870 |
| | 1.7-2.0 | 2590 | | | 3.0-4.0 | 2320 | 2720 | | 3.0-3.2 | 2390 | 2790 |
| | 2.1-2.4 | 2510 | | | 4.25-4.75 | 2340 | 2740 | | 3.25-5.25 | 2350 | 2750 |
| | 2.5-2.75 | 2460 | | | 5.0-5.25 | 2420 | 2820 | | 5.5-6.75 | 2380 | 2780 |
| | 3.0-3.25 | 2570 | | | 5.5-8.0 | 2520 | 2920 | | 7.0-10.0 | 2460 | 2860 |
| Φ32 Φ38 | 1.8-2.0 | 2590 | | Φ102 | 2.3-3.0 | 2350 | 2750 | Φ168.3 | 2.75 | 2660 | 3060 |
| | 2.1-2.4 | 2510 | | | 3.25-4.50 | 2320 | 2720 | | 3.0-3.25 | 2480 | 2880 |
| | 2.5-3.25 | 2470 | | | 4.75-5.75 | 2390 | 2790 | | 3.5-6.0 | 2420 | 2820 |
| | 3.5 | 2500 | | | 5.8-6.25 | 2470 | 2870 | | 6.25-8.0 | 2470 | 2870 |
| | 3.75-4.0 | 2590 | | | 6.5-9.0 | 2570 | 2970 | | 8.25-9.0 | 2530 | 2930 |
| Φ33.7 (1") | 1.8-2.0 | 2490 | | Φ108 | 2.2-2.4 | 2450 | 2850 | | 9.25-11.5 | 2600 | 3000 |
| | 2.1-2.4 | 2410 | | | 2.5-3.0 | 2340 | 2740 | Φ177.8 (Φ180) | 2.75 | 2600 | 3000 |
| | 2.5-3.25 | 2370 | | | 3.25-4.50 | 2320 | 2720 | | 3.0 | 2500 | 2900 |
| | 3.5 | 2400 | | | 4.75-5.75 | 2360 | 2760 | | 3.25-3.5 | 2400 | 2800 |
| | 3.75-4.0 | 2490 | | | 5.8-6.25 | 2440 | 2840 | | 3.75-6.00 | 2350 | 2750 |
| Φ42.3 (1.2") | 1.8-2.0 | 2540 | | Φ114.3 (4") | 6.5-9.0 | 2570 | 2970 | | 6.25-8.75 | 2400 | 2800 |
| | 2.1-2.4 | 2430 | 2830 | | 2.2-2.5 | 2370 | 2770 | | 9.0-11.5 | 2500 | 2900 |
| | 2.5-3.5 | 2400 | 2800 | | 2.75-4.0 | 2300 | 2700 | Φ194 Φ203 | 2.75 | 2660 | 3060 |
| | 3.75 | 2420 | 2820 | | 4.25-4.75 | 2340 | 2740 | | 3.0 | 2590 | 2990 |
| | 4.0 | 2470 | 2870 | | 5.0-6.25 | 2390 | 2790 | | 3.25-3.75 | 2500 | 2900 |
| Φ48.3 (1.5") | 1.8-2.0 | 2520 | 2920 | | 6.5-9.0 | 2490 | 2890 | | 4.0-6.75 | 2420 | 2820 |
| | 2.1-2.4 | 2370 | 2770 | Φ121 Φ127 | 2.5-2.75 | 2500 | 2900 | | 6.8-8.0 | 2480 | 2880 |
| | 2.5-3.25 | 2330 | 2730 | | 3.0 | 2440 | 2840 | | 8.25-11.5 | 2540 | 2940 |
| | 3.5 | 2380 | 2780 | | 3.25-4.75 | 2390 | 2790 | Φ190.7 Φ216.3 (Jap. Std) | 2.75 | 2790 | 3190 |
| | 3.75 | 2430 | 2830 | | 5.0-5.75 | 2440 | 2840 | | 3.0 | 2720 | 3120 |
| | 4.0-4.25 | 2540 | 2940 | | 6.0-8.0 | 2520 | 2920 | | 3.25-3.75 | 2630 | 3030 |
| | 4.5-7.0 | 2740 | 3140 | | 8.25-11.0 | 2630 | 3030 | | 4.0-6.75 | 2550 | 2950 |
| Φ50 Φ57 | 1.8-2.3 | 2540 | 2940 | Φ133 | 2.75-3.0 | 2370 | 2770 | | 6.8-10.0 | 2620 | 3020 |
| | 2.5-3.75 | 2440 | 2840 | | 3.25-6.0 | 2340 | 2740 | | 10.25-12.0 | 2720 | 3120 |
| | 4.0-4.75 | 2530 | 2930 | | 6.25-6.75 | 2390 | 2790 | Φ219 | 2.75 | 2590 | 2990 |
| | 5.0-7.0 | 2650 | 3050 | | 7.0-9.75 | 2490 | 2890 | | 3.0 | 2510 | 2910 |
| Φ60.3 (2") | 1.8-2.0 | 2380 | 2780 | Φ139.7 | 2.5-2.75 | 2550 | 2950 | | 3.25 | 2410 | 2810 |
| | 2.1-2.4 | 2350 | 2750 | | 3.0 | 2400 | 2800 | | 3.3-8.25 | 2360 | 2760 |
| | 2.5-3.5 | 2320 | 2720 | | 3.25-4.5 | 2350 | 2750 | | 8.5-9.75 | 2390 | 2790 |
| | 3.75-4.0 | 2370 | 2770 | | 4.75-5.75 | 2400 | 2800 | | 10.0-12.0 | 2460 | 2860 |
| | 4.25-4.75 | 2430 | 2830 | | 6.0-7.0 | 2520 | 2920 | Φ244.5 | 4.0-5.0 | 2560 | 2960 |
| | 5.0-7.0 | 2550 | 2950 | | 7.25-10.0 | 2620 | 3020 | | 5.25-10.0 | 2480 | 2880 |
| Φ76.1 (2.5") | 2.5-2.75 | 2330 | 2730 | Φ152 | 2.5-2.75 | 2580 | 2980 | | 10.25-12 | 2510 | 2910 |
| | 3.0-4.0 | 2320 | 2720 | | 3.0 | 2510 | 2910 | Φ273.1 | 5.0-8.75 | 2480 | 2880 |
| | 4.1-4.75 | 2340 | 2740 | | 3.25-5.75 | 2440 | 2840 | | 9.0-11.0 | 2530 | 2930 |
| | 4.8-5.25 | 2400 | 2800 | | 6.0-8.75 | 2540 | 2940 | | 11.25-12.0 | 2570 | 2970 |
| | 5.5-7.0 | 2500 | 2900 | | 9.0-10.0 | 2640 | 3040 | Φ299 | 4.75-9.75 | 2850 | 3300 |
| Φ73 Φ98 | 2.5-2.75 | 2480 | 2880 | Φ159 | 2.5-2.75 | 2470 | 2870 | | 11.5-11.75 | 2880 | 3330 |
| | 3.0-4.0 | 2450 | 2850 | | 3.0 | 2400 | 2800 | Φ325 | 5.5-9.75 | 2700 | 3150 |
| | 4.1-4.75 | 2480 | 2880 | | 3.25-6.75 | 2350 | 2750 | | 11.5-11.75 | 2730 | 3180 |
| | 4.8-5.25 | 2550 | 2950 | | 6.8-8.5 | 2390 | 2790 | Φ340 | 4.75*11.75 | 2950 | 3400 |
| | 5.5-7.0 | 2650 | 3050 | | 8.6-10.0 | 2470 | 2870 | | | | |

website: http:www.tytgg.com www.tytsteelpipe.com

Contact persion: Mr. Song Mobile:+86-13682134391

（Marketing Department）

TEL：+86-22-28891186

+86-22-28891187

FAX：+86-22-28891185

**If you require hot dipped galvanization, oiling, painting , package threading, sockets ,grooving, shouldered ends , pls send inquiry**

**Email: song@tytgg.com**

Bank Information: Bank Of China , Tianjin Branch,Jinghai Sub-Branch

Address : 31 SHENGLI STREET JINGHAI TIANJIN CHINA

Account:273975199460

Swift Code: BKCHCNBJ200

Note：

1.Ordinary erw pipe:more than 6.5 meter:20RMB/ton

2.Steel pipe of special steel grade:more than 6.5 meter: 80RMB/ton

3.Insert small dia. Into bigger pipe: 20RMB/TON

4.Lift charge:5RMB/ton，Note：PCC pipe: 40RMB/ton

5.Fee of moving inner welded seam on line according to Rule 20100624

6.heat treatment by Medium frequency on line:30RMB/ton

Bevelled ends;50RMB/ton. Hydraulic test:80RMB/ton

7.Dia. Less than 114 made by steel grade Q195, drop 20RMB/ton

8.Steelseal on line:20RMB/ton

9.Pipes used for fire control pipe system,structure,machine:50RMB/ton

11.The price listed is valid for cash.

13.Since 2014 August 15th,our mill has already kept capacity of moving inner weld seam, medium frequency annealing under high standard

14.Pipe for sports equipment:

Thickness below 2.6mm: 3400RMB/ton

Thicker than 2.6mm: 3300RMB/ton