



Introduction:

P4mm Indoor Die Casting Rental led display PR-FINE:

Rental LED Displays has huge markets during these years, and to let our products perfect-standard out from all of our competitors, we developed a new led display featuring Small pitch, High Resolution, More lighter and easy to assemble led display cabinets. Such as Our Indoor Rental Slim LED Display PR-Slim Series, the assembled cabinet totally weight less than 8.3KG, and which makes transportation and disassembling operations much easier.

Features

P4mm Indoor Die Casting Rental led display PR-FINE:

1. The High Definition led display adopts patented SMD Encapsulation Technology..
2. We take **Die Casting Rental** hanging system led display cabinets, the cabinets are made by quality aluminum alloy 5052 through Ultra-thin processors, which helps ensure higher precision, small joint and reliable strength.
3. For this type PR-FINE series cabinets, we can design the Pitch P4MM, P4.66MM, P5.6MM, P6.22MM for clients optional.
4. The cabinets are designed with receptacle compatibility in mind, Available compatible receptacle includes, NEUTRICK,SEENTRONIC,CHOGORI connectors. Customization requirement can also be met..
5. So Lighter LED Display cabinet, standard cabinet size 448mm x 504mm,only 8.2KG/pc.
6. The high refresh rate of 1500HZ, accurate color reproduction, 18Bit grayscale and brightness correction function combine to enable the product to deliver HD quality videos, thus meeting various indoor use requirements.

Technical Specification (P6mm Indoor Rental Slim led display PR-Slim):

产品规格 specification	PR-Fine 4	PR-Fine 4.66	PR-Fine 5.6	PR-Fine 6.22
像素点距离 Dot distance	4mm	4.66mm	5.6mm	6.22mm
箱体分辨 cabinet solution	112*126	96*108	80*90	72*80
像素点组 pixel compose	1R1G1B 3 in 1	1R1G1B 3 in 1	1R1G1B 3 in 1	1R1G1B 3 in 1
像素点密度 pixel density	62500dot/m ²	46050dot/m ²	31887dot/m ²	25847dot/m ²
箱体材质 cabinet material	Aluminum	Aluminum	Aluminum	Aluminum
箱体重量 cabinet weight	8.2KG	8.2KG	8.2KG	8.2KG
亮度 Brightness	>1450CD/m ²	>1800CD/m ²	>1800CD/m ²	>1800CD/m ²
视角 Viewing angle	H:120° V: 110°	H:120° V: 110°	H:120° V: 110°	H:120° V: 110°
刷新频率 Refresh rate	>1500HZ	>1500HZ	>1500HZ	>1500HZ



SHENZHEN PORSTAR ELECTRONICS CO.,LTD

<http://www.porstarled.net/www.pstled.com>

对比度 contrast ration	3000:1	3000:1	3000:1	3000:1
供电电压 Voltage	AC 110V-240V.50-60HZ	AC 110V-240V.50-60HZ	AC 110V-240V.50-60HZ	AC 110V-240V.50-60HZ
功耗 power consumption (AV&Max)	1100W/m ² ,560/m ²	980W/m ² ,490W/m ²	780W/m ² -390W/m ²	480W/m ² -380W/m ²
工作温度 Work Temperature	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
存储温度 Storage Temperature	-35℃~+85℃	-35℃~+85℃	-35℃~+85℃	-35℃~+85℃
工作湿度 Work humidity	10%—95%RH	10%—95%RH	10%—95%RH	10%—95%RH
使用寿命 Life	>50000H	>50000H	>50000H	>50000H
平均无故障时间 MTBF	>5000H	>5000H	>5000H	>5000H
失控比率 Ratio Control	<0.0003	<0.0003	<0.0003	<0.0003

Cabinets Style for Rental Application

