

HONGER SHEET METAL STRAIGHTENER

1. TL Straightener for material thickness 0.4-2.2mm

Model	TL-200	TL-300	TL-400	TL-500	TL-600	TL-700	TL-800
Coil Width (mm)	200	300	400	500	600	700	800
Coil Thickness (mm)	0.4-2.2						
Straightening Roller	Φ50*7			Φ60*7			
Feeding Roller	Φ60*2, Φ80*2			Φ70*2, Φ98*2			
Power (HP)	1		2		3		5
Inverter	No						
Feeding Speed (m/min)	16						

2. HS-A High Precision Straightener for material thickness 0.5-4.5mm

Model	HS-300A	HS-400A	HS-500A	HS-600A
Coil Width (mm)	300	400	500	600
Coil Thickness (mm)	0.5-4.5			
Straightening Roller	Ø70*9			
Feeding Roller	Ø95*4			
Roller Pressing Way	Cylinder Pressure			
Roller Adjustment	Eccentric turbine worm adjusting			
Power (HP)	5		7.5	
Inverter	Delta, Taiwan			
Feeding Speed (m/min)	16			

3. HS-B High Precision Straightener for material thickness 1.0-6.0mm

Model	HS-300B	HS-400B	HS-500B	HS-600B
Coil Width (mm)	300	400	500	600
Coil Thickness (mm)	1.0-6.0			
Straightening Roller	Ø90*9			
Feeding Roller	Ø120*4			
Roller Pressing Way	Cylinder Pressure			
Roller Adjustment	Eccentric turbine worm adjusting			
Power (HP)	5		7.5	
Inverter	Delta, Taiwan			
Feeding Speed (m/min)	16			

4. High Speed S-loop Straightener

Model	JMS-200	JMS-300
Coil Width (mm)	200	300
Coil Thickness (mm)	0.3-1.2	
Straightening Roller	Ø32*15	
Roller Adjustment	4 points adjusting	
Transmission Way	Bottom gear drive	
Power (HP)	1	
Inverter	No	
Feeding Speed (m/min)	16	

5. High Precision Straightener SNL for material thickness 0.1-0.6mm

Model	SNL-150	SNL-200	SNL-300	SNL-400
Coil Width (mm)	150	200	300	400
Coil Thickness (mm)	0.1-0.6			
Straightening Roller	Ø20*19			
Roller Adjustment	4 points adjusting			
Transmission Way	Bottom gear drive			
Power (HP)	0.5		1	
Inverter	No			
Feeding Speed (m/min)	16			

Please contact with our sales team to find a suitable configuration for your material:

Email: export@he-machine.com

Tel: +86 755 28372363

Add: F1601-02, A4 Bldg Zhujiang Plaza, Longgang, Shenzhen, 518172, China

www.hongerjixie.com