



Test Report: HVG-65-54

65W Constant Voltage + Constant Current LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ **ESIGN VERIFY TEST**

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RIPPLE & NOISE	V1 : 300 mVp-p (Max)	I/P : 347VAC O/P : FULL LOAD Ta : 25°C	V1 : 29 mVp-p (Max)
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 49V ~ 58 V	I/P : 480 VAC I/P : 347 VAC O/P : MIN LOAD Ta : 25°C	47.29 V ~ 60.79 V / 480 VAC 47.284 V ~ 60.79 V / 347 VAC
3	OUTPUT CURRENT ADJUST RANGE	CH1 : 0.72A~1.21A	I/P : 480 VAC I/P : 347 VAC O/P : CV MODE Ta : 25°C	0.510 A~ 1.338 A / 480 VAC 0.508 A~ 1.336 A / 347 VAC
4	OUTPUT VOLTAGE TOLERANCE	V1 : 1%~ -1 % (Max)	I/P : 180 VAC / 480 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.029 %~ -0.029 %
5	LINE REGULATION	V1 : 0.5 %~ -0.5% (Max)	I/P : 180 VAC ~ 480 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ -0.012 %
6	LOAD REGULATION	V1 : 0.5 %~ -0.5% (Max)	I/P : 347 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.023 %~ -0.034 %
7	SET UP TIME	480 VAC : 400 ms (Max) 347VAC : 400 ms(Max) 230VAC : 500 ms(Max)	I/P : 480 VAC I/P : 347 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	480 VAC/ 169 ms 347VAC/ 268 ms 230VAC/ 329 ms
8	RISE TIME	480 VAC : 80 ms (Max) 347VAC : 80 ms (Max) 230VAC : 80 ms (Max)	I/P : 480 VAC I/P : 347 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	480 VAC/ 51 ms 347VAC/ 52 ms 230VAC/ 52 ms
9	HOLD UP TIME	480 VAC : 30 ms (TYP) 347VAC : 16 ms (TYP)	I/P : 480 VAC I/P : 347 VAC O/P : FULL LOAD Ta : 25°C	480 VAC/ 37.2 ms 347VAC/ 16.6 ms
10	OVER/UNDERSHOOT TEST	< ±5%	I/P : 347 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %

11	DYNAMIC LOAD	V1 : 5400 mVp-p	I/P : 347VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)290 mVp-p (2)180 mVp-p (3)180 mVp-p (4)640 mVp-p																																																																																																																																																																																																						
12	<p>DIMMER TEST (B Type only) SPEC: ※Built-in 3 in 1 dimming function, IP67 rated. Output constant current level can be adjusted through output cable by connecting a resistance or 0 ~ 10Vdc or 10V PWM signal between DIM+ and DIM-. ※Please DO NOT connect "DIM-" to "-V". ※Reference resistance value for output current adjustment (Typical)</p> <table border="1" data-bbox="151 835 1326 947"> <tr> <th>Resistance value</th> <th>Short</th> <th>10K</th> <th>20K</th> <th>30K</th> <th>40K</th> <th>50K</th> <th>60K</th> <th>70K</th> <th>80K</th> <th>90K</th> <th>100K</th> <th>OPEN</th> </tr> <tr> <td>Output current</td> <td>0%</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> <td>95%~108%</td> </tr> </table> <p>*1 ~ 10V dimming function for output current adjustment (Typical)</p> <table border="1" data-bbox="151 981 1326 1093"> <tr> <th>Dimming value</th> <th>Short</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>6V</th> <th>7V</th> <th>8V</th> <th>9V</th> <th>10V</th> <th>OPEN</th> </tr> <tr> <td>Output current</td> <td>0%</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> <td>95%~108%</td> </tr> </table> <p>*10V PWM signal for output current adjustment (Typical) : Frequency range :100Hz ~ 3KHz</p> <table border="1" data-bbox="151 1126 1326 1238"> <tr> <th>Duty value</th> <th>Short</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> <th>OPEN</th> </tr> <tr> <td>Output current</td> <td>0%</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> <td>95%~108%</td> </tr> </table> <p>TEST RESULT: I/P : 230 VAC ;Ta : 25°C</p> <table border="1" data-bbox="151 1305 1369 1727"> <tr> <td rowspan="3">1</td> <td>Resistance value</td> <td>SHORT</td> <td>10K</td> <td>20K</td> <td>30K</td> <td>40K</td> <td>50K</td> <td>60K</td> <td>70K</td> <td>80K</td> <td>90K</td> <td>100K</td> <td>OPEN</td> </tr> <tr> <td>Output current</td> <td>0.000A</td> <td>0.126A</td> <td>0.246A</td> <td>0.366A</td> <td>0.486A</td> <td>0.606A</td> <td>0.725A</td> <td>0.847A</td> <td>0.964A</td> <td>1.085A</td> <td>1.197A</td> <td>1.271A</td> </tr> <tr> <td>%</td> <td>0.00%</td> <td>10.41%</td> <td>20.33%</td> <td>30.25%</td> <td>40.17%</td> <td>50.08%</td> <td>59.92%</td> <td>70.00%</td> <td>79.67%</td> <td>89.67%</td> <td>98.93%</td> <td>105.04%</td> </tr> <tr> <td rowspan="3">2</td> <td>Dimming value</td> <td>SHORT</td> <td>1V</td> <td>2V</td> <td>3V</td> <td>4V</td> <td>5V</td> <td>6V</td> <td>7V</td> <td>8V</td> <td>9V</td> <td>10V</td> <td>OPEN</td> </tr> <tr> <td>Output current</td> <td>0.000A</td> <td>0.137A</td> <td>0.252A</td> <td>0.372A</td> <td>0.500A</td> <td>0.621A</td> <td>0.741A</td> <td>0.855A</td> <td>0.982A</td> <td>1.105A</td> <td>1.221A</td> <td>1.271A</td> </tr> <tr> <td>%</td> <td>0.00%</td> <td>11.32%</td> <td>20.83%</td> <td>30.74%</td> <td>41.32%</td> <td>51.32%</td> <td>61.24%</td> <td>70.66%</td> <td>81.16%</td> <td>91.32%</td> <td>100.91%</td> <td>105.04%</td> </tr> <tr> <td rowspan="3">3</td> <td>Duty value</td> <td>SHORT</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> <td>OPEN</td> </tr> <tr> <td>Output current</td> <td>0.000A</td> <td>0.152A</td> <td>0.261A</td> <td>0.381A</td> <td>0.502A</td> <td>0.622A</td> <td>0.743A</td> <td>0.864A</td> <td>0.985A</td> <td>1.106A</td> <td>1.227A</td> <td>1.271A</td> </tr> <tr> <td>%</td> <td>0.00%</td> <td>12.56%</td> <td>21.57%</td> <td>31.49%</td> <td>41.49%</td> <td>51.40%</td> <td>61.40%</td> <td>71.40%</td> <td>81.40%</td> <td>91.40%</td> <td>101.40%</td> <td>105.04%</td> </tr> </table>				Resistance value	Short	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	OPEN	Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%	Dimming value	Short	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN	Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%	Duty value	Short	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN	Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%	1	Resistance value	SHORT	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	OPEN	Output current	0.000A	0.126A	0.246A	0.366A	0.486A	0.606A	0.725A	0.847A	0.964A	1.085A	1.197A	1.271A	%	0.00%	10.41%	20.33%	30.25%	40.17%	50.08%	59.92%	70.00%	79.67%	89.67%	98.93%	105.04%	2	Dimming value	SHORT	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN	Output current	0.000A	0.137A	0.252A	0.372A	0.500A	0.621A	0.741A	0.855A	0.982A	1.105A	1.221A	1.271A	%	0.00%	11.32%	20.83%	30.74%	41.32%	51.32%	61.24%	70.66%	81.16%	91.32%	100.91%	105.04%	3	Duty value	SHORT	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN	Output current	0.000A	0.152A	0.261A	0.381A	0.502A	0.622A	0.743A	0.864A	0.985A	1.106A	1.227A	1.271A	%	0.00%	12.56%	21.57%	31.49%	41.49%	51.40%	61.40%	71.40%	81.40%	91.40%	101.40%	105.04%
Resistance value	Short	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	OPEN																																																																																																																																																																																														
Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%																																																																																																																																																																																														
Dimming value	Short	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN																																																																																																																																																																																														
Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%																																																																																																																																																																																														
Duty value	Short	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN																																																																																																																																																																																														
Output current	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95%~108%																																																																																																																																																																																														
1	Resistance value	SHORT	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	OPEN																																																																																																																																																																																													
	Output current	0.000A	0.126A	0.246A	0.366A	0.486A	0.606A	0.725A	0.847A	0.964A	1.085A	1.197A	1.271A																																																																																																																																																																																													
	%	0.00%	10.41%	20.33%	30.25%	40.17%	50.08%	59.92%	70.00%	79.67%	89.67%	98.93%	105.04%																																																																																																																																																																																													
2	Dimming value	SHORT	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN																																																																																																																																																																																													
	Output current	0.000A	0.137A	0.252A	0.372A	0.500A	0.621A	0.741A	0.855A	0.982A	1.105A	1.221A	1.271A																																																																																																																																																																																													
	%	0.00%	11.32%	20.83%	30.74%	41.32%	51.32%	61.24%	70.66%	81.16%	91.32%	100.91%	105.04%																																																																																																																																																																																													
3	Duty value	SHORT	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN																																																																																																																																																																																													
	Output current	0.000A	0.152A	0.261A	0.381A	0.502A	0.622A	0.743A	0.864A	0.985A	1.106A	1.227A	1.271A																																																																																																																																																																																													
	%	0.00%	12.56%	21.57%	31.49%	41.49%	51.40%	61.40%	71.40%	81.40%	91.40%	101.40%	105.04%																																																																																																																																																																																													
13	CONSTANT CURRENT REGION	32.4V ~ 54V	I/P : 347 VAC O/P : FULL LOAD Ta : 25°C	O/P=32.4V :1.231 A O/P=53V: 1.231 A																																																																																																																																																																																																						

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	180VAC~528 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	158V~480V
			I/P : LOW-LINE-3V=177V HIGH-LINE+3V=531 V O/P : FULL/MIN LOAD ON : 30 Sec. OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P : 180VAC ~ 528 VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK
3	POWER FACTOR	0.98 / 230 VAC(TYP)	I/P : 230VAC	PF= 0.9959 / 230 VAC
		0.97 / 277VAC(TYP)	I/P : 277VAC	PF= 0.9912 / 277 VAC
		0.97 /347 VAC(TYP)	I/P : 347VAC	PF= 0.9792 / 347VAC
		0.93 / 480 VAC(TYP)	I/P : 480VAC O/P : FULL LOAD Ta : 25°C	PF= 0.9686 / 480VAC
4	EFFICIENCY	90% (TYP)	I/P : 347 VAC O/P : FULL LOAD Ta : 25°C	91.1 %
5	INPUT CURRENT	347V/ 0.22 A (TYP)	I/P : 347 VAC	I = 0.211 A/ 347 VAC
		480V/ 0.18 A (TYP)	I/P : 480 VAC O/P : FULL LOAD Ta : 25°C	I = 0.156 A/ 480 VAC
6	INRUSH CURRENT	480V/ 25 A (TYP) (twidth=420us measured at 50% Ipeak) COLD START	I/P : 480VAC O/P : FULL LOAD Ta : 25°C	I = 20 A/ 480VAC T50= 400 us
7	LEAKAGE CURRENT	< 0.75 mA / 480 VAC	I/P : 480 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.25 mA N-FG : 0.26 mA
8	TOTAL HARMONIC DISTORTION	Total harmonic distortion will be lower than 20% when output loading is 60% or higher at 230VAC / 277VAC / 347VAC	I/P : 230VAC I/P : 277VAC I/P : 347VAC O/P : 60% LOAD Ta : 25°C	THD : 13.38 % THD : 15.04 % THD : 12.93 %
		Total harmonic distortion will be lower than 20% when output loading is 75% or higher at 480VAC	I/P : 480VAC O/P : 75% LOAD Ta : 25°C	THD : 16.23 %

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER CURRENT	95% - 108%	I/P : 480 VAC I/P : 347 VAC O/P : TESTING Ta : 25°C	103.12%/ 480 VAC 102.89%/ 347 VAC Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH1 : 59V - 65 V	I/P : 480 VAC I/P : 347 VAC O/P : MIN LOAD Ta : 25°C	61.11V/ 480VAC 61.13V/ 347 VAC Shut down o/p voltage with auto-recovery or re-power on to recovery
3	OVER TEMPERATURE PROTECTION	SPEC : NO DAMAGE	I/P : 347 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage, recovers automatically after temperature goes down
4	SHORT PROTECTION	NO DAMAGE	I/P : 528VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Constant current limiting, recovers automatically after fault condition is removed

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated : 9A/950V	I/P : High-Line +3V = 531 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 810 V (2) 802 V (3) 546 V
2	Diode Peak Voltage	D101 Rated : 10A/200V	I/P : High-Line +3V = 531 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 168 V (2) 158 V (3) 168 V
3	Input Capacitor Voltage	C5 Rated : 22u/450V	I/P : High-Line +3V = 531 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 396 V (2) 384 V (3) 384 V
4	Control IC Voltage Test	U1 Rated : 10.3V-22.5V U2 Rated : 11V-28V	I/P : High-Line +3V = 531 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Ta : 25°C	(1) 19.3 V (2) 20.7 V (3) 19.3 V (4) 17.1 V (5) 19.1 V (6) 16.7 V

5	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 9A/950V	I/P : High-Line +3V = 531 V O/P : (1) Full Load Turn on (2) Output Short (3) Full load continue Ta : 25°C	(1) 825 V (2) 857 V (3) 817 V
---	---	--------------------	---	-------------------------------------

SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min I/P-FG : 2 KVAC/min O/P-FG : 1.5 KVAC/min	I/P-O/P : 4 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 1.8 KVAC/min Ta : 25°C	I/P-O/P : 3.28 mA I/P-FG : 2.952 mA O/P-FG : 1.966 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C/70%RH	I/P-O/P : 3.37 GΩ I/P-FG : 2.16 GΩ O/P-FG : 10.8 GΩ NO DAMAGE
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	23 mΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:230VAC/380VAC/50HZ/60HZ O/P:100/60%ELECTRONIC LOAD O/P:100%LED LOAD Ta:25°C	PASS
2	CONDUCTION	EN55015 CLASS B FCC Part 15 Subpart B	I/P: 230VAC/380VAC/50HZ/60HZ O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab
3	RADIATION	EN55015 CLASS B FCC Part 15 Subpart B	I/P: 230VAC/380VAC/50HZ/60HZ O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230VAC/380VAC/50HZ/60HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P: 230VAC/380VAC/50HZ/60HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230VAC/380VAC/50HZ/60HZ O/P:FULL LOAD Ta:25°C	CRITERIA A

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																
1	TEMPERATURE RISE TEST	MODEL : HVG-65-24 1. ROOM AMBIENT BURN-IN : 4.5 HRS I/P : 347VAC O/P : FULL LOAD Ta=33.2 °C 2. HIGH AMBIENT BURN-IN : 1 HRS I/P : 347VAC O/P : FULL LOAD Ta=65.5 °C	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 33.2 °C</th> <th>HIGH AMBIENT Ta= 65.5 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>52.5°C</td><td>82.2°C</td></tr> <tr><td>2</td><td>L2</td><td>55.3°C</td><td>84.7°C</td></tr> <tr><td>3</td><td>Q1</td><td>57.8°C</td><td>86.9°C</td></tr> <tr><td>4</td><td>U1</td><td>55.3°C</td><td>85.1°C</td></tr> <tr><td>5</td><td>Q3</td><td>60.1°C</td><td>88.9°C</td></tr> <tr><td>6</td><td>C5</td><td>56.6°C</td><td>85.4°C</td></tr> <tr><td>7</td><td>RTH2</td><td>54.1°C</td><td>83.5°C</td></tr> <tr><td>8</td><td>T1</td><td>65.0°C</td><td>93.4°C</td></tr> <tr><td>9</td><td>C62</td><td>56.7°C</td><td>85.6°C</td></tr> <tr><td>10</td><td>C46</td><td>51.7°C</td><td>81.8°C</td></tr> <tr><td>11</td><td>D101</td><td>65.5°C</td><td>95.1°C</td></tr> <tr><td>12</td><td>C102</td><td>60.3°C</td><td>89.5°C</td></tr> <tr><td>13</td><td>C203</td><td>58.9°C</td><td>87.8°C</td></tr> <tr><td>14</td><td>LF100</td><td>55.1°C</td><td>84.7°C</td></tr> <tr><td>15</td><td>C104</td><td>55.7°C</td><td>85.3°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 33.2 °C	HIGH AMBIENT Ta= 65.5 °C	1	BD1	52.5°C	82.2°C	2	L2	55.3°C	84.7°C	3	Q1	57.8°C	86.9°C	4	U1	55.3°C	85.1°C	5	Q3	60.1°C	88.9°C	6	C5	56.6°C	85.4°C	7	RTH2	54.1°C	83.5°C	8	T1	65.0°C	93.4°C	9	C62	56.7°C	85.6°C	10	C46	51.7°C	81.8°C	11	D101	65.5°C	95.1°C	12	C102	60.3°C	89.5°C	13	C203	58.9°C	87.8°C	14	LF100	55.1°C	84.7°C	15	C104	55.7°C	85.3°C	
NO	Position	ROOM AMBIENT Ta= 33.2 °C	HIGH AMBIENT Ta= 65.5 °C																																																																	
1	BD1	52.5°C	82.2°C																																																																	
2	L2	55.3°C	84.7°C																																																																	
3	Q1	57.8°C	86.9°C																																																																	
4	U1	55.3°C	85.1°C																																																																	
5	Q3	60.1°C	88.9°C																																																																	
6	C5	56.6°C	85.4°C																																																																	
7	RTH2	54.1°C	83.5°C																																																																	
8	T1	65.0°C	93.4°C																																																																	
9	C62	56.7°C	85.6°C																																																																	
10	C46	51.7°C	81.8°C																																																																	
11	D101	65.5°C	95.1°C																																																																	
12	C102	60.3°C	89.5°C																																																																	
13	C203	58.9°C	87.8°C																																																																	
14	LF100	55.1°C	84.7°C																																																																	
15	C104	55.7°C	85.3°C																																																																	
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 528VAC/180VAC O/P : 100 % LOAD Ta= -40 °C	TEST : OK																																																																
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60°C NO DAMAGE	I/P : 528 VAC O/P : FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK																																																																
4	TEMPERATURE COEFFICIENT	± 0.03%(0-60°C)	I/P : 347 VAC O/P : FULL LOAD	± 0.011 %(0-60°C)																																																																
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK																																																																
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 347VAC/Fu11 Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK																																																																

7	VIBRATION TEST	<p>1 Carton & 1 Set</p> <p>(1) Waveform : Sine Wave</p> <p>(2) Frequency : 10-500Hz</p> <p>(3) Sweep Time : 12min/sweep cycle</p> <p>(4) Acceleration : 5G</p> <p>(5) Test Time : 72min in each axis (X.Y.Z)</p> <p>(6) Ta : 25°C</p>	TEST : OK																				
8	CAPACITOR LIFE CYCLE	<p>SUPPOSE C102 IS THE MOST CRITICAL COMPONENT</p> <p>(1) I/P : 347VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME</p> <p>(2) I/P : 347VAC O/P : FULL LOAD Ta= 60 °C LIFE TIME</p> <p>(3) I/P : 347VAC O/P : 75% LOAD Ta= 60 °C LIFE TIME</p> <p>(4) I/P : 347VAC O/P : 50% LOAD Ta= 60 °C LIFE TIME</p>	<p>(1) 579367 HRS</p> <p>(2) 63534 HRS</p> <p>(3) 68662 HRS</p> <p>(4) 99873 HRS</p>																				
9	MTBF	<p>Conducted by Parts Stress Analysis Prediction</p> <p>612.6K hrs min. Telcordia SR-332 (Bellcore) ; 208K hrs min. MIL-HDBK-217F (25°C)</p>																					
10	DMTBF/Accelerated Life Test	<p>Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase 75°C</p> <table border="1"> <caption>Graph Data: Lifetime vs Tcase</caption> <thead> <tr> <th>Tcase (°C)</th> <th>LIFETIME(kh)</th> </tr> </thead> <tbody> <tr><td>20</td><td>100</td></tr> <tr><td>30</td><td>100</td></tr> <tr><td>40</td><td>100</td></tr> <tr><td>50</td><td>100</td></tr> <tr><td>60</td><td>100</td></tr> <tr><td>65</td><td>100</td></tr> <tr><td>70</td><td>70</td></tr> <tr><td>75</td><td>50</td></tr> <tr><td>80</td><td>35</td></tr> </tbody> </table>		Tcase (°C)	LIFETIME(kh)	20	100	30	100	40	100	50	100	60	100	65	100	70	70	75	50	80	35
Tcase (°C)	LIFETIME(kh)																						
20	100																						
30	100																						
40	100																						
50	100																						
60	100																						
65	100																						
70	70																						
75	50																						
80	35																						

RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT TSENG

12.10.30 A50-F031