



TEST REPORT: HVG-240-24

240W Constant Voltage + Constant Current LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test


E.M.C. Test

■ RELIABILITY TEST


ENVIRONMENT TEST

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE ADJUST RANGE	CH1: 22.40V ~ 25.60V	I/P : 347VAC O/P: MIN LOAD TA: 25°C	CH1: 20.87V ~ 26.12V
2	CONSTANT CURRENT REGION	CH1: 12V~ 24V	I/P: 347 VAC O/P:FULL LOAD Ta:25°C CV MODE TEST	0.45V~24V /347VAC
3	CURRENT ADJ. RANGE	CH1:5A~ 10A	I/P: 347 VAC I/P:230VAC O/P:CV MIN & CV MAX-1V Ta:25°C CV MODE TEST	3.897A~10.651A/347VAC@CV MAX-1V 3.886A~10.696A /347VAC@CV MIN 3.892A~10.651A/230VAC@CV MAX-1V 3.89A~ 10.697A/230VAC@CV MIN
4	OUTPUT VOLTAGE TOLERANCE (Max)	V1 : 1.0% ~ -1.0%	I/P : 180VAC / 528VAC O/P: FULL / MINLOAD TA= 25°C	V1: 0.19% ~ -0.18%
5	LINE REGULATION (MAX.)	V1 : 0.5% ~ -0.5%	I/P : 180VAC / 528VAC O/P: FULL LOAD TA : 25°C	V1: 0.00% ~ 0.00%
6	LOAD REGULATION (MAX.)	V1 : 0.5% ~ -0.5%	I/P : 347VAC O/P: MIN LOAD ~ FULL LOAD TA : 25°C	V1: 0.19% ~ -0.18%
7	OVER/UNDERSHOOT TEST	< ±5%	I/P : 347VAC O/P: FULL LOAD TA : 25°C	TEST < ±5%
8	RIPPLE & NOISE(Max)	V1 : 150 mVp-p	I/P : 347VAC O/P: FULL LOAD TA : 25°C	V1 : 40.2 mVp-p
		<p>low frequency :</p> <p>DSD-X 3024A, MY65140424 Mon Oct 19 16:49:53 2015</p> <p>1 2 3 10% 4 0.0s 5.000s/ 停止</p> <p>DC +3.05000A 5.00:1 AC +0.0V 10.0:1 AC BW 1.00:1 AC BW +0.0V 1000:1</p>		
SET UP TIME (MAX.)	347VAC : 500ms 230VAC : 500ms 480VAC : 500ms	I/P : 347VAC I/P : 230VAC I/P : 480VAC O/P: FULL LOAD TA : 25°C	347VAC: 368.0ms 230VAC 296ms 480VAC 376ms	




RISE TIME (MAX.)	347VAC : 150ms	I/P : 347VAC	347VAC: 28ms
	230VAC : 150ms	I/P : 230VAC	230VAC : 29ms
	480VAC : 150ms	I/P : 480VAC	480VAC : 27.6ms
		O/P: FULL LOAD	
		TA : 25°C	



HOLD UP TIME (TYP.)	347VAC : 12ms	I/P : 347VAC	347VAC: 22.8ms
	480VAC : 12ms	I/P : 480VAC	480VAC: 23.2ms
		O/P: FULL LOAD	
		TA : 25°C	




DYNAMIC LOAD	V1 : 2400 mVp-p	I/P : 347VAC	(1). (2). unit:mVp
		O/P:	V1: 1990mv 500mv
		(1)Full/Min load 50%duty/120HZ	
		(2)Full/Min load 50%duty/1KHZ	
		TA : 25°C	




INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	180VAC ~ 528VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE = 177VAC HIGH-LINE = 538VAC O/P : FULL/MIN LOAD ON:30 Sec ; OFF:30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	134.0VAC ~ 528VAC TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~ 63HZ NO DAMAGE	I/P : 200VAC ~ 528VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK
3	INPUT CURRENT (TYP.)	0.8 / 347VAC 0.6 / 480VAC	I/P : 347VAC I/P : 480VAC O/P: FULL LOAD TA : 25°C	I= 0.7493 / 347VAC I= 0.5458 / 480VAC
4	LEAKAGE CURRENT	< 0.75mA	I/P : 480VAC O/P: MIN LOAD TA : 25°C	L-FG: 0.175 mA N-FG: 0.197 mA
	POWER FACTOR (TYP.)	0.95 / 347VAC 0.93 / 480VAC 0.97 / 277VAC 0.98 / 230VAC	I/P : 347VAC I/P : 480VAC I/P : 277VAC I/P : 230VAC O/P: FULL LOAD TA : 25°C	PF= 0.99 / 347VAC PF= 0.9748 / 480VAC PF= 0.9917 / 277VAC PF= 0.9933 / 230VAC




EFFICIENCY (TYP.)	92.5%	I/P : 347VAC O/P: FULL LOAD TA: 25°C	92.51 %
-------------------	-------	--	---------

6




TOTAL HARMONIC DISTORTION	Total harmonic distortion will be lower than 20% when output loading is 50% or higher at 230VAC / 277VAC / 347VAC / 480VAC	I/P : 347VAC / 50% LOAD I/P : 480VAC / 50% LOAD TA: 25°C	THD : 10.569 / 347VAC THD : 16.542 / 480VAC
---------------------------	--	--	--

7



INRUSH CURRENT (TYP.)	50A / 480VAC twidth= 532 us measured at 50% Ipeak COLD START	I/P : 480VAC O/P: FULL LOAD TA: 25°C	I= 41A / 480VAC T50= 532 us
-----------------------	--	--	--------------------------------

8





DIMMING OPERATION (for B-Type)



※ 3 in 1 dimming function (for B-Type)

- Output constant current level can be adjusted by applying one of the three methodologies between DIM+ and DIM-: 0 ~ 10VDC, or 10V PWM signal or resistance.
- Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.
- Dimming source current from power supply: 100 μ A (typ.)



◎ Applying additive 0 ~ 10VDC



◎ Applying additive 10V PWM signal (frequency range 100Hz ~ 3KHz):



◎ Applying additive resistance:




- Note : 1. Min. dimming level is about 5% and the output current is not defined when 0% < I_{out} < 5%.
 2. The output current could drop down to 0% when dimming input is about 0k Ω or 0Vdc, or 10V PWM signal with 0% duty cycle.

24V	R	SHORT	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	OPEN
	O/P CURRENT	0.00000A	1.083A	2.061A	3.043A	4.071A	5.061A	6.056A	7.069A	8.055A	9.071A	10.100A	10.355A
%	0.00%	10.83%	20.61%	30.43%	40.71%	50.61%	60.56%	70.69%	80.55%	90.71%	101.00%	103.55%	
24V	V	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN
	O/P CURRENT	0.00000A	1.146A	2.153A	3.085A	4.127A	5.135A	6.112A	7.149A	8.082A	9.094A	10.021A	10.355A
%	0.00%	11.46%	21.53%	30.85%	41.27%	51.35%	61.12%	71.49%	80.82%	90.94%	100.21%	103.55%	
24V	PWM (100HZ)	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN
	O/P CURRENT	0.00000A	1.153A	2.138A	3.142A	4.170A	5.158A	6.145A	7.125A	8.098A	9.073A	10.036A	10.355A
%	0.00%	11.53%	21.38%	31.42%	41.70%	51.58%	61.45%	71.25%	80.98%	90.73%	100.36%	103.55%	

※ Smart timer dimming function (for Dxx-Type by User definition)

MEAN WELL Smart timer dimming primarily provides the adaptive proportion dimming profile for the output constant current level to perform up to 14 consecutive hours. 3 dimming profiles hereunder are defined accounting for the most frequently seen applications. If other options may be needed, please contact MEAN WELL for details.

Ex : Ⓒ D01-Type: the profile recommended for residential lighting



Set up for D01-Type in Smart timer dimming software program:


	T1	T2	T3	T4
TIME**	06:00	07:00	11:00	---
LEVEL**	100%	70%	50%	70%

** : TIME matches Operating Time in the diagram whereas LEVEL matches Dimming Level.

Example: If a residential lighting application adopts D01-Type, when turning on the power supply at 6:00pm, for instance:

- [1] The power supply will switch to the constant current level at 100% starting from 6:00pm.
- [2] The power supply will switch to the constant current level at 70% in turn, starting from 0:00am, which is 06:00 after the power supply turns on.
- [3] The power supply will switch to the constant current level at 50% in turn, starting from 1:00am, which is 07:00 after the power supply turns on.
- [4] The power supply will switch to the constant current level at 70% in turn, starting from 5:00am, which is 11:00 after the power supply turns on. The constant current level remains till 8:00am, which is 14:00 after the power supply turns on.

Ex : Ⓒ D02-Type: the profile recommended for street lighting



Set up for D02-Type in Smart timer dimming software program:


	T1	T2	T3	T4	T5
TIME**	01:00	03:00	8:00	11:00	---
LEVEL**	50%	80%	100%	60%	80%

** : TIME matches Operating Time in the diagram whereas LEVEL matches Dimming Level.

Example: If a street lighting application adopts D02-Type, when turning on the power supply at 5:00pm, for instance:

- [1] The power supply will switch to the constant current level at 50% starting from 5:00pm.
- [2] The power supply will switch to the constant current level at 80% in turn, starting from 6:00pm, which is 01:00 after the power supply turns on.
- [3] The power supply will switch to the constant current level at 100% in turn, starting from 8:00pm, which is 03:00 after the power supply turns on.
- [4] The power supply will switch to the constant current level at 60% in turn, starting from 1:00am, which is 08:00 after the power supply turns on.
- [5] The power supply will switch to the constant current level at 80% in turn, starting from 4:00am, which is 11:00 after the power supply turns on. The constant current level remains till 6:30am, which is 14:00 after the power supply turns on.

Ex : Ⓒ D03-Type: the profile recommended for tunnel lighting



Set up for D03-Type in Smart timer dimming software program:

	T1	T2	T3
TIME**	01:30	11:00	---
LEVEL**	70%	100%	70%

** : TIME matches Operating Time in the diagram whereas LEVEL matches Dimming Level.

Example: If a tunnel lighting application adopts D03-Type, when turning on the power supply at 4:30pm, for instance:

- [1] The power supply will switch to the constant current level at 70% starting from 4:30pm.
- [2] The power supply will switch to the constant current level at 100% in turn, starting from 6:00pm, which is 01:30 after the power supply turns on.
- [3] The power supply will switch to the constant current level at 70% in turn, starting from 5:00am, which is 11:00 after the power supply turns on. The constant current level remains till 6:30am, which is 14:00 after the power supply turns on.

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95% ~ 108%	I/P: 528VAC I/P: 180VAC O/P: TESTING TA: 25°C	105.0% /528VAC 105.2% /180 VAC Constant Current Limiting
2	OVER VOLTAGE PROTECTION	27.00V ~ 34.00V	I/P: 528VAC I/P: 180VAC O/P: MIN LOAD TA: 25°C	29.6 528VAC 29.6 180VAC Shut down Re- power ON
3	OVER TEMPERATURE PROTECTION	Shut down Re- power ON	I/P: 347VAC O/P: FULL LOAD	O.T.P. Active Shut down Re- power ON
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 528VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	Q901 Rated : 950V 9.0A	I/P : 531VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz (6)Dynamic Load Full/Min Load 50%Duty/120Hz (7)0%→400% Load Ta : 25°C	VIN: 531VAC VDS: (1). 863.0V (2). 831.0V (3). 799.0V (4). 863.0V (5). 871.0V (6). 871.0V (7). 823.0V
2	O/P Diode (MOSFET)	Q101 Rated : 80V 120.0A Q102 Rated : 80V 120.0A	I/P : 531VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz (6)Dynamic Load Full/Min Load 50%Duty/120Hz (7)0%→400% Load (8) NO LOAD Ta : 25°C	Q101 Q102 VDS : VDS : (1). 71.9V 71.9V (2). 16.8V 13.5V (3). 58.2V 59.0V (4). 67.8V 71.9V (5). 67.0V 72.7V (6). 67.8V 77.5V (7). 56.6V 57.4V (8). 51.0V 51.0V
3	Input Capacitor	C5 Rated : 82uf 450V	I/P : 531VAC O/P : (1)Full Load Turn on /Off (2)Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1). 421.0V (2). 441.0V (3). 396.0V
4	Control IC	U1 Rated : 20V (max) 10V (min)	I/P : 531VAC O/P : (1)Full Load (2)Output Short Change (4)O.V.P (5)Low Line No Load Vo(min) Ta : 25°C	U1 (1). 15.1V (2). 15.1V (3). 13.5V (4). 15.1V (5). 11.5V
5	PFC Power Transistor	Q1 Rated : 1050V 9.0A	I/P : 531VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz 50%Duty/120Hz	VIN: 531VAC VDS: (1). 849.0V (2). 969.0V (3). 849.0V (4). 865.0V (5). 873.0V (6). 849.0V

		(7)0%→400% Load	(7). 849.0V
		Ta : 25°C	

SAFETY & E.M.C. TEST
SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75KVAC /min I/P-FG : 2.0KVAC /min O/P-FG : 1.5KVAC /min	I/P-O/P: 4.13KVAC /min I/P-FG: 2.40KVAC /min O/P-FG: 1.80KVAC /min Ta : 25°C	I/P-O/P: 2.0mA I/P-FG: 1.9mA O/P-FG: 1.0mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P: 500VDC I/P-FG: 500VDC O/P-FG: 500VDC Ta : 25°C/70%RH	I/P-O/P: 15.6GΩ I/P-FG: 19.8GΩ O/P-FG: 30GΩ NO DAMAGE
2	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C/70%RH	26 mΩ

E.M.C. TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONDUCTION	FCC Part 15 Subpart B	I/P : 440VAC/60HZ O/P : FULL LOAD / 30% LOAD Ta : 25°C	PASS Test by certified Lab
2	RADIATION	FCC Part 15 Subpart B	I/P : 480VAC/60HZ O/P : FULL LOAD / 10% LOAD Ta : 25°C	PASS Test by certified Lab
3	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
4	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
5	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV;L/N-PE : 4KV	I/P : 230VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A

RELIABILITY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																												
1	TEMPERATURE RISE TEST	MODEL : HVG-240-24 1. ROOM AMBIENT BURN-IN : 3.0hrs IP: 230VAC O/P: 100% LOAD TA= 24.8°C 2. HIGH AMBIENT BURN-IN : 2.0hrs IP: 230VAC O/P: 100% LOAD TA= 59.2°C																																																																														
<table border="1"> <thead> <tr> <th>CH.</th> <th>Position</th> <th>ROOM AMBIENT Ta= 24.8°C</th> <th>HIGH AMBIENT Ta= 59.2°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>62.0°C</td><td>93.3°C</td></tr> <tr><td>2</td><td>Q1</td><td>62.5°C</td><td>94.5°C</td></tr> <tr><td>3</td><td>Q901</td><td>63.9°C</td><td>96.4°C</td></tr> <tr><td>4</td><td>L2</td><td>60.7°C</td><td>91.6°C</td></tr> <tr><td>5</td><td>C2</td><td>58.9°C</td><td>88.5°C</td></tr> <tr><td>6</td><td>C10</td><td>61.3°C</td><td>92.9°C</td></tr> <tr><td>7</td><td>L1</td><td>64.2°C</td><td>97.1°C</td></tr> <tr><td>8</td><td>ZNR2</td><td>76.4°C</td><td>103.3°C</td></tr> <tr><td>9</td><td>RTH3</td><td>58.8°C</td><td>90.5°C</td></tr> <tr><td>10</td><td>T1</td><td>68.5°C</td><td>103.7°C</td></tr> <tr><td>11</td><td>C46</td><td>62.0°C</td><td>93.8°C</td></tr> <tr><td>12</td><td>C54</td><td>60.6°C</td><td>92.1°C</td></tr> <tr><td>13</td><td>Q102</td><td>62.0°C</td><td>94.8°C</td></tr> <tr><td>14</td><td>C102</td><td>59.6°C</td><td>91.8°C</td></tr> <tr><td>15</td><td>C201</td><td>63.0°C</td><td>94.5°C</td></tr> <tr><td>16</td><td>C200</td><td>61.7°C</td><td>93.6°C</td></tr> <tr><td>17</td><td>U1</td><td>63.6°C</td><td>95.2°C</td></tr> <tr><td>20</td><td>C5</td><td>61.9°C</td><td>93.4°C</td></tr> </tbody> </table>					CH.	Position	ROOM AMBIENT Ta= 24.8°C	HIGH AMBIENT Ta= 59.2°C	1	BD1	62.0°C	93.3°C	2	Q1	62.5°C	94.5°C	3	Q901	63.9°C	96.4°C	4	L2	60.7°C	91.6°C	5	C2	58.9°C	88.5°C	6	C10	61.3°C	92.9°C	7	L1	64.2°C	97.1°C	8	ZNR2	76.4°C	103.3°C	9	RTH3	58.8°C	90.5°C	10	T1	68.5°C	103.7°C	11	C46	62.0°C	93.8°C	12	C54	60.6°C	92.1°C	13	Q102	62.0°C	94.8°C	14	C102	59.6°C	91.8°C	15	C201	63.0°C	94.5°C	16	C200	61.7°C	93.6°C	17	U1	63.6°C	95.2°C	20	C5	61.9°C	93.4°C
CH.	Position	ROOM AMBIENT Ta= 24.8°C	HIGH AMBIENT Ta= 59.2°C																																																																													
1	BD1	62.0°C	93.3°C																																																																													
2	Q1	62.5°C	94.5°C																																																																													
3	Q901	63.9°C	96.4°C																																																																													
4	L2	60.7°C	91.6°C																																																																													
5	C2	58.9°C	88.5°C																																																																													
6	C10	61.3°C	92.9°C																																																																													
7	L1	64.2°C	97.1°C																																																																													
8	ZNR2	76.4°C	103.3°C																																																																													
9	RTH3	58.8°C	90.5°C																																																																													
10	T1	68.5°C	103.7°C																																																																													
11	C46	62.0°C	93.8°C																																																																													
12	C54	60.6°C	92.1°C																																																																													
13	Q102	62.0°C	94.8°C																																																																													
14	C102	59.6°C	91.8°C																																																																													
15	C201	63.0°C	94.5°C																																																																													
16	C200	61.7°C	93.6°C																																																																													
17	U1	63.6°C	95.2°C																																																																													
20	C5	61.9°C	93.4°C																																																																													

2	LOW TEMPERATURE TURN ON TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 528VAC / 180VAC O/P : FULL LOAD Ta : -45.0°C	TEST : OK
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60°C NO DAMAGE	I/P : 528VAC O/P : FULL LOAD Ta : 60°C HUMIDITY= 95.0% RH	TEST : OK
4	TEMPERATURE COEFFICIENT	±0.03% /°C(0~60°C)	I/P : 347VAC O/P : FULL LOAD	±0.01% /°C(0~60°C)
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C ~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		TEST : OK
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C ~ 65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 230V Full Load AC ON/OFF to turn on 3sec ; turn off 1sec @ 15cycle Full Load burn in@ 1cycle		TEST : OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK
8	CAPACITOR LIFE CYCLE	HVG-240-24 :SUPPOSE C102 IS THE MOST CRITICAL COMPONENT (1) I/P : 347VAC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 347VAC O/P : FULL LOAD Ta= 60°C LIFE TIME (3) I/P : 347VAC O/P : 75% LOAD Ta= 60°C LIFE TIME (4) I/P : 347VAC O/P : 50% LOAD Ta= 60°C LIFE TIME		(1). 288585 HRS (2). 29688 HRS (3). 47188 HRS (4). 84252 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 114.5K hrs min. MIL-HDBK-217F (25°C)		
10	DMTBF /Accelerated Life test	Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase80°C 		

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT ZENG