



MODEL : NSD15-12D12

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 100 mVp-p (Max) V2: 100 mVp-p (Max)	I/P: 12VDC O/P:FULL LOAD Ta:25°C	V1: 20 mVp-p (Max) V2: 20 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 %- -2 % (Max) V2: 2 %- -2 % (Max)	I/P: 9.4VDC / 36VDC O/P:FULL/ 10% LOAD Ta:25°C	V1: 1.1 %- -1.1 % V2: 1.1 %- -1.1 %	P
3	LINE REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 9.4VDC ~ 36VDC O/P:FULL LOAD Ta:25°C	V1: 0.1 %- -0.1 % V2: 0.1 %- -0.1 %	P
4	LOAD REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 12VDC O/P:FULL ~10% LOAD Ta:25°C	V1: 0.2 %- -0.2 % V2: 0.2 %- -0.2 %	P
5	CROSS REGULATION	V1: 1%- -1 % (Max) V2: 1%- -1% (Max)	I/P: 12V VDC O/P: Testing O/P 60%LOAD Other O/P 40%LOAD Change Ta:25°C	V1: 0.89 %- -0.6 % V2: 0.84 %- -0.7 %	P
6	OVER/UNDERSHOOT TEST	< ±5%	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
7	DYNAMIC LOAD	V1: 1200 mVp-p	I/P: 12VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	426 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9.4VDC~ 36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.1 V~36 V	P
			I/P: LOW-LINE-0.2V= 9.2 V HIGH-LINE+5%= 37.8 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	80 % (TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	81.8 %	P
3	INPUT CURRENT	12 VDC/ 1.8A(TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	I = 1.5 A	P
4	SHUTDOWN IDLE CURRENT	20 mA / 12VDC	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	17 mA / 12VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 12VDC O/P: TESTING Ta: 25°C	177 % / 12V Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 13.8 V~ 18V CH2: -13.8 V~ -18V	I/P: DC SOURCE O/P: MIN LOAD Ta: 25°C	15.5 V / CH1 / 0.15A 15.5V / CH2 / 0.15A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 60 SECOND NO DAMAGE	I/P: 36 VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : NSD15-12D5 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 12 VDC O/P: FULL LOAD Ta=28.2°C 2. HIGH AMBIENT BURN-IN : 1HRS I/P: 12 VDC O/P: FULL LOAD Ta= 59.1°C			P																																																												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 28.2 °C</th> <th>HIGH AMBIENT Ta= 59.1°C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>L100</td> <td>TS026</td> <td>79.4°C</td> <td>106.0°C</td> </tr> <tr> <td>2</td> <td>T1 COIL</td> <td>147PE5151</td> <td>89.0°C</td> <td>115.6°C</td> </tr> <tr> <td>3</td> <td>Q2</td> <td>CET1012 10A/120V</td> <td>87.0°C</td> <td>114.5°C</td> </tr> <tr> <td>4</td> <td>L1</td> <td>1.4UH</td> <td>84.2°C</td> <td>109.2°C</td> </tr> <tr> <td>5</td> <td>Q1</td> <td>BCX56 1A/80V</td> <td>77.9°C</td> <td>105.4°C</td> </tr> <tr> <td>6</td> <td>U1</td> <td>TL3843D</td> <td>81.7°C</td> <td>108.4°C</td> </tr> <tr> <td>7</td> <td>D100</td> <td>MBRD660CT 6A/60V</td> <td>85.6°C</td> <td>112.5°C</td> </tr> <tr> <td>8</td> <td>D200</td> <td>MBRD660CT 6A/60V</td> <td>83.6°C</td> <td>109.5°C</td> </tr> <tr> <td>9</td> <td>C106</td> <td>100U/10V 125°C</td> <td>72.7°C</td> <td>98.2°C</td> </tr> <tr> <td>10</td> <td>ZD2</td> <td>SMAJ90A</td> <td>85.9°C</td> <td>114.2°C</td> </tr> <tr> <td>11</td> <td>CASE</td> <td>上方中間處</td> <td>75.3°C</td> <td>102.4°C</td> </tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 28.2 °C	HIGH AMBIENT Ta= 59.1°C	1	L100	TS026	79.4°C	106.0°C	2	T1 COIL	147PE5151	89.0°C	115.6°C	3	Q2	CET1012 10A/120V	87.0°C	114.5°C	4	L1	1.4UH	84.2°C	109.2°C	5	Q1	BCX56 1A/80V	77.9°C	105.4°C	6	U1	TL3843D	81.7°C	108.4°C	7	D100	MBRD660CT 6A/60V	85.6°C	112.5°C	8	D200	MBRD660CT 6A/60V	83.6°C	109.5°C	9	C106	100U/10V 125°C	72.7°C	98.2°C	10	ZD2	SMAJ90A	85.9°C	114.2°C	11	CASE	上方中間處	75.3°C	102.4°C		
NO	Position	P/N	ROOM AMBIENT Ta= 28.2 °C	HIGH AMBIENT Ta= 59.1°C																																																													
1	L100	TS026	79.4°C	106.0°C																																																													
2	T1 COIL	147PE5151	89.0°C	115.6°C																																																													
3	Q2	CET1012 10A/120V	87.0°C	114.5°C																																																													
4	L1	1.4UH	84.2°C	109.2°C																																																													
5	Q1	BCX56 1A/80V	77.9°C	105.4°C																																																													
6	U1	TL3843D	81.7°C	108.4°C																																																													
7	D100	MBRD660CT 6A/60V	85.6°C	112.5°C																																																													
8	D200	MBRD660CT 6A/60V	83.6°C	109.5°C																																																													
9	C106	100U/10V 125°C	72.7°C	98.2°C																																																													
10	ZD2	SMAJ90A	85.9°C	114.2°C																																																													
11	CASE	上方中間處	75.3°C	102.4°C																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 12VDC O/P: 120 % LOAD Ta:25°C	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 12 VDC O/P: 100 % LOAD Ta= -25°C	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P: 39 VDC O/P:FULL LOAD Ta= 60°C HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-60°C)	I/P: 12 VDC O/P:FULL LOAD	± 0.001 %(0-60°C)	P																																																												
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																												

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVDC/min	I/P-O/P: 1.8KVDC/min Ta:25°C	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C / 70% RH	I/P-O/P: 30GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1673.1K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated CUE1012 : 120 V 10 A	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 67 V (2) 74 V	P
2	Diode Peak Voltage	D100 Rated STPS10170CB 10A/170V D200 Rated STPS10170CB 10A/170V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 104 V (2) 24 V (1) 108 V (2) 105 V	P
3	Input Capacitor Voltage	C5 Rated : 105 / 50V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 39 V (2) 39 V (3) 39 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 20 V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 11.4 V (2) 10.9 V (3) 11.4 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/2/16	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
	PRODUCT SAMPLE W0703C68	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023