



Test Report : MHB100-48S12

100W DC-DC Half-Brick Regulated Single Output Converter

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1%~+1% (Max)	I/P:48VDC O/P:100% LOAD Ta:25°C	0.20%	P
2	RIPPLE & NOISE	150mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	19 mV	P
3	LINE REGULATION	-0.2%~+0.2% (Max)	I/P:36VDC~75VDC O/P:FULL LOAD Ta:25°C	-0.05% ~ +0.01%	P
4	LOAD REGULATION	-0.2%~+0.2% (Max)	I/P:48VDC O/P:MIN-FULL LOAD Ta:25°C	-0.04% ~ +0.03%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	36VDC~75VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	32.03~75VDC	P
2	EFFICIENCY	89% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	90.3%	P
3	DC CURRENT	2445mA / FULL LOAD (Max) 50 mA / NO LOAD (Max)	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	2303 mA / FULL LOAD 19 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110% ~ 140% (Max)	I/P:48VDC O/P:TESTING Ta:25°C	127.7% HICCUP MODE AUTO-RECOVER	P
2	OVER VOLTAGE PROTECTION	115% ~ 140% (Max)	I/P: TESTING O/P: MIN LOAD Ta:25°C	CLAMP BY ZENER DIODE	P
3	OVER TEMPERATURE PROTECTION	CASE:100 +/- 5°C NO DAMAGE	I/P:48VDC O/P:FULL LOAD	99.8°C	P
4	INPUT UNDER VOLTAGE LOCKOUT	Power Up 34V (Typ) Power Down 32.5V (Typ)	I/P:TESTING O/P: 10% LOAD Ta:25°C	Vin turn off : 32.03V Vin turn on : 33.38V	P

5	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:75VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P
---	------------------	--	---------------------------------------	--	---

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C ~ -Vin:open Power off : R.C ~ -Vin <0.8Vdc	I/P:48VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>2.1Vdc or Open Power off : R.C<2.0Vdc or Short	P
2	TRIM CONTROL	+10%~ -10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 10k ohm VR	I/P:48VDC O/P:FULL LOAD Ta:25°C	Trim DOWN -11.86% Trim UP +20.13%	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 3 HOURS	I/P:48VDC O/P: 100% LOAD Ta= -40°C	TEST : OK	P

TEST RESULT	TESTER	APPROVAL
PASS	PETER CHENG	VINCNET ZENG