



Test Report : SKA40B-05

35W DC-DC Regulated Single Output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:24VDC O/P:100% LOAD Ta:25°C	0.26%	P
2	RIPPLE & NOISE	60mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	40mV	P
3	LINE REGULATION	-0.5%~+0.5% (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	-0% ~ +0.04%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:24VDC O/P:MIN-FULL LOAD Ta:25°C	-0.28% ~ +0.14%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	15.6~36VDC	P
2	EFFICIENCY	92% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	92.07%	P
3	DC CURRENT	1900 mA / FULL LOAD (Max) 100 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	1815mA / FULL LOAD 86 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~180% (Typ)	I/P:24VDC O/P:TESTING Ta:25°C	119% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >2.5Vdc or open Power off : R.C <0.5Vdc or short (-Vin)	I/P:24VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>1.1Vdc or Open Power off : R.C<1.1Vdc or Short	P
2	REMOTE SENSE	YES	I/P:24VDC O/P:FULL LOAD Ta:25°C	+SENSE OK -SENSE OK	P
3	TRIM CONTROL	+10%~ -10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 500k ohm VR	I/P:24VDC O/P:FULL LOAD Ta:25°C	Trim DOWN -9.81% Trim UP +10.33%	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT									
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 19HRS I/P:24VDC O/P:FULL LOAD Ta=60°C			* NOTE1									
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>64.8°C</td> <td>99.8°C</td> </tr> </tbody> </table>				NO	Position	P/N	1	2	1	CASE	CENTER	64.8°C
NO	Position	P/N	1	2										
1	CASE	CENTER	64.8°C	99.8°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 3 HOURS	I/P:24VDC O/P: 100% LOAD Ta= -40°C	TEST : OK	P									

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010.3.17	RD SAMPLE	PASS	PETER	VINCENT ZENG