



Test Report : GS36x05

AC-DC Industrial Adaptor

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	90 mVp-p (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	52 mVp-p	P
2	VOLTAGE TOLERANCE	-5% ~ +5% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD Ta:25°C	-3.46% ~ +2.98%	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD Ta:25°C	-0.29% ~ +0.03%	P
4	LOAD REGULATION	-5% ~ +5% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	-3.14% ~ +2.98%	P
5	SET UP TIME	1000 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	132.4 mS	P
6	RISE TIME	20 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	6.4 mS	P
7	HOLD UP TIME	15 mS (Min)	I/P:115VAC O/P:FULL LOAD Ta:25°C	23.0 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC ~ 264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	68V ~ 264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	76.5% (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	77.15%	P
4	AVERAGE EFFICIENCY	79.45% (LEVEL V)	I/P:115/230VAC O/P:25%、50%、75%、100% LOAD Ta:25°C	79.73% (115VAC) 79.89% (230VAC)	P
5	AC CURRENT	0.7A (Max)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.44A	P
6	NO LOAD POWER CONSUMPTION	< 0.3W (Max)	I/P:230VAC O/P: NO LOAD Ta:25°C	0.11W	P

7	INRUSH CURRENT	< 60A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	54.9A	P
8	LEAKAGE CURRENT	< 0.25mA	I/P:240VAC O/P:Min LOAD Ta:25°C	L-FG: 0.02mA N-FG: 0.02mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110% ~ 250%	I/P:230VAC O/P:TESTING Ta:25°C	156% HICCUP MODE RESET : AUTO RECOVER	P
2	OVER VOLTAGE PROTECTION	105% ~ 135%	I/P:230VAC O/P:MIN LOAD Ta:25°C	124% (1N4735A) Clamp by ZENER diode	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE RESET AUTO RECOVER	P

■ SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:4242 VDC/min	I/P-O/P:4242 VDC/min Ta:25°C	I/P-O/P: 0.03uA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																				
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:100% LOAD Ta=25°C 2. ROOM AMBIENT BURN-IN : 4HRS I/P:115VAC O/P:100% LOAD Ta=25°C	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>I/P C5</td> <td>54.9°C</td> <td>57.0°C</td> </tr> <tr> <td>2</td> <td>BD1</td> <td>53.7°C</td> <td>59.7°C</td> </tr> <tr> <td>3</td> <td>Q1</td> <td>69.7°C</td> <td>71.3°C</td> </tr> <tr> <td>4</td> <td>C40</td> <td>57.9°C</td> <td>57.1°C</td> </tr> <tr> <td>5</td> <td>T1</td> <td>61.4°C</td> <td>61.6°C</td> </tr> <tr> <td>6</td> <td>O/P D100</td> <td>74.4°C</td> <td>66.5°C</td> </tr> <tr> <td>7</td> <td>O/P C105</td> <td>60.2°C</td> <td>61.5°C</td> </tr> <tr> <td>8</td> <td>CASE</td> <td>49.6°C</td> <td>52.0°C</td> </tr> </tbody> </table>	NO	Position	1	2	1	I/P C5	54.9°C	57.0°C	2	BD1	53.7°C	59.7°C	3	Q1	69.7°C	71.3°C	4	C40	57.9°C	57.1°C	5	T1	61.4°C	61.6°C	6	O/P D100	74.4°C	66.5°C	7	O/P C105	60.2°C	61.5°C	8	CASE	49.6°C	52.0°C		P
NO	Position	1	2																																						
1	I/P C5	54.9°C	57.0°C																																						
2	BD1	53.7°C	59.7°C																																						
3	Q1	69.7°C	71.3°C																																						
4	C40	57.9°C	57.1°C																																						
5	T1	61.4°C	61.6°C																																						
6	O/P D100	74.4°C	66.5°C																																						
7	O/P C105	60.2°C	61.5°C																																						
8	CASE	49.6°C	52.0°C																																						
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P : 230VAC O/P : 100% LOAD Ta= -20°C	TEST : OK	P																																				

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P:230 VAC O/P:100% LOAD Ta=25°C LIFE TIME= 111579HRS I/P:115 VAC O/P:100% LOAD Ta=25°C LIFE TIME= 101964HRS			P
2	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.48 M.T.B.F : 675357HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	PETER CHENG	VINCENT TSENG