



Test Report : GS36x48

AC-DC Industrial Adaptor

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	240 mVp-p (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	70 mVp-p	P
2	VOLTAGE TOLERANCE	-2% ~ +2% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD Ta:25°C	-0.09% ~ +0.19%	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD Ta:25°C	-0% ~ +0%	P
4	LOAD REGULATION	-2% ~ +2% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	-0.09% ~ +0.19%	P
5	SET UP TIME	1000 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	125 mS	P
6	RISE TIME	20 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	20.8 mS	P
7	HOLD UP TIME	15 mS (Min)	I/P:115VAC O/P:FULL LOAD Ta:25°C	17.1 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC ~ 264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	58V ~ 264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	87.5% (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	87.51%	P
4	AVERAGE EFFICIENCY	84.63% (LEVEL V)	I/P:115/230VAC O/P:25%、50%、75%、100% LOAD Ta:25°C	84.84% (115VAC) 86.17% (230VAC)	P
5	AC CURRENT	0.7A (Max)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.68A	P
6	NO LOAD POWER CONSUMPTION	< 0.3W (Max)	I/P:230VAC O/P: NO LOAD Ta:25°C	0.11W	P

7	INRUSH CURRENT	< 60A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	52.1 A	P
8	LEAKAGE CURRENT	< 0.25mA	I/P:240VAC O/P:Min LOAD Ta:25°C	L-FG: 0.02mA N-FG: 0.02mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110% ~ 250%	I/P:230VAC O/P:TESTING Ta:25°C	218% HICCUP MODE RESET : AUTO RECOVER	P
2	OVER VOLTAGE PROTECTION	105% ~ 135%	I/P:230VAC O/P:MIN LOAD Ta:25°C	117% (1N4758A) Clamp by ZENER diode	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE RESET AUTO RECOVER	P

■ SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:4242 VDC/min	I/P-O/P:4242 VDC/min Ta:25°C	I/P-O/P: 0.03uA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:100% LOAD Ta=25°C 2. ROOM AMBIENT BURN-IN : 4HRS I/P:115VAC O/P:100% LOAD Ta=25°C	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>I/P C5</td> <td>72.5°C</td> <td>77.3°C</td> </tr> <tr> <td>2</td> <td>Q1</td> <td>111.4°C</td> <td>114.6°C</td> </tr> <tr> <td>3</td> <td>T1</td> <td>79.6°C</td> <td>80.4°C</td> </tr> <tr> <td>4</td> <td>O/P D100</td> <td>69.1°C</td> <td>72.7°C</td> </tr> <tr> <td>5</td> <td>O/P C105</td> <td>62.9°C</td> <td>65.2°C</td> </tr> </tbody> </table>	NO	Position	1	2	1	I/P C5	72.5°C	77.3°C	2	Q1	111.4°C	114.6°C	3	T1	79.6°C	80.4°C	4	O/P D100	69.1°C	72.7°C	5	O/P C105	62.9°C	65.2°C		P
NO	Position	1	2																										
1	I/P C5	72.5°C	77.3°C																										
2	Q1	111.4°C	114.6°C																										
3	T1	79.6°C	80.4°C																										
4	O/P D100	69.1°C	72.7°C																										
5	O/P C105	62.9°C	65.2°C																										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P : 230VAC O/P : 100% LOAD Ta= -20°C	TEST : OK	P																								

OTHER

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P:230 VAC O/P:100% LOAD Ta=25°C LIFE TIME= 92535HRS I/P:115 VAC O/P:100% LOAD Ta=25°C LIFE TIME= 78898HRS			P
2	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.48 M.T.B.F : 675357HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	PETER CHENG	VINCENT TSENG