



Hangzhou Powerkey Industries and Trade Co., Ltd  
Add: Rm1903,Keda Touzi Bldg, No.555,Xincheng Rd,Binjiang, Hangzhou, China  
Tel: 0086-571-86433485 Fax:0086-571-86433481 P.I.C.: Richard Zeng  
Web: www.fridgtec.com E-mail: sales@fridgtec.com

## Aluminum foil tape

Aluminium tape with annealed aluminium backing (thickness mm 0.150), the product has been developed for realising a highly efficiency heat-exchange between the evaporator and the refrigerator & freezer, the aluminum tape can be with or without removable silicon paper liner.

The aluminum tape widely used in household and electric appliances production, HAVC, package etc.

High tensile strength aluminum foil made from special high quality aluminum foil, coated with aggressive solvent-based acrylic adhesive, which provide strong stickiness, good peel strength, high tensile strength and great ageing resistance, especially very good resistance to low temperatures as well as to the temperatures which are normally reached during the manufacture of refrigerators and freezers

Backing:	aluminium foil
Colour	silver
Adhesive type:	Acrylic
Thickness	0.07~0.15mm ( $\pm 0.005$ )
Tape width	from 25~1000mm standard width: 40, 45, 50, 100mm
Roll length	from 50~200m
Paper core	O.D.76mm
Adhesion	$\geq 12\text{N}/25\text{mm}$
Initial adhesion	$\leq 10\text{cm}/\Phi 11\text{mm}$ steel-ball
Glass transition temperature	- 55° C
Temperature resistance	+ 140° C
Ageing resistance	> 12 months

\* The dimension can vary according to customer's needs and requirements.

### PACKING:

- rolls in carton boxes; carton boxes on pallet

