



HIGH PERFORMANCE CUTTING



## **HD series**

High-definition, maximized productivity, long life consumables

# HD-200/200W/200Pro

# HD-300/300W

- The HD plasma cutting system achieves exceptional consumable life, impressive cutting speed and ultimate cutting quality.
- Designed for heavy duty, high capacity CNC plasma cutting and gouging, The HD series delivers reliable performance across a wide range of industrial application.



## Specifications

System	HD-200/200W/200Pro	HD-300/300W
Input Voltages	380VAC, 3PH, 50Hz/60Hz 400VAC, 3PH, 50Hz/60Hz 220VAC, 3PH, 50Hz/60Hz	380VAC, 3PH, 50Hz/60Hz 400VAC, 3PH, 50Hz/60Hz
Max. Load Power Capacity	40KVA	75KVA
Rated output voltage	50~200VDC	50~200VDC
Max output current	200A	300A
Open circuit voltage (OCV)	430VDC	430VDC
Duty cycle rating	380V/400V: 100% @ 200A, at 40°C (104°F) 220V: 100% @ 200A, at 40°C (104°F)	100% @ 300A, at 40°C (104°F)
Operating temperature	-10 °C~40°C	-10°C~40°C
Torch	TP200, 1.5m	TP200, 1.5m
Dimensions	960*420*1100	1300*800*580
Weight	165KG	256KG
Certifications	CE,ROHS	CE,ROHS
Gas supply		
Plasma gas	Air、O <sub>2</sub> 、N <sub>2</sub>	Air、O <sub>2</sub> 、N <sub>2</sub>
Shield gas	Air、N <sub>2</sub>	Air、N <sub>2</sub>
Supply gas pressure	6.2±0.7Bar	6.2±0.7Bar


## Excellent Cutting Performance

- TOPWELL HD series plasma system provides faster cutting speed to maximize productivity.
- The cutting speed of dross free can reach 1000mm/min for 25mm mild steel.
- With water spray cutting process, the stainless steel and aluminum cutting will be less warping and produce a small heat-affected zone to minimize high-cost secondary operations.
- Designed with 100% duty cycle for the most demanding production environments.
- Designed and tested as the TOPWELL HD series product for superior reliability in the most demanding cutting environments.



## Long-life Consumables

- 12mm mild steel;
- 200A Air/Air;
- 20s duration;
- The number of consumable starts can reach more than 500 times (ISO9013 Range 2).



## Simple Operation:

- User-friendly control system, simple and intuitive operation interface;
- Easy to install, easy to operate, easy to maximize performance;
- Digital control, and advanced diagnostics simplify troubleshooting and service;
- TOPWELL HD series plasma systems deliver the industry's best precision cutting on carbon steel, stainless steel and aluminum;

## Consumables



## Cutting capacity and operating data

		HD200	HD200W	HD200Pro	HD300	HD300W
<b>Capacity</b> carbon steel	Dross free*(Air/Air)	25	25	25	35	35
	CNC pierce	32	32	32	40	40
	Severance	75	75	75	80	80
Stainless steel	CNC pierce	/	20	20	/	25
	Severance	/	64	64	/	75
Aluminum	CNC pierce	/	20	20	/	32
	Severance	/	75	75	/	80
<b>Speed</b> Carbon steel	Book specifications at highest output current	12mm(1/2") 3500mm/min (138ipm)			12mm(1/2") 4000mm/min (157ipm)	
Cut angle	ISO9013 range**	2				
Weldability	Ready to weld					
Process gases by material (plasma/shield)	Carbon Steel	Air/Air	Air/Air	O <sub>2</sub> /Air	Air/Air	Air/Air
	Stainless Steel	/	Air/Air +water spray	N <sub>2</sub> /N <sub>2</sub>	N <sub>2</sub> /N <sub>2</sub>	Air/Air +water spray
	Aluminum	/	Air/Air +water spray	N <sub>2</sub> /N <sub>2</sub>	N <sub>2</sub> /N <sub>2</sub>	Air/Air +water spray
Process amps (cutting)	Not all processes available for all materials	30~200			30~300	

\*Feature and material type can influence dross free performance.

\*\*ISO 9013 is a standard that defines cut quality of thermally cut parts. The lower the range (range 1 is the lowest), the smaller the angle on the cut face. Cut angle in range 4 is better than in range 5.



**HIGH PERFORMANCE CUTTING**

**Web & Mail**

[www.cn-topwell.com](http://www.cn-topwell.com)  
[sales@topwellwelders.com](mailto:sales@topwellwelders.com)

**Phone**

(+86)571-88231791  
(+86)571-88231792