



Zhejiang Fotech International Co., Ltd  
**Material Safety Data Sheet**

**1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION**

**MATERIAL IDENTIFICATION**

MSDS Number: FOTECH005

Formula: C<sub>2</sub>HF<sub>5</sub>

Molecular Weight: 120

**TRADENAMES AND SYNONYMS**

HFC-125

**COMPANY IDENTIFICATION**

**MANUFACTURER/DISTRIBUTOR' NAME**

Zhejiang Fotech International Co., Ltd.

No.139, Renmin West RD., Jinhua, Zhejiang, P.R. China-321000

**PHONE NUMBERS**

Product Information: +86-571-87918266

Medical Emergency: +86-571-87085066

**2. COMPOSITION/INFROMATION ON INGREDIENTS**

**COMPONENTS**

Material: pentafluoroethane

CAS Number: 354-33-6

Purity: 99.8%

**3. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material.

Overexposure may cause dizziness and loss of concentration. At higher levels, CNS



depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides.

## POTENTIAL HEALTH HAZARDS

### SKIN

Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

### EYES

Liquid contact can cause severe irritation and frostbite. Mist may irritate.

### INHALATION

R-125 is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

### INGESTION

Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

### DELAYED EFFECTS

None Known

## 4. FIRST AID MEASURES

### SKIN

Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.



## EYES

Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite, water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

## INHALATION

Immediately remove patient to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention immediately. **DO NOT** give epinephrine (adrenaline).

## INGESTION

Ingestion is unlikely because of the physical properties and is not expected to be hazardous. **DO NOT** induce vomiting unless instructed to do so by a physician.

## ADVICE TO PHYSICIAN

Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

## 5. FIRE-FIGHTING MEASURES

### FLAMMABLE PROPERTIES

<b>FLASH POINT:</b>	Gas, not applicable per DOT regulations
<b>FLASH POINT METHOD:</b>	Not applicable
<b>AUTOIGNITION TEMPERATURE:</b>	>750°C
<b>UPPER FLAME LIMIT (volume % in air):</b>	None*
<b>LOWER FLAME LIMIT (volume % in air):</b>	None*
	*Based on ASHRAE Standard 34 with match ignition
<b>FLAME PROPAGATION RATE (solids):</b>	Not applicable
<b>OSHA FLAMMABILITY CLASS:</b>	Not applicable

### EXTINGUISHING MEDIA

Use any standard agent – choose the one most appropriate for type of surrounding fire (material itself is not flammable)



## UNUSUAL FIRE AND EXPLOSION HAZARDS

R-125 is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources.

Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

## SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### IN CASE OF SPILL OR OTHER RELEASE

(Always wear recommended personal protective equipment.)

Evacuate unprotected personnel. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return until air has been tested and determined safe, including low-lying areas.

## 7. HANDLING AND STORAGE

### NORMAL HANDLING

(Always wear recommended personal protective equipment.)

Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders.

R-125 should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

### STORAGE RECOMMENDATIONS

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect



cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

### PERSONAL PROTECTIVE EQUIPMENT

#### SKIN PROTECTION

Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

#### EYE PROTECTION

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

#### RESPIRATORY PROTECTION

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH approved breathing apparatus or supplied air respirator. For escape: use the former or a NIOSH approved gas mask with organic vapor canister.

#### ADDITIONAL RECOMMENDATIONS

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick drench shower facilities at convenient locations.

### EXPOSURE GUIDELINES

INGREDIENT NAME	ACGIH TLV	OSHA PEL	OTHER LIMIT
Pentafluoroethane	None	None	*1000 ppm TWA (8hr)



- \* = Limit established by National Refrigerants, Inc.  
\*\* = Workplace Environmental Exposure Level (AIHA)  
\*\*\* = Biological Exposure Index (ACGIH)

**OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:**

Hydrogen Fluoride: ACGIH TLV = 3 ppm ceiling

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE:</b>	Clear, colorless liquid and vapor
<b>PHYSICAL STATE:</b>	Gas at ambient temperatures
<b>MOLECULAR WEIGHT:</b>	120
<b>CHEMICAL FORMULA:</b>	CHF <sub>2</sub> CF <sub>3</sub>
<b>ODOR:</b>	Faint ethereal odor
<b>SPECIFIC GRAVITY (water = 1.0):</b>	1.21 @ 21.1°C (70°F)
<b>SOLUBILITY IN WATER (weight %):</b>	Unknown
<b>PH:</b>	Neutral
<b>BOILING POINT:</b>	-48.5°C (-55.4°F)
<b>FREEZING POINT:</b>	Not determined
<b>VAPOR PRESSURE:</b>	180.4 psia @ 70°F 407.7 psia @ 130°F
<b>VAPOR DENSITY (air = 1.0):</b>	4.2
<b>EVAPORATION RATE:</b>	>1 <b>COMPARED TO: CC14 = 1</b>
<b>% VOLATILES:</b>	100
<b>FLASH POINT:</b>	Not applicable

**10. STABILITY AND REACTIVITY**

**NORMALLY STABLE? (CONDITIONS TO AVOID):**

The product is stable.

Do not mix with oxygen or air above atmospheric pressure. Any source of high temperatures, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

**INCOMPATIBILITIES:**

(Under specific conditions: e.g. very high temperatures and/or appropriate pressures) – Freshly abraded aluminum surfaces (may cause strong exothermic reaction). Chemically reactive metals: potassium, calcium, powdered aluminum, magnesium, and zinc.



## HAZARDOUS DECOMPOSITION PRODUCTS:

Halogens, halogen acids and possibly carbonyl halides.

## HAZARDOUS POLYMERIZATION:

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### IMMEDIATE (ACUTE) EFFECTS

LC50: 4 hr. (rat) - > 800,000 ppm / Cardiac Sensitization threshold (dog) 75,000 ppm

### DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS

Teratogenic NOEL (rat and rabbit) – 50,000 ppm

Subchronic inhalation (rat) NOEL – > 50,000 ppm

Chronic NOEL – 10,000 ppm

### OTHER DATA

Not active in four genetic studies

## 12. ECOLOGICAL INFORMATION

### Degradability (BOD)

R-125 is a gas at room temperature; therefore, it is unlikely to remain in water.

### Octanol Water Partition Coefficient

Log Pow = 1.48

## 13. DISPOSAL CONSIDERATIONS

### RCRA

Is the unused product a RCRA hazardous waste if discarded? Not a hazardous waste

If yes, the RCRA ID number is:

Not applicable

### OTHER DISPOSAL CONSIDERATIONS

Disposal must comply with federal, state, and local disposal or discharge laws. R-125 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.



The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

## 14. TRANSPORT INFORMATION

US DOT HAZARD CLASS: US DOT PROPER SHIPPING NAME: Pentafluoroethane  
US DOT HAZARD CLASS: 2.2  
US DOT PACKING GROUP: Not applicable  
US DOT ID NUMBER: UN3220

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

## 15. REGULATORY INFORMATION

### TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Listed on the TSCA inventory  
OTHER TSCA ISSUES: None

### STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME	WEIGHT %	COMMENT
No ingredients listed in this section		

### ADDITIONAL REGULATORY INFORMATION

R-125 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

#### WARNING

**DO NOT** vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. Contains Pentafluoroethane (HFC-125), a greenhouse gas which may contribute to global warming.

### WHMIS CLASSIFICATION (CANADA)



This product has been evaluated in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

## FOREIGN INVENTORY STATUS

EU - EINECS # 2065578

## 16. OTHER INFORMATION

The information given corresponds to the current state of our knowledge and experience of the product, and is not exhaustive. This applies to product that conforms to the specification, unless otherwise stated. In the case of combinations and mixtures one must make sure that no new dangers can arise. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and environment.

Responsibility for MSDS: MSDS Coordinator  
Zhejiang Fotech International Co., Ltd.  
No.139, Renmin West Rd., Jinhua, Zhejiang, P.R. China – 321000  
Telephone: +86-571-87918266

Indicates updated section.

End of MSDS