








Shaanxi Tiangong PTFE & Plastic Material Co.,Ltd.

COMPANY ADDRESS: NO. 368, DAQING ROAD, LIANHU COUNTY XI'AN CHINA

TEL: 0086-029-89549229 FAX: 0086-029-88629271

Item	Picture	Material	Weight	Harness Cradle	Shell color	Venting
SV100		ABS	310 g	4 point woven nylon with LDPE suspension	Red,blue, yellow, accept customized color	Unvented
		HDPE	260 g			
SLT100		ABS	/	4 point woven nylon with LDPE suspension	Red,blue, yellow, accept customized color	Vented
		HDPE	240 g			
SLS100		ABS	360 g	4 point LDPE suspension	Red,blue, yellow, accept customized color	Unvented
		HDPE	/			
SS200		ABS	330 g	8 point woven nylon with LDPE suspension	Red,blue, yellow, accept customized color	Vented
		HDPE	/			
SR200		ABS	304 g	8 point woven nylon with LDPE suspension	Red,blue, yellow, accept customized color	Vented
		HDPE	256 g			
SH200		ABS	302 g	8 point LDPE suspension	Red,blue, yellow, accept customized color	Unvented
		HDPE	242 g			
ST200		ABS	350 g	8 point woven nylon with LDPE suspension	Red,blue, yellow, accept customized color	Vented
		HDPE	/			

FEATURE

Large temperature range from -20°C to 80°C.

Largest front area for any industrial logos.Buckle adjustable system from 55 to 64 cm.

Manufactured from quality ABS or HDPE material.Accept other material customized,such as PC,FRP.