






聚邦助剂
Jubang Auxiliaries

无锡市聚邦助剂有限公司

WUXI JUBANG AUXILIARIES CO., LTD

Product name	Picture	Application
<p>CPE 135a (氯化聚乙烯)</p>		<p>CPE/CM has a various usage. CPE can mix with all kinds of plastics, such as PVC, PP, ABS, CPVC, PE, PC and PVC etc.</p>
<p>PVC resin (聚氯乙烯)</p>		<p>PVC products 65% of consumption in the hard products (including pipes, pipe fittings 15% and 5%, 30%, 8% of plate and plate doors and Windows and profile, etc.) 35% for soft products production.</p>
<p>PVC Stabilizer (复合稳定剂)</p>		<p>It can meet the production requirements of all kinds of non-transparent PVC product, such as wire and cable, profiles, pipes, injection fittings, plates, plastic waving tiles, etc.</p>
<p>Titanium Dioxide (钛白粉)</p>		<p>Widely used in Coatings, plastics, inks, paper, etc.</p>

<p>PE wax (聚乙烯蜡)</p>		<p>PE wax is recommended for all kinds of PVC applications such as PVC window profile, PVC door, PVC fencing, PVC clear film, PVC clear sheet, PVC bottle, PVC foam board etc. as lubricant. Recommended using dosage: 0.3-1.2kg per 100kg PVC resin.</p>
<p>Stearic acid (硬脂酸)</p>		<p>Stearic acid is widely used in PVC plastic pipes, plates, profiles, film manufacturing, rubber industry etc.</p>
<p>Whitening agent (增白剂)</p>		<p>Used for the whitening and brightening of polypropylene plastic, hard PVC, ABS, EVA, polystyrene, Polycarbonate.etc.</p>