

SIMATIC MOBILE PANEL 177 PN W. INTEGRATED ENABLING BUTTON, CONFIGURABLE W. WINCC FLEXIBLE COMPACT VERSION 2005 AND HIGHER OR TIA PORTAL V11 AND HIGHER



Figure similar

Display	
Design of display	STN
Screen diagonal	5.7 in
Number of colors	256
Color type	Colors
Resolution (pixels)	
• Horizontal image resolution	320 Pixel
• Vertical image resolution	240 Pixel
• Resolution (WxH in pixel)	320 x 240
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
• Backlight dimmable	No
Control elements	
Control elements	Keys and Touch
Keyboard fonts	
• Membrane keyboard	Yes
— user-definable label membrane keys	
• Function keys	14 function keys, 8 with LEDs

— Number of function keys	14
— Number of function keys with LEDs	8
• Keys with LED	Yes; 8 with LED
• System keys	Yes
— Number of configurable system keys	14
• Numeric/alphabetical input	Yes / Yes
— hexadecimal keyboard	Yes
• Multi-key operation	Yes
— Number of multi-key operations	2

Touch operation

• Design as touch screen	Yes; analog, resistive
--------------------------	------------------------

Special operator controls

• Stop button	No
• Acknowledgement button	Yes
• Key-operated switch	No
• Illuminated pushbutton	No
• Handwheel	No

Supply voltage

Description	via connection box
Type of supply voltage	DC

Processor

Processor type	RISC 32-bit, 200 MHz
----------------	----------------------

Drives

Diskette drive	No
CD-ROM	No
Hard disk	No

Memory

Type of memory	Flash / RAM
Memory available for user data	2 048 kbyte

Type of output

Info LED	No
Power LED	No
Error LED	No

Interfaces

Interfaces/bus type	1 x RS485, 1 x Ethernet (RJ45)
Number of RS 485 interfaces	1
• Transmission rate, max.	0 Mbit/s
Number of USB interfaces	0
Number of parallel interfaces	0
USB port	No

PC card slot	No
CF card slot	No
Multimedia card/SD card slot	combined
Special interfaces	1 x special interfaces
Industrial Ethernet	
• Industrial Ethernet interface	1 x Ethernet (RJ45)
• Industrial Ethernet status LED	0

Protocols

PROFINET	Yes
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	No
AS-Interface	No

Protocols (Ethernet)

• TCP/IP	Yes
----------	-----

Further protocols

• CAN	No
• INTERBUS	No
• MODBUS	Yes
• Data-Highway	No
• DeviceNet	No
• Local Operating Network	No
• SUCOnet	No
• other bus systems	Yes

Degree and class of protection

Enclosure according to EN 60529	IP65
---------------------------------	------

Standards, approvals, certificates

Certifications	CE, cULus, C-TICK, SIBE
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes

Highest safety class achievable in safety mode

• Performance level according to EN ISO 13849-1:2008	d
--	---

Use in hazardous areas

• cULus Class I Zone 2, Division 2	No
• FM Class I Division 2	No

Ambient conditions

Free fall	
• Fall height, max.	1.5 m
Ambient temperature during operation	

• min.	0 °C
• max.	40 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	80 %

Operating systems	
Operating system	Windows CE

Configuration	
Message indicator	Yes
Alarm logging system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe administration	Yes

Configuration software	
• WinCC flexible Compact	Yes
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes
• WinCC Advanced (TIA Portal)	Yes
• WinCC Professional (TIA Portal)	Yes
• Configuration tool	WinCC flexible Compact Version 2005 or higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Compact
— Version	Version 2005
— Configuration tool	WinCC flexible
— Type	Compact

Languages	
Online languages	
• Number of online/runtime languages	5
Project languages	
• Languages per project	32

Functionality under WinCC (TIA Portal)	
Libraries	Yes
Applications/options	Sm@rtService, Sm@rtAccess
• Pocket Word	No
• Pocket Excel	No
• PDF Viewer	No

• Media Player	No
• SIMATIC WinCC Sm@rtServer	Yes
• SIMATIC WinCC Audit	No
• Connection point identification	Yes
Number of Visual Basic Scripts	No
• Debugging in the simulator	No
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
Message system	
• Number of alarm classes	32
• Number of messages	2 000
• Bit messages	Yes
— Number of bit messages	2 000
• Analog messages	Yes
— Number of analog messages	50
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	No
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Message length (in characters)	80
• Lines	1
• Number of process values per message	8
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Recipe administration	
• Number of recipes	100
• Data records per recipe	200
• Entries per data record	200
• Recipe memory	32 KB integrated Flash, expandable
Variables	
• Number of variables per device	1 024
• Number of variables per screen	50
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes

• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	2,500 text elements
• Number of I/O fields per image	50
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, vector graphics
Complex image objects	
• Status/control	With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, invisible buttons
• Methods	Trend / profile
• Limit value lines	Yes
• Number of bars per chart	5
• Limit value lines	Yes
• Number of visible switches per project	1 000
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	300
• Number of entries per text list	30
• Number of graphics lists per project	100
Archiving	
• Number of archives per device	0
• Message archive	No
• Process value archive	No
• Archiving methods	
— Sequential archive	No
— Short-term archive	No
• Memory location	
— PC card	No
— CF card	No
— USB memory	No
— Ethernet	No
• Data storage format	
— CSV	No
— TXT	No
• Online evaluation	

— using trend curves	No
Security	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Data carrier support	
• PC card	No
• CF card	No
• Diskette drive	No
• Hard disk	No
Transfer (upload/download)	
• Transfer of configuration	Serial, Ethernet, automatic transfer recognition
Process coupling	
• Connection to controller	S7-200, S7- 300/400, Win AC, PC (TCP/IP), SIMOTION, Modicon (Modbus), see the chapter "System interfaces"
• S7-1200	Yes; with restrictions
• S7-1500	Yes; with restrictions
• S7-200	Yes
— PPI (point-to-point)	No
— PPI network	No
— MPI	No
— PROFIBUS DP	No
— Ethernet	Yes
• S7-300/400	Yes
— MPI	No
— PROFIBUS DP	No
— PROFINET	Yes
• LOGO!	No
• SINUMERIK	Yes
• SIMOTION	Yes
• S5	No
— serial	No
— PROFIBUS DP	No
• TI 505	No
• Allen Bradley (EtherNet/IP)	Yes
• Allen Bradley (DF1)	No
• Allen Bradley (DF485)	No
• Mitsubishi (MC TCP/IP)	Yes
• Mitsubishi (FX)	No
• Mitsubishi (MP4)	No
• Telemecanique (ADJUST)	No

• Telemecanique (Uni-Telway)	No
• OMRON (FINS TCP)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus TCP/IP)	Yes
• Modicon (Modbus)	No
• GE-Fanuc (SNP)	No
Functions	
• Key repeat	No
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
• Menu tree editor	No
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	No
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
• Monitoring function for battery and memory	Yes
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	Yes
Peripherals/Options	
Peripherals	Printer
• Printer	Yes
• SIMATIC HMI MM memory card: Multi Media Card	Yes
• SIMATIC HMI SD memory card: Secure Digital memory card	No
• USB memory	No
Mechanics/material	
Type of housing (front)	plastic
Dimensions	
Enclosure diameter	245 mm
Depth of housing	58 mm
Weights	
Weight (without packaging)	1.3 kg
Other	

free hotline	Yes
Warranty period	1 y
last modified:	08.01.2016