

SIMATIC MOBILE PANEL 277F IWLAN USA VERSION, WITH INTEGRATED ENABLING BUTTON AND EMERGENCY-STOP BUTTON, CONFIGURABLE W. WINCC FLEXIBLE STANDARD VERSION 2007 AND HIGHER INCL. 1 MAIN BATTERY POWER SUPPLY TO BE ORDERED SEPARATELY: 6AV6671-5CE00-0AX0 CHARGING ST. 6AV6671-5CN00-0AX1 EXTERNAL POWER SUPPLY UNIT (EU/US/UK/JP)

General information

Customer-specific configuration	Yes
---------------------------------	-----

Display

Design of display	TFT
Screen diagonal	7.5 in
Color display	Yes
Number of colors	65 536

Resolution (pixels)

- | | |
|-------------------------------|-----------|
| • Horizontal image resolution | 640 Pixel |
| • Vertical image resolution | 480 Pixel |

Backlighting

- | | |
|--------------------------------|----------|
| • MTBF backlighting (at 25 °C) | 50 000 h |
|--------------------------------|----------|

Control elements

Control elements	Keys and touch
------------------	----------------

Keyboard fonts

- | | |
|--------------------------------------|-----|
| • Membrane keyboard | |
| — user-definable label membrane keys | Yes |
| • Function keys | |
| — Number of function keys | 18 |
| — Number of function keys with LEDs | 18 |
| • Keys with LED | Yes |
| • Numeric keyboard | Yes |
| • alphanumeric keyboard | Yes |
| • Multi-key operation | Yes |
| — Number of multi-key operations | 2 |

Touch operation

- | | |
|--------------------------|------------------------|
| • Design as touch screen | Yes; analog, resistive |
|--------------------------|------------------------|

Connection type

- | | |
|--|-----------------|
| • Type of connection for mouse/keyboard/barcode reader | USB / USB / USB |
|--|-----------------|

Special operator controls

- Illuminated pushbutton
- Handwheel

No

No

Supply voltage

Design of the power supply	Via charging station or table power supply
Type of supply voltage	DC

Processor

Processor type	ARM, 520 MHz
----------------	--------------

Memory

Type of memory	Flash / RAM
Memory available for user data	6 Mbyte
Capacity of main memory, max.	128 Mbyte

Accumulator

Buffer battery	Yes; Maximum buffer time 5 min
----------------	--------------------------------

Main rechargeable battery

• Rated voltage	7.2 V
• Capacity	5 100 mA·h
• Number of loading cycles, min	500
• Charging time, typ.	4 h
• Operating time, typ.	4 h
• Display for battery capacity	Yes
• Energy-saving mode	Yes
• Battery replacement during operation	Yes

Type of output

Power LED	Yes
LED for safe	Yes
LED for communication	Yes
LED for battery	Yes
Vibrations	Yes

Time of day

Clock	
• Hardware clock (real-time)	Yes
• retentive	Yes; Via bypass battery
• synchronizable	Yes

Interfaces

Interfaces/bus type	1x Ethernet (RJ45)
Number of USB interfaces	1
Number of wireless interfaces	1
Multimedia card/SD card slot	1 MMC/SD card slot

WLAN

• Wireless LAN	Yes
----------------	-----

• Supports rapid roaming	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
Protocols (Ethernet)	
• TCP/IP	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, C-TICK
CE mark	Yes
TÜV safety certification	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	e
• SIL acc. to IEC 61508	SIL 3
Ambient conditions	
Free fall	
• Fall height, max.	1.2 m
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	80 %
Operating systems	
pre-installed operating system	Windows CE
Configuration	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
• Configuration tool	WinCC flexible Standard Version 2007 or higher (to be ordered separately)
Languages	
Online languages	
• Number of online/runtime languages	16

Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Applications/options	Internet Explorer, Sm@rtService, Sm@rtAccess
• Web browser	Yes
• SIMATIC WinCC Sm@rtServer	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
Message system	
• Number of alarm classes	32
• Number of messages	4 000
• Bit messages	Yes
— Number of bit messages	4 000
• Analog messages	Yes
— Number of analog messages	4 000
• System messages HMI	Yes
• System messages PLC	Yes
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	99
• Message indicator	Yes
• First/last value	Yes
Recipe management	
• Number of recipes	300
• Data records per recipe	500
• Entries per data record	1 000
• Recipe memory	64 KB integrated Flash, expandable
Variables	
• Number of variables per device	2 048
• Number of variables per screen	200
• Number of variables	1 000
• Initial values	2 048
• Type Date & Time	2 048
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	

• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	10,000 text elements
• Number of I/O fields per image	200
• Number of date/time fields	200
• Return	Yes
• Graphics object	Bit maps, icons, vector graphics
— Icons	1 000
Complex image objects	
• Status/control	Yes; With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	1 000
— Number of curve diagrams per image	10
• Methods	Trend / profile
• Bar graphs	
— Number of bars per chart	10
• Sliders	
— Number of slides per image	10
• Pointer instruments	
— Number of analog indicators per image	10
• Limit value lines	Yes
• Number of alphanumeric fields	300
— alphanumeric fields per image	200
• Number of numerical fields	2 048
— numerical fields per image	200
• Number of password fields	2 048
• Number of visible switches per project	200
— visible switches per image	200
— hidden switches per image	200
• Number of status switches per project	200
— Number of status switches per image	200
• Number of selector switches per project	200
— Selector switches per image	200
• Number of decade switches per project	200
— Decade switches per image	200
• Number of signal lamps per project	200
— Signal lamps per image	200

Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
Lists	
• Number of text lists per project	500
• Number of text lists per image	200
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
Archiving	
• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods	
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	MultiMediaCard
• Data storage format	
— CSV	Yes
• Online evaluation	
— using trend curves	Yes
Filters	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
Security	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Logging through printer	
• Recording/Printing	Alarms, report (shift report), PROFINET
Transfer (upload/download)	
• Transfer of configuration	USB, Ethernet, automatic transfer recognition
Process coupling	
• Connection to controller	S7-200, S7- 300/400 see section on "System interfaces"
• S7-200	Yes
— Ethernet	Yes

• S7-300/400	Yes
— PROFINET	Yes
Functions	
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
Service tools/configuration aids	
• Clean screen	Yes
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
Peripherals/Options	
Peripherals	
• SIMATIC HMI MM memory card: Multi Media Card	Yes
• SIMATIC HMI SD memory card: Secure Digital memory card	Yes
• USB memory	Yes
Additional software components loadable	Yes
Mechanics/material	
Enclosure material (front)	plastic
Dimensions	
Enclosure diameter	290 mm
Depth of housing	103 mm
Weights	
Weight (without packaging)	2.2 kg
Other	
free hotline	Yes
last modified:	08/06/2019