



X2 marine 7

7" HMI with iX runtime

800 × 480 pixel (16:9) TFT-LCD touch screen
1.5 GB application memory
Ethernet 1x100 Mbit
CE, FCC, KCC, UL approvals
DNV, KR, GL, LR, ABS, CCS marine approvals

Facts

General description

| | |
|-------------|-----------|
| Part number | 630002505 |
| Part status | Active |
| Warranty | 2 year |

Certifications

| | |
|---------|------------------------------|
| General | CE, FCC, KCC, UL 61010-2-201 |
| Marine | DNV, KR, GL, LR, ABS, CCS |

Mechanical

| | |
|-------------------|----------------------------------|
| Mechanical size | 204 x 143 x 50mm |
| Mounting option | Panel Mount, VESA 75 x 75 |
| Number of touches | 1million finger touch operations |
| Touch type | Resistive |
| Cut-out size | 189 x 128mm |
| Weight | 0.8 kg |
| Housing material | Powder-coated aluminum, Black |

Power

| | |
|-------------------------|--|
| Input voltage | 24 V DC (18 to 32 VDC)CE: The power supply must conformwith the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supplymust conformwith the requirements for class II power supplies. |
| Power consumption (max) | 14.4W |
| Input fuse | Internal DC fuse |

System

| | |
|-------|---|
| CPU | i.MX6Solo Single Cortex-A9 1.0GHz 512kB L2cache |
| RAM | 512 MB |
| FLASH | 2GB SSD(eMMC), 1.5GB free for application |

Display

| | |
|----------------------|---|
| Size diagonal | 7" diagonal |
| Resolution | 800x480 pixels |
| Backlight | LED Backlight |
| Backlight life time | 50000 hours |
| Backlight brightness | 500 cd/m2 |
| Backlight dimming | Marine optimized dimming, down to 0,5 cd/m2 |
| Display type | TFT-LCD with LED backlight |

Communication serial

| | |
|------------------------|--------------------------------|
| Number of serial ports | 1 Port 9pin DSUB |
| Serial port 1 | RS 232 (RTS/CTS) |
| Serial port 2 | RS422/485 |
| Serial port 3 | RS485 (only if COM 2 is RS485) |

Ethernet communication

| | |
|--------------------------|---------------------------------|
| Number of ethernet ports | 1 |
| Ethernet port 1 | 1x10/100 Base-T (shielded RJ45) |

Expansion interface

| | |
|----------------|---------------------------|
| Expansion port | Yes, ciX expansion module |
| SD card | SD and SDHC |
| USB | 1xUSB 2.0 500mA |

Environmental

| | |
|-----------------------|---|
| Operating temperature | -10°C to +60°C |
| Storage temperature | -20°C to +70°C |
| Shock | 15g, half-sine, 11ms according to IEC60068-2-27 |
| Vibration | 1g, according to IEC 60068-2-6, Test Fc |
| Sealing front | IP65, NEMA 4X/ 12 and UL Type 4X/ 12 |
| Sealing back | IP20 |
| Humidity | 5% – 85% non-condensed |

Drivers

Everything for your HMI running



Touch.Keypad.Display
✉ sales@vicpas.com
☎ +86-15876525394