

LOGO! TD TEXTDISPLAY, FOR LOGO! ..0BA6 AND ..0BA7, 4 LINES, WITH CABLE (2.5M) AND MOUNTING ACCESSORIES, CONFIGURATION WITH LOGO! SOFT COMFORT V6.0



General information

Suitability for use	Connection to all LOGO! basic units from ..0BA6
---------------------	---

Display

Design of display	STN
-------------------	-----

Line display

- | | |
|---------------------------------|----|
| • Number of lines | 4 |
| • Number of characters per line | 24 |

Backlighting

- | | |
|------------------------|-----|
| • Type of backlighting | LED |
|------------------------|-----|

Control elements

Keyboard fonts

- | | |
|--------------------------------------|-----|
| • System keys | Yes |
| — Number of configurable system keys | 10 |
| • Numeric/alphabetical input | No |
| — alphanumeric keyboard | |

Supply voltage

Type of supply voltage	AC/DC
------------------------	-------

Interfaces

Number of RS 485 interfaces	0
-----------------------------	---

Degree and class of protection

IP (at the front)	IP40
-------------------	------

Ambient conditions

Ambient temperature during operation

• min.	0 °C
• max.	55 °C

Accessories

Function description	Connecting cable length 2.5 m
----------------------	-------------------------------

belongs to product	LOGO!
--------------------	-------

Dimensions

Width	128.2 mm
-------	----------

Height	86 mm
--------	-------

Depth	38.7 mm
-------	---------

Overall depth	38.7 mm
---------------	---------

Weights

Weight, approx.	220 g
-----------------	-------

Scope of supply

Delivery quantity in pieces	1
-----------------------------	---

last modified: 05/23/2017