

LOGO! TD Text Display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8



Figure similar

| General information  |                                     |
|--|-------------------------------------|
| Product type designation   | LOGO! TDE                           |
| Suitability for use  | Can be used with LOGO! 8 and higher |
| Display  |                                     |
| Design of display  | FSTN                                |
| Line display   |                                     |
| <ul style="list-style-type: none"> <li>• Number of lines</li> </ul>  | 6                                   |
| <ul style="list-style-type: none"> <li>• Number of characters per line</li> </ul>  | 20                                  |
| Backlighting   |                                     |
| <ul style="list-style-type: none"> <li>• Type of backlighting</li> </ul>   | LED                                 |
| Control elements   |                                     |
| Keyboard fonts   |                                     |
| <ul style="list-style-type: none"> <li>• System keys</li> </ul>  | Yes                                 |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— Number of configurable system keys</li> </ul> </li> </ul> | 0                                   |
| <ul style="list-style-type: none"> <li>• alphanumeric keyboard</li> </ul>  | No                                  |
| Installation type/mounting   |                                     |

|  |  |
|--|--|
| Wall mounting/direct mounting                          | No   |
| <b>Supply voltage</b>                                  |  |
| Type of supply voltage                                 | AC/DC  |
| Rated value (DC)                                       | 12 V; 12/24 V DC, 24 V AC                                      |
| <b>Power loss</b>                                      |  |
| Power loss, typ.                                       | 1.8 W; At 24 V DC  |
| <b>Interrupts/diagnostics/status information</b>       |  |
| Diagnostic functions                                   | No   |
| <b>Degree and class of protection</b>                  |  |
| IP (at the front)                                      | IP65   |
| <b>Standards, approvals, certificates</b>              |  |
| CE mark  | Yes  |
| UL approval  | Yes  |
| FM approval  | Yes  |
| KC approval  | Yes  |
| Marine approval  |  |
| • American Bureau of Shipping (ABS)                    | Yes  |
| <b>Ambient conditions</b>                              |  |
| Ambient temperature during operation                   |  |
| • min.   | -20 °C; No condensation  |
| • max.   | 55 °C  |
| Ambient temperature during storage/transportation      |  |
| • min.   | -40 °C   |
| • max.   | 70 °C  |
| Altitude during operation relating to sea level        |  |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| <b>Configuration</b>                                   |  |
| Configuration software                                 |  |
| • Configuration tool                                   | LOGO! Soft Comfort V8  |
| <b>Accessories</b>                                     |  |
| belongs to product                                     | LOGO!  |
| <b>Mechanics/material</b>                              |  |
| Design of housing                                      | plastic  |
| <b>Dimensions</b>                                      |  |
| Width  | 128.2 mm   |
| Height   | 86 mm  |
| Depth  | 38.7 mm  |
| Overall depth  | 38.7 mm  |

## Weights

|                 |       |
|-----------------|-------|
| Weight, approx. | 220 g |
|-----------------|-------|

## Scope of supply

|                             |   |
|-----------------------------|---|
| Delivery quantity in pieces | 1 |
|-----------------------------|---|

|                       |            |
|-----------------------|------------|
| <b>last modified:</b> | 01/29/2018 |
|-----------------------|------------|