

LOGO! TD text display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8

| General information                       |                                     |
|---|-------------------------------------|
| Product type designation                  | Text display                        |
| Suitability for use                       | Can be used with LOGO! 8 and higher |
| Display                                   |                                     |
| Design of display                         | FSTN                                |
| Line display                              |                                     |
| • Number of lines                         | 6                                   |
| • Number of characters per line           | 20                                  |
| Backlighting                              |                                     |
| • Type of backlighting                    | LED                                 |
| Control elements                          |                                     |
| Keyboard fonts                            |                                     |
| • System keys                             | Yes                                 |
| — Number of configurable system keys      | 0                                   |
| • alphanumeric keyboard                   | No                                  |
| Installation type/mounting                |                                     |
| Wall mounting/direct mounting             | No                                  |
| Supply voltage                            |                                     |
| Type of supply voltage                    | AC/DC                               |
| Rated value (DC)                          | 12 V; 12/24 V DC, 24 V AC           |
| Power loss                                |                                     |
| Power loss, typ.                          | 1.8 W; At 24 V DC                   |
| Interrupts/diagnostics/status information |                                     |
| Diagnostics function                      | No                                  |
| Degree and class of protection            |                                     |
| IP (at the front)                         | IP65                                |
| Standards, approvals, certificates        |                                     |
| CE mark                                   | Yes                                 |
| UL approval                               | Yes                                 |
| FM approval                               | Yes                                 |
| KC approval                               | Yes                                 |
| Marine approval                           |                                     |
| • American Bureau of Shipping (ABS)       | Yes                                 |

| Ambient conditions                                     |  |
|--|--|
| Ambient temperature during operation                   |  |
| • min.   | -20 °C; No condensation  |
| • max.   | 55 °C  |
| Ambient temperature during storage/transportation      |  |
| • min.   | -40 °C   |
| • max.   | 70 °C  |
| Altitude during operation relating to sea level        |  |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m) |

| Configuration          |                       |
|------------------------|-----------------------|
| Configuration software |                       |
| • Configuration tool   | LOGO! Soft Comfort V8 |

| Accessories        |       |
|--------------------|-------|
| belongs to product | LOGO! |

| Mechanics/material |         |
|--------------------|---------|
| Design of housing  | plastic |

| Dimensions    |          |
|---------------|----------|
| Width         | 128.2 mm |
| Height        | 86 mm    |
| Depth         | 38.7 mm  |
| Overall depth | 38.7 mm  |

| Weights         |       |
|-----------------|-------|
| Weight, approx. | 220 g |

| Scope of supply             |            |
|-----------------------------|------------|
| Delivery quantity in pieces | 1          |
| <b>last modified:</b>       | 10/29/2020 |