



Figure similar

SIMATIC DP, Connection IM 153-1, for ET 200M, for max. 8 S7-300 modules

General information	
Product type designation	IM 153-1 DP ST
Vendor identification (VendorID)	801Dh
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	not necessary
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	5 ms
Input current	
Current consumption, max.	350 mA; At 24 V DC
Inrush current, typ.	2.5 A
I <sup>2</sup> t	0.1 A <sup>2</sup> ·s
output voltage / header	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Addressing volume	
<ul style="list-style-type: none"> <li>Inputs</li> <li>Outputs</li> </ul>	128 byte
	128 byte
Hardware configuration	
Number of modules per DP slave interface, max.	8
Interfaces	
Transmission procedure	RS 485
Transmission rate, max.	12 Mbit/s
1. Interface	
automatic detection of transmission rate	Yes
Interface types	
<ul style="list-style-type: none"> <li>Output current of the interface, max.</li> <li>Design of the connection</li> </ul>	90 mA
	9-pin sub D socket
PROFIBUS DP slave	
<ul style="list-style-type: none"> <li>GSD file</li> </ul>	(for DPV1) SIEM801D.GSD; SI01801D.GSG

• automatic baud rate search	Yes
<b>Protocols</b>	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
<b>PROFIBUS DP</b>	
• Number of node addresses, max.	1 to 125 permitted
<b>Services</b>	
— SYNC capability	Yes
— FREEZE capability	Yes
— Direct data exchange (slave-to-slave communication)	Yes; Sender
<b>Potential separation</b>	
Potential separation exists	Yes
<b>Isolation</b>	
Isolation tested with	Isolation voltage 500 V
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m
<b>configuration / header</b>	
Configuration software	
• STEP 7	STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	117 mm
<b>Weights</b>	
Weight, approx.	360 g
<b>last modified:</b>	4/1/2022 