



SIMATIC S7-300, Digital output SM 322, isolated, 32 DO, 120 V/230 V AC, 1 A, double-width, 2x 20-pole

Figure similar

Supply voltage	
Load voltage L1	
<ul style="list-style-type: none"> Rated value (AC) 	120 V; 120/230 V AC
<ul style="list-style-type: none"> permissible range, lower limit (AC) 	79 V
<ul style="list-style-type: none"> permissible range, upper limit (AC) 	264 V
<ul style="list-style-type: none"> permissible frequency range, lower limit 	47 Hz
<ul style="list-style-type: none"> permissible frequency range, upper limit 	63 Hz
Input current	
from load voltage L1 (without load), max.	10 mA
from backplane bus 5 V DC, max.	190 mA
Power loss	
Power loss, typ.	25 W
Digital outputs	
Number of digital outputs	32
Short-circuit protection	No
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	Size 4 according to NEMA
Zero-crossing switch	Yes; Max. 60 V
Switching capacity of the outputs	
<ul style="list-style-type: none"> on lamp load, max. 	50 W
Output voltage	
<ul style="list-style-type: none"> for signal "1", min. 	L1 (-0.8 V)
Output current	
<ul style="list-style-type: none"> for signal "1" rated value 	1 A
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 40 °C, min. 	10 mA
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 40 °C, max. 	1 A
<ul style="list-style-type: none"> for signal "1" permissible range for 40 to 60 °C, min. 	10 mA
<ul style="list-style-type: none"> for signal "1" permissible range for 40 to 60 °C, max. 	1 A
<ul style="list-style-type: none"> for signal "1" minimum load current 	10 mA
<ul style="list-style-type: none"> for signal "1" permissible surge current, max. 	10 A; per group (for 2 AC cycles)
<ul style="list-style-type: none"> for signal "0" residual current, max. 	2 mA
Output delay with resistive load	
<ul style="list-style-type: none"> "0" to "1", max. 	1 AC cycle
<ul style="list-style-type: none"> "1" to "0", max. 	1 AC cycle
Parallel switching of two outputs	
<ul style="list-style-type: none"> for uprating 	No
<ul style="list-style-type: none"> for redundant control of a load 	Yes; only outputs of the same group

Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. 	10 Hz
<ul style="list-style-type: none"> • with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> • with inductive load (acc. to IEC 60947-5-1, AC15), max. 	0.5 Hz
<ul style="list-style-type: none"> • on lamp load, max. 	1 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	3 A
vertical installation	
— up to 40 °C, max.	4 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	Yes; Fuse blown or load voltage missing
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
<ul style="list-style-type: none"> • Status indicator digital output (green) 	Yes; per channel
Potential separation	
Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels 	Yes
<ul style="list-style-type: none"> • between the channels, in groups of 	8
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes; Optocoupler
Isolation	
Isolation tested with	4 000 V DC
connection method / header	
required front connector	20-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	500 g
last modified:	1/16/2021 