



Figure similar

SIMATIC S7-300, Analog input SM 331, Isolated 8 AI, resolution 13 bits  
U/I/resistor/Pt100, NI100, NI1000, LG-NI1000, PTC/KTY, 66 ms conversion  
time; 1x 40-pole

| Input current   |  |
|---|--|
| from backplane bus 5 V DC, max.                                       | 90 mA                                    |
| Power loss  |  |
| Power loss, typ.  | 0.4 W                                    |
| Analog inputs   |  |
| Number of analog inputs   | 8  |
| • For resistance measurement  | 8  |
| permissible input voltage for voltage input (destruction limit), max. | 30 V; 12 V continuous, 30 V for max. 1 s |
| permissible input current for current input (destruction limit), max. | 40 mA                                    |
| Input ranges  |  |
| • Voltage   | Yes                                      |
| • Current   | Yes                                      |
| • Thermocouple  | No                                       |
| • Resistance thermometer  | Yes                                      |
| • Resistance  | Yes                                      |
| Input ranges (rated values), voltages                                 |  |
| • 0 to +10 V  | Yes                                      |
| — Input resistance (0 to 10 V)  | 100 kΩ                                   |
| • 1 V to 5 V  | Yes                                      |
| — Input resistance (1 V to 5 V)                                       | 100 kΩ                                   |
| • 1 V to 10 V   | No                                       |
| • -1 V to +1 V  | Yes                                      |
| — Input resistance (-1 V to +1 V)                                     | 100 kΩ                                   |
| • -10 V to +10 V  | Yes                                      |
| — Input resistance (-10 V to +10 V)                                   | 100 kΩ                                   |
| • -2.5 V to +2.5 V  | No                                       |
| • -250 mV to +250 mV  | No                                       |
| • -5 V to +5 V  | Yes                                      |
| — Input resistance (-5 V to +5 V)                                     | 100 kΩ                                   |
| • -50 mV to +50 mV  | Yes                                      |
| — Input resistance (-50 mV to +50 mV)                                 | 100 kΩ                                   |
| • -500 mV to +500 mV  | Yes                                      |
| — Input resistance (-500 mV to +500 mV)                               | 100 kΩ                                   |
| • -80 mV to +80 mV  | No                                       |
| Input ranges (rated values), currents                                 |  |
| • 0 to 20 mA  | Yes                                      |
| — Input resistance (0 to 20 mA)                                       | 100 Ω                                    |

|   |  |
|---|--|
| • -10 mA to +10 mA  | No   |
| • -20 mA to +20 mA  | Yes  |
| — Input resistance (-20 mA to +20 mA)                         | 100 Ω  |
| • -3.2 mA to +3.2 mA  | No   |
| • 4 mA to 20 mA   | Yes  |
| — Input resistance (4 mA to 20 mA)                            | 100 Ω  |
| <b>Input ranges (rated values), thermocouples</b>             |  |
| • Type B  | No   |
| • Type C  | No   |
| • Type E  | No   |
| • Type J  | No   |
| • Type K  | No   |
| • Type L  | No   |
| • Type N  | No   |
| • Type R  | No   |
| • Type S  | No   |
| • Type T  | No   |
| • Type U  | No   |
| • Type TXK/TXK(L) to GOST                                     | No   |
| <b>Input ranges (rated values), resistance thermometer</b>    |  |
| • Cu 10   | No   |
| • Ni 100  | Yes; Standard/climate  |
| — Input resistance (Ni 100)                                   | 100 MΩ   |
| • Ni 1000   | Yes  |
| — Input resistance (Ni 1000)                                  | 100 MΩ   |
| • LG-Ni 1000  | Yes; Standard/climate  |
| — Input resistance (LG-Ni 1000)                               | 100 MΩ   |
| • Ni 120  | No   |
| • Ni 200  | No   |
| • Ni 500  | No   |
| • Pt 100  | Yes; Standard/climate  |
| — Input resistance (Pt 100)                                   | 100 MΩ   |
| • Pt 1000   | No   |
| • Pt 200  | No   |
| • Pt 500  | No   |
| <b>Input ranges (rated values), resistors</b>                 |  |
| • 0 to 150 ohms   | No   |
| • 0 to 300 ohms   | No   |
| • 0 to 600 ohms   | Yes  |
| — Input resistance (0 to 600 ohms)                            | 100 MΩ   |
| • 0 to 6000 ohms  | Yes  |
| — Input resistance (0 to 6000 ohms)                           | 100 MΩ   |
| <b>Thermocouple (TC)</b>                                      |  |
| <b>Temperature compensation</b>                               |  |
| — parameterizable   | No   |
| — internal temperature compensation                           | No   |
| — external temperature compensation with compensations socket | No   |
| <b>Characteristic linearization</b>                           |  |
| • parameterizable   | Yes  |
| — for thermocouples   | No   |
| — for resistance thermometer                                  | yes; Pt100 standard/air con.; Ni100 standard/air con.; Ni1000 standard/air con.; LG-Ni1000 standard/air con. |
| <b>Cable length</b>   |  |
| • shielded, max.  | 200 m; max. 50 m at 50 mV  |
| <b>Analog value generation for the inputs</b>                 |  |
| <b>Integration and conversion time/resolution per channel</b> |  |
| • Resolution with overrange (bit including sign), max.        | 13 bit   |
| • Integration time, parameterizable                           | Yes; 60 / 50 ms  |
| • Basic conversion time (ms)                                  | 66 / 55 ms   |

- Interference voltage suppression for interference frequency f1 in Hz

50 / 60 Hz

## Encoder

### Connection of signal encoders

- for voltage measurement Yes
- for current measurement as 2-wire transducer Yes; with external supply
- for current measurement as 4-wire transducer Yes
- for resistance measurement with two-wire connection Yes
- for resistance measurement with three-wire connection Yes
- for resistance measurement with four-wire connection Yes

## Errors/accuracies

### Operational error limit in overall temperature range

- Voltage, relative to input range, (+/-) 0.6 %;  $\pm 0.6$  % ( $\pm 5$  V, 10 V, 1 to 5 V, 0 to 10 V);  $\pm 0.5$  % ( $\pm 50$  mV, 500 mV, 1 V)
- Current, relative to input range, (+/-) 0.5 %;  $\pm 20$  mA, 0 to 20 mA, 4 to 20 mA
- Resistance, relative to input range, (+/-) 0.5 %; 0 to 6 kohms, 0 to 600 kohms
- Resistance thermometer, relative to input range, (+/-) 1 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic); 1.2 Kelvin (Pt100, Ni100, standard)

### Basic error limit (operational limit at 25 °C)

- Voltage, relative to input range, (+/-) 0.4 %; 0.4% ( $\pm 5$  V, 10 V, 1 to 5 V, 0 to 10 V); 0.3% ( $\pm 50$  mV, 500 mV, 1 V)
- Current, relative to input range, (+/-) 0.3 %;  $\pm 20$  mA, 0 to 20 mA, 4 to 20 mA
- Resistance, relative to input range, (+/-) 0.3 %; 0 to 6 kohms, 0 to 600 kohms
- Resistance thermometer, relative to input range, (+/-) 1 Kelvin (Pt100, Ni100, standard); 0.8 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic)

## Interrupts/diagnostics/status information

Diagnostics function No

### Alarms

- Diagnostic alarm No
- Limit value alarm No

### Diagnoses

- Diagnostic information readable No

### Diagnostics indication LED

- Group error SF (red) No

## Potential separation

### Potential separation analog inputs

- between the channels No
- between the channels and backplane bus Yes

## Isolation

Isolation tested with 500 V DC

## connection method / header

required front connector 40-pin

## Dimensions

Width 40 mm  
 Height 125 mm  
 Depth 117 mm

## Weights

Weight, approx. 250 g

last modified: 3/2/2021 