


CP430T-ETH



CP435 T-ETH Control Panel 7" TFT Touch s

General Information

Extended Product Type	CP430T-ETH
Product ID	1SBP260196R1001
ABB Type Designation	CP430T-ETH
EAN	3471522601964
Catalog Description	CP435 T-ETH Control Panel 7" TFT Touch s
Long Description	CP430 T-ETH Control Panel 1 menu 5 defined keys 5.7" TFT Touch screen 64K Colors + Ethernet

Additional Information

ABB Type Designation	CP430T-ETH
Ambient Air Temperature	Operation 0 ... +50 °C Storage -10 ... +60 °C
Battery Information	Button Cell Yes Weight 0.0037 kg Contains Hg <0.001 % Contains Cd <0.002 %
Battery Type	Portable
CN8	85381000
Communication	Depend on Driver
Communication Interface	Ethernet
Communication Speed	4.8 ... 187.5 kBd
Country of Origin	Taiwan, Province Of China (TW)
Customs Tariff Number	85381000
Data Sheet, Technical Information	1SBC159107L0202
Declaration of Conformity - CE	1SBD240515C1000
Display Type	TFT Touch + keys
EAN	3471522601964
Fieldbus Interface Type	Modbus RTUAC500_ModbusASCIIothers (contact us)
Fuse Size	5 x 20_MMTx
Fuse Type	SLEEK.36ESr
Gross Weight	1.34 kg
Instructions and Manuals	1SBC159103M0202
Instructions and Manuals (Part 2)	1SBC159106M0202
Invoice Description	CP435 T-ETH Control Panel 7" TFT Touch s
Made To Order	No
Memory Size User Data	512 kB
Memory Size User Program	4000 kB

CP430T-ETH

Memory Type User Data	512 kilobyte RAM
Memory Type User Program	4 MB ROM
Minimum Order Quantity	1 piece
Mounting Position	0 to 135 °
Mounting Type	Front face
Mounting on DIN Rail	No
Number of Characters Per Line	40
Number of Display Lines	30
Number of Function Keys	5
Number of LEDs	0
Operating Mode	off-lineon-line
Order Multiple	1 piece
	20 V·A
Power Supply	24 V DC
Product Main Type	CP430
Product Name	Control Panel
Product Net Height	145 mm
Product Net Length	60 mm
Product Net Weight	0.86 kg
Product Net Width	195 mm
Product Type	PLC-CP400
Profibus	No
Programming Software	CP400 Soft
Quote Only	No
Real-time Clock	Yes
Release Type	V11.11.10
RoHS Information	1SBD340002R0202
Screen Color	64k colors
Screen Resolution	320 x 240 pixel
Screen Size	4:3 screen 5.7 in
Screen Type	TFT color, CCFL backlight, touch screen
Security	password protection with 9 user levels
Selling Unit of Measure	piece
Serial Port 1 Type	RS232/RS485
Serial Port 2 Type	RS232/RS422/RS485
Service Life	60000 hour
Short Description	CP430 T-ETH Control Panel 5.7" TFT Touch screen
Short-Circuit Protective Devices	gG Type Fuses Integrated
Software Function	alarm managementrecipe managementtrendsmacro & laddersub-screen
Stocked At (Warehouses)	Central Stock Europe
Supply Voltage	20.4 ... 27.6 V DC
UL Certificate	NRAQ.E240320
USB Port 1 Type	Host, version 2.0
USB Port 2 Type	1 Device Ver. 2.0
Viewing Area Height	88.4 mm
Viewing Area Length	117.2 mm
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
cUL Certificate	1SAA960000-1709

—

Categories

PLC Automation → Legacy products → CP400 → Devices

