GE Intelligent Platforms



10" QuickPanel^{+™}

Operator Interface for the Industrial Internet

Streamline your system and simplify development and maintenance with one powerful device for both your operator interface (OI) and control requirements. The QuickPanel⁺, OI for the Industrial Internet, is a multi-functional device that delivers actionable data and insight—smarter, faster and easier than ever before.

QuickPanel⁺ integrates process control, view, and an option to run embedded data historian to improve real-time control and simplify integration into plant-wide systems. The QuickPanel⁺ takes machine interfaces into the Industrial Internet age for new levels of productivity, insight, and user experience.

To succeed in an outcome-driven world, businesses must operate faster and leaner and be increasingly connected. At GE Intelligent Platforms, we understand today's connected business environment, and are committed to simplifying it. That's why we've designed an automation architecture that helps you design better machines and plants, operate them smarter, and redefine the interaction with your equipment.

High Performance

With faster processing speeds and more memory, QuickPanel⁺ delivers high-performance control, visualization, and data historian capabilities to maximize productivity and cost efficiency, even in third-party environments.

QuickPanel⁺ incorporates the latest display and multi-touch technology to enhance the user experience. The capacitive, multitouch screen is built to last in an industrial environment, yet is as sensitive as the latest smartphone or tablet. The wide screen provides vivid, clear images and more complete process visualization. Double-tap or pinch to view your interface at up to 400% and tap twice to return to original size. Swipe to navigate between interactive schematics.

Multi-functional Capability

QuickPanel⁺ provides core capabilities that help users operate in today's connected world. It's an all-in-one OI: an OI/HMI, a PLC/ process controller, machine gateway, and a data historian. This combination puts more data at your fingertips, providing instant insight and control while reducing inventory and TCO. Remote programming technology makes it easy to access user accounts through a single access point. And, a single object-based programming environment means implementation is fast and easy.

Full-Function Browser & Multimedia Access

QuickPanel⁺ offers a fully-functional HTML5 browser and multimedia support with the Windows EC7 operating system. This results in a new level of versatility for an OI. Users can quickly and easily access the Internet or their intranet to view training videos, compile reports or access other critical information.

Interoperability & Flexibility

The plug-and-play interoperability of the QuickPanel⁺ adds to its ease of use and implementation. Using serial and Ethernet connectivity, it can be used with controllers and I/O from multiple vendors for swift and smooth implementation. Enjoy the functionality of a PC—such as remote desktop, web browser, built-in peer networking and FTP and HTTP servers—without the IT headaches.

QuickPanel⁺ supports 5 IEC programming languages: Relay Ladder, Sequential Function Chart, Structured Text, Instruction List, and Function Block Diagram. The operator can select multi-language support when the system is online. Configuration is easy a common database reduces development time by eliminating the need to re-enter tag names, and an extensive library of preconfigured animation objects is provided.





10" QuickPanel⁺ – Operator Interface for the Industrial Internet

Specifications

Processor Node

- Freescale i.MX535 1GHz based on ARM Cortex A8
- 2D/3D Graphics Processing Unit
- 32KB Level 1 Instruction/Data Caches
- 256KB Level 2 Unified Instruction and Data Cache
- NEON SIMD Media Accelerator
- Vector Floating Point Coprocessor

Memory

- 1GB DDR3 SDRAM
- 512MB SLC NAND Flash
- 512KB Battery Backed SRAM

Display

- 10" TFT LCD
- 800 x 600 SVGA Resolution
- Projected Capacitive Display
- Multi-touch (two-point)

Ethernet Port

• 2x 10/100BaseT (RJ-45)

Serial I/O

• 1x RS-232 (5-Pin Connector), 1x RS-485 COM Ports (5-Pin Connector)

USB

- 2x USB 2.0 (Type-A)
- 1x USB 2.0 (Mini Type-B)

Storage

• 1x SD/SDHC Card Slot

Audio

• x1 Line Out (stereo) (3.5mm Jack)

Status Indicators

- Tri-color LED (Amber/Green/Red)
- On-board Buzzer

Operating System

• Microsoft Windows Embedded Compact 7

Power Requirements

+12/24VDC ±20% (3-Pin Connector)

Max power Consumption: 30W

- **Physical Specification**
- External Dimensions: 278(W) x 222(H) x 65(D) mm
 Weight: 2.4Kg

Mounting Option

- Panel Cutout Dimensions: 266(W) x 210(H) mm
- Panel Mount Brackets Included
- Mounting Gasket
- VESA 100

Environmental

- Cooling Methodology: Natural Convection
- Operating Temp: 0°C to +55°C
- Storage Temp: -10°C to +60°C
- Humidity: 85% RH (non-condensing) @ 30°C

Compliance

- UL 60950
- CE (EN 60950-1, EN 61000-6-4, 61000-6-2)
- FCC Part15 Class A
- IP65F (JEM 1030)
- CUL Mark US/CAN Zone 2
- ATEX Zone 2*
- NEMA 4X
- RoHS

* Approval Pending





Ordering Information

IC755CSS10CDA	QuickPanel* View & Control, 10" Color TFT with Multi-touch Projected Capacitive Screen, GE Monogram Bezel, 24 VDC Powered
IC755CBS10CDA	QuickPanel* View & Control, 10" Color TFT with Multi-touch Projected Capacitive Screen, Blank Bezel, 24 VDC Powered
IC755ACC10GAS	QuickPanel* 10" Replacement Gasket
IC755ACC10MNT	QuickPanel* 10" Accessory Kit - Replacement Mounting Clips, Power & Serial Port Connectors
IC755ACC10PRO	QuickPanel ⁺ 10" Replacement Screen Protectors, Package of 3
IC755ACCBATTNL	Replacement Battery (No Leads), for use with 10", 12", and 15"