

SIEMENS

Product data sheet

6FX2007-1AC14


Abb. ähnlich

SINUMERIK FM-NC/840D/810D HAND-HELD UNIT B-MPI CABLE 10 M,
2 EMERGENCY-STOP CHANNELS,
2 PERMISSIVE SWITCH CHANNELS, 3 STEPS

power consumption / max.	6 W
Current consumption / without load max.	250 mA
relative humidity	
• storage	5 ... 95% at 25 °C
• operation	5 ... 80% at 25 °C
ambient temperature	
• when stored	-20 ... +60 °C
• when transported	-20 ... +60 °C
ambient temperature	
• during operation	0 ... 45 °C
scanning frequency / max.	2 kHz
cable length / to sequence electronics / max.	200 m
dimension	
• width	114 mm
• height	110 mm

• depth	250 mm
Length	252 mm
• of the housing	252 mm
weight / approx.	1.4 kg

Weitere Informationen

[Informations- und Downloadcenter der Industrie Automation und Antriebstechnik](#)

[Technische Dokumentation \(Motion Control\)](#)

[Industry Mall \(Online-Bestellsystem\)](#)

[Service & Support \(FAQs, Handbücher, Betriebsanleitungen, Zertifikate, Kennlinien, ...\)](#)

letzte Änderung:

Mar 3, 2014