Catalogue No: **6176M-19VT**

VICPAS

INDUSTRIAL MONITOR STD 1950M 19in TOUCH VESA MOUNT

Automation Systems > Operator Panels and Industrial Computers > Industrial Computers > Allen-Bradley® Industrial Computers > Industrial Monitors > 6176M Industrial Standard Monitors





1950M STANDARD MONITOR 19in TOUCH VESA MOUNT

- Industrial Environment Computers offer solutions for the physical limitations and requirements of your environment.
- Non-display Computers provide a variety of options in form factors, RAM, storage, performance, operating temperatures and optical drives.
- Integrated Display Computers are available in different screen sizes, storage options, performance packages, and models with built-in keypads.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS		
Product Series	6176M	
Power Supply	90-264V AC	
Component Type Ind. Computer	Industrial Monitor	
Operator Input Method(s)	Monitor	
Display Size	19 inches	
Display Technology	LCD, TFT (Thin Film Transistor)	
Display Resolution	1280x1024 pixels	
Display Colours	16700 k	
Display Brightness	300 cd/m2	
Display Backlight Life	50000 hours	
Touch Screen Type	Resistive	
Material, Bezel	Plastic	
Peripheral I/O Interface(s)	2 x USB 2.0 1 x DVI-D 1 x VGA	
Height, Cutout	363.5 mm	
Width, Cutout	449.6 mm	
IP Rating, Front	IP66	
Communication Port(s)	D-sub 9 Socket	
Mounting (Multiple)	VESA Mount	
NEMA Enclosure Class (NEMA 250:2003)	Type 1 Type 12 Type 4	
Operating Temperature, Max	45 °C max	
Operating Temperature, Min	0 °C min	
Storage Temperature, Max	60 °C max	
Storage Temperature, Min	-20 °C min	
Relative Humidity, Max	90 %RH	
Shock Acceleration (Max.)	15 g	

Catalogue No: 6176M-19VT

VICPAS HMI Parts Center

INDUSTRIAL MONITOR STD 1950M 19in TOUCH VESA MOUNT



Automation Systems > Operator Panels and Industrial Computers > Industrial Computers > Allen-Bradley® Industrial Computers > Industrial Monitors > 6176M Industrial Standard Monitors

Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	1 m/s²
Vibration Frequency, Operational (Max.)	500 Hz
Certifications	CE C-Tick C-UL

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	Selection Guide

