

SIMATIC S7-200, DIGITAL I/O EM 223, FOR S7-22X CPU ONLY, 8 DI DC 24 V, SINK/SOURCE, 8 DO DC 24V, 0.75A/POINT SOURCE



Figure similar

Supply voltage

Load voltage L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V

Input current

from backplane bus 5 V DC, max.	80 mA
---------------------------------	-------

Power losses

Power loss, typ.	3 W
------------------	-----

Digital inputs

Number of digital inputs	8
--------------------------	---

Input voltage

• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	15V DC to 30V DC

Input current

• for signal "1", typ.	4 mA
------------------------	------

Input delay (for rated value of input voltage)

for standard inputs	
— at "0" to "1", max.	4.5 ms

Digital outputs

Number of digital outputs	8
---------------------------	---

short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "0", max.	0.1 V
• for signal "1", min.	20 V
Output current	
• for signal "1" rated value	750 mA
Aggregate current of outputs (per group)	
all mounting positions	
— Current per conductor/group, max.	3 A
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	0.75 A; per output
— on lamp load, max.	5 W
— with resistive load, max.	0.75 A; per output
Cable length	
• shielded, max.	500 m
• Unshielded, max.	150 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— Permissible quiescent current (2-wire sensor), max.	1 mA
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	Yes; Optocoupler
• between the channels, in groups of	4
Potential separation digital outputs	
• Potential separation digital outputs	Yes; Optocoupler
• between the channels, in groups of	4
Isolation	
Isolation checked with	500 V AC
Connection method	
Plug-in I/O terminals	Yes
Dimensions	
Width	71.2 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	200 g

last modified:

20.04.2015