

SIMATIC S7-200, T/C INPUT MOD. EM 231, FOR S7-22X CPU ONLY, 4 AI, +/-80 MV AND THERMOCOUPLE TYPE J,K,S,T,R,E,N; 15BIT+VORZ.



Figure similar

Input current	
from load voltage L+ (without load), max.	60 mA
from backplane bus 5 V DC, max.	87 mA
Power loss	
Power loss, typ.	1.8 W
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V
Loop resistance cable	100 Ω
Updating time (all channels)	405 ms
Input ranges	
• Voltage	Yes
• Current	No
• Thermocouple	Yes
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	

• -80 mV to +80 mV	Yes
• Input resistance (-80 mV to +80 mV)	1 MΩ
Input ranges (rated values), thermocouples	
• Type E	Yes
• Input resistance (Type E)	1 MΩ
• Type J	Yes
• Input resistance (type J)	1 MΩ
• Type K	Yes
• Input resistance (Type K)	1 MΩ
• Type N	Yes
• Input resistance (Type N)	1 MΩ
• Type R	Yes
• Input resistance (Type R)	1 MΩ
• Type S	Yes
• Input resistance (Type S)	1 MΩ
• Type T	Yes
• Input resistance (Type T)	1 MΩ
Cable length	
• shielded, max.	100 m; to the sensor
Analog value generation	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; Temperature 0.1 °C / 0.1 °F
• Interference voltage suppression for interference frequency f1 in Hz	85 dB at 50 / 60 / 400 Hz
Displayable conversion value range	
• bipolar signals	-27.648 to +27.648
Errors/accuracies	
cold connection point	+/-1,5 °C
Repeat accuracy in steady state at 25 °C (relative to input area), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Voltage, relative to output area, (+/-)	0.1 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
• Common mode voltage, max.	120 V; AC
• Common mode interference, min.	120 dB; At 120 V DC
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• external fault EXTf (red)	Yes
• Group error SF (red)	Yes

Potential separation

Potential separation analog inputs

- Potential separation analog inputs Yes

Permissible potential difference

Between the inputs and MANA (UCM)	500 V AC
between M internally and the inputs	500 V AC

Connection method

Plug-in I/O terminals	No
-----------------------	----

Dimensions

Width	71.2 mm
Height	80 mm
Depth	62 mm

Weights

Weight, approx.	210 g
-----------------	-------

last modified: 31.07.2015