

SIMATIC S7-200 SMART, CPU SR30, Standard CPU, AC/DC/relay, onboard I/O: 18 DI 24 V DC; 12 DO relay 2A; Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 30 KB



General information	
Product type designation	CPU SR30 AC/DC/Relay
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 Micro/WIN SMART
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Supply voltage	
Type of supply voltage	85V to 264VAC
Rated value (DC)	
<ul style="list-style-type: none"> <li>24 V DC</li> </ul>	No
Rated value (AC)	
<ul style="list-style-type: none"> <li>120 V AC</li> </ul>	Yes
<ul style="list-style-type: none"> <li>230 V AC</li> </ul>	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Reverse polarity protection	Yes
Line frequency	
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>	47 Hz

- permissible range, upper limit

63 Hz

### Input current

Current consumption (rated value)	72 mA; at 240 V AC
Current consumption, max.	136 mA; At 120 V DC
Inrush current, max.	8.9 A; at 264 V

### Output current

Current output, max.	300 mA; 24 V DC Sensor Power
for backplane bus (5 V DC), max.	1.4 A; max. 5 V DC for EM bus

### Power loss

Power loss, typ.	10 W; Typical
Power loss, max.	14 W; max.

### Memory

Type of memory	DDR
Flash	Yes
RAM	Yes
Memory available for user data	12 kbyte
Memory size	18 kbyte; Program memory
Micro Memory Card	Yes; microSDHC Card (optional)

### CPU processing times

for bit operations, typ.	150 ns; / instruction
for word operations, typ.	1.2 $\mu$ s; / instruction
for floating point arithmetic, typ.	3.6 $\mu$ s; / instruction

### Address area

I/O address area	
• Inputs	144 byte; 256 bit of digital inputs & 56 words of analog inputs
• Outputs	144 byte; 256 bit of digital outputs & 56 words of analog outputs

### Time of day

Clock	
• Type	Hardware clock, no battery backup
• Hardware clock (real-time)	Yes
• Backup time	7 d
• Deviation per day, max.	4 s; within 120s/month at 25 °C

### Digital inputs

Number of digital inputs	18
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	< 5 V DC
• for signal "1"	+15 to +30V

<b>Input current</b>	
• for signal "1", typ.	4 mA
<b>Cable length</b>	
• shielded, max.	500 m; 50m shielded for HSC inputs
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	12; Relays
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	2 A
• on lamp load, max.	30 W; 30 W with DC, 200 W with AC
<b>Relay outputs</b>	
• Number of relay outputs	12
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Interfaces</b>	
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	1
<b>1. Interface</b>	
Interface type	Ethernet
Physics	RJ45
Isolated	Yes; Transformer isolated, 1,500V AC
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
<b>2. Interface</b>	
Interface type	RS 485 (max. 187.5 Mbit/s)
<b>Communication functions</b>	
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes
<b>Test commissioning functions</b>	
<b>Forcing</b>	
• Forcing	Yes
<b>Integrated Functions</b>	
Number of counters	4; 4 HSC at 200 kHz for single phase or 2 HSC at 100 kHz for A/B phase

PID controller	Yes; PID closed-loop control function blocks: Continuous controller outputs, binary controller outputs, automatic/manual mode, setpoint limitation
----------------	--

## EMC

### Interference immunity against discharge of static electricity

<ul style="list-style-type: none"> <li>• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 <ul style="list-style-type: none"> <li>— Test voltage at air discharge</li> <li>— Test voltage at contact discharge</li> </ul> </li> </ul>	<p>Yes</p> <p>8 kV</p> <p>4 kV</p>
---	------------------------------------

### Interference immunity against high-frequency electromagnetic fields

<ul style="list-style-type: none"> <li>• Interference immunity against high-frequency radiation acc. to IEC 61000-4-3</li> </ul>	Yes; 10 V/m, 80 to 1 000 MHz (to IEC 61000-4-3); 10 V/m, 900 MHz, 1.89 GHz, 50% ED (to IEC 61000-4-3)
--	---

### Interference immunity to cable-borne interference

<ul style="list-style-type: none"> <li>• Interference immunity on supply lines acc. to IEC 61000-4-4</li> <li>• Interference immunity on signal cables acc. to IEC 61000-4-4</li> </ul>	<p>Yes; 2 kV acc. to IEC 61000-4-4, burst</p> <p>Yes; ±2 kV acc. to IEC 61000-4-4, Burst</p>
---	--

### Interference immunity against conducted variable disturbance induced by high-frequency fields

<ul style="list-style-type: none"> <li>• Interference immunity against high frequency current feed acc. to IEC 61000-4-6</li> </ul>	Yes; 10 V, 150 kHz to 80 MHz (to IEC 61000-4-6)
---	---

### Emission of radio interference acc. to EN 55 011

<ul style="list-style-type: none"> <li>• Limit class A, for use in industrial areas</li> </ul>	Yes; EN 61000-6-4, interference emission: Intended for use in industrial areas.
--	---

### Emission of conducted and non-conducted interference

<ul style="list-style-type: none"> <li>• Interference emission via line/AC current cables</li> </ul>	EN 61000-6-4, interference emission: Intended for use in industrial areas.
--	--

## Degree and class of protection

Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> <li>• IP20</li> </ul>	Yes

## Standards, approvals, certificates

CE mark	Yes
---------	-----

## Ambient conditions

### Free fall

<ul style="list-style-type: none"> <li>• Fall height, max.</li> </ul>	0.3 m; five times, in product package
---	---------------------------------------

### Ambient temperature during operation

<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	<p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>45 °C</p>
--	--

### Ambient temperature during storage/transportation

• min.	-40 °C
• max.	70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
<b>Altitude during operation relating to sea level</b>	
• Installation altitude, min.	-1 000 m
• Installation altitude, max.	2 000 m
<b>Relative humidity</b>	
• Operation at 25 °C without condensation, max.	95 %

<b>Configuration</b>	
<b>Programming</b>	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes

<b>Dimensions</b>	
Width	110 mm
Height	100 mm
Depth	81 mm

<b>Weights</b>	
Weight, approx.	435 g
<b>last modified:</b>	09/10/2018