

SIMATIC S7-200 SMART, Digital I/O SM DT16, 8DI/8DO, 8 DI 24 V DC, Sink/Source, 8 DO, Transistor 0.75A



## General information

Product type designation	SM DT16, DI 8x24 V DC, DQ 8x24 V DC/0.75 A
--------------------------	--

## Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

## Input current

from backplane bus 5 V DC, typ.	115 mA; For 5 V DC from CPU module
---------------------------------	------------------------------------

## Digital inputs

Number of digital inputs	8
• in groups of	2
Parallel switching of inputs	Yes
Input characteristic curve in accordance with IEC 61131, type 1	Yes

## Number of simultaneously controllable inputs

horizontal installation	
— up to 50 °C, max.	8
vertical installation	

— up to 40 °C, max.	8
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	< 5 V DC
• for signal "1"	+15 to +30 V
<b>Input current</b>	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", min.	2.5 mA
• for signal "1", max.	5 mA
• for signal "1", typ.	4 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— at "0" to "1", max.	200 µs
— at "1" to "0", max.	200 µs
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	8
• in groups of	2
Current-sinking	No
Current-sourcing	Yes
Short-circuit protection	No
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	0.75 A
• on lamp load, max.	5 W
<b>Output voltage</b>	
• Rated value (DC)	24 V
• for signal "0", max.	0.1 V
• for signal "1", min.	20 V
• for signal "1", max.	28.8 V; max. value is equal to feed L+
<b>Output current</b>	
• for signal "1" rated value	0.75 A
<b>Output delay with resistive load</b>	
• "0" to "1", max.	50 µs
• "1" to "0", max.	200 µs
<b>Parallel switching of two outputs</b>	
• for logic links	Yes; only outputs of the same group
• for uprating	Yes; possible (only outputs of the same group)
• for redundant control of a load	Yes; only outputs of the same group

Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	3 A
horizontal installation	
— up to 50 °C, max.	3 A
vertical installation	
— up to 40 °C, max.	3 A
all other mounting positions	
— up to 40 °C, max.	3 A
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• for status of the inputs	Yes
• for status of the outputs	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	Yes; Optocoupler
Potential separation digital outputs	
• between the channels	Yes; Optocoupler
Isolation	
Isolation tested with	500V AC for 1 minute
EMC	
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-3	
— Frequency range of the RF radiation	80 to 1000 MHz, 10 V/m, 1.4 to 2.0 GHz, 3 V/m, 2.0 to 2.7 GHz, 1 V/m (In the range of 87 MHz to 187 MHz, 174 MHz to 230 MHz and 470 MHz to 790 MHz: 3V/m )
Interference immunity against voltage surge	
• asymmetric interference	
— Test voltage on supply cables	2 kV
— Test voltage on signal cables >30m	2 kV
Interference immunity against conducted variable disturbance induced by high-frequency fields	
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-6	Yes; 10 V/m, with 80% amplitude modulation at 1 kHz
— Test voltage at 80% amplitude modulation with 1kHz in the range 9 kHz to 80 MHz	10 V
Emission of radio interference acc. to EN 55 011	
• Emission of radio interference	Interference emission to EN 50081-2, testing to EN 55011, Class A, Group 1
• Limit class A, for use in industrial areas	Yes
Degree and class of protection	

Degree of protection acc. to EN 60529	
• IP20	Yes
<b>Dimensions</b>	
Width	45 mm
Height	100 mm
Depth	81 mm
<b>Weights</b>	
Weight, approx.	179.7 g
<b>last modified:</b>	04/09/2020